

Location At your side. At your side. R

intellifAX²-HOME/OFFICE PLAIN PAPER FAX

PHONE & COPIER

Featuring...

- 10 page auto document feeder
- 100 sheet paper cassette
- Easy to change replacement print cartridge prints up to 250 pages
- 512KB memory stores up to 25 pages* for out-of-paper
- Quick Scan faxes for memory transmittal
- 58 station auto dialing
- Multi-copying up to 99 copies, plus sorting, enlargement and reduction
- Broadcasting to up to 58 locations
- Call Waiting/Caller ID and Distinctive Ring Detection ready**
- Navigation keys for menus, options and index dialing
- 64 Shade Gray Scale for Photograph Transmission
- Automatically receives fax and voice calls on the same phone line
- Fax Forwarding, Paging and Remote Retrieval
- Copy Enlargement to 150%, Reduction to 50%
- Search stored Auto Dial numbers alphabetically
- Includes special offer from CallManage™ providing "One-Touch" access to Internet calling and faxing †



Easy to change

drop-in printing

cartridge





- **Electronic Cover Page**
- Multiple Resolution Transmission sends individual pages with different resolutions, all in a single transmission
- Enhanced Remote Activation enables you to transfer a fax call from any single line phone extension in the house
- "Smoothing" Enhanced Image Resolution
- **Answering Machine Interface**
- Polling and Delayed Transmission
- Error Correction Mode (ECM)
- Auto reduction of incoming faxes



- Using ITU-T Test Chart #1 at standard resolution in error correction mode
- Sold separately. This model is packaged for sale with a starter print cartridge yielding approximately 30 pages
- Contact local phone company for availability of these services.
- Requires change of carrier to CallManage, Inc. This feature may not be available in some parts of the USA and is not available in Canada. Brother International Corp. is not responsible for long distance services or customer billing. See complete terms and conditions inside Owner's Manual.

PRODUCT SPECIFICATIONS

Approved: UL and FCC Unit Dimensions: 13.3" x 12" x 7.2" Unit Weight: 9.5 lbs. Carton Dimensions: 17.1" x 15" x 10" Carton Weight: 13.2 lbs. UPC Code: 0 12502 60055 8 Compatibility: Group 3 ITU-TS

Coding Method: MH

Modulation: 9600/7200/4800/2400 bps Transmission Time: 15 seconds (8.5" x 11")*

Original Input Width: 5.8" to 8.5" Recording Paper Size: 8.5" x 11"/8.5" x 14"

Effective Scanning/ Printing Width: 8.2"

Resolution: Standard: 203 x 98 lines/inch Fine Mode: 203 x 196 lines/inch Super Fine: 203 x 392 lines/inch

Display: LCD, 16 characters

Dialing System: Tone Speaker Type: Monitor Communication Source: Public Switched

Telephone Network

Communication USOC RJ11C Modular Jack Requirements: (or equivalent)

Power Supply: 120V, 50/60Hz Power Consumption: Standby: Under 5W Peak: Under 170W

Operating Environment: 41° to 95° (F)

OPTIONAL ACCESSORIES*

PC301: Replacement Printing

Cartridge

PC302RF: 2 Refill Rolls for PC301

PC304RF: 4 Refill Rolls for PC301 (USA only)

* Requires additional purchase



