

Ariston GL2.5; GL4; GL6+

Electric point-of-use water heaters

GL2.5 for 1 sink; GL4 for 2 sinks; GL6+ for 2 or more sinks.



Features

- Glass-lined tank for longer life
- 6-year warranty on tank
- All models plug into standard 120-volt outlet
- Easy installation
- Temperature/pressure relief valve included
- GL6+ model can be mounted horizontally or vertically
- Meets ASHRAE 90.1 standard
- · Mounts on wall or floor
- Three sizes to choose from
- Elegant Italian design



Technical Specifications			
ARISTON	GL2.5	GL4	GL6+
Tank Volume	2.75 gallons	3.85 gallons	7.0 gallons
Dimensions	13¾" x 13¾" x 10¾"	13¾" x 13¾" x 13½"	17½" x 17½" x 14½"
Voltage	120V	120V	120V
Amperage	12 amps	12 amps	12 amps
Wire Type	Plug-in	Plug-in	Hardwired
Heating Capacity	1440 watts	1440 watts	1440 watts
Recovery at 90°F Rise	6.8 gph	6.8 gph	6.8 gph
Temperature Range	65-145°F	65-145°F	65-145°F
Water Connections	½" NPT	½" NPT	3⁄4" NPT
Operating Pressure	150 PSI	150 PSI	150 PSI
Relief Valve	Installed	Installed	Included






gph: gallons per hour

No waiting for hot water

Every year billions of gallons of water are wasted turning on the faucet and waiting for hot water to arrive. Save water by installing an Ariston under the sink and eliminate the wait for hot water to reach the tap without the need to install costly recirculating lines and pumps.





Bosch Thermotechnology Corp. 50 Wentworth Ave Londonderry, NH 03053

Telephone: 1-866-798-8161 www.efficientelectricwaterheaters.com