

Ariston GL2.5; GL4; GL6+

Electric point-of-use water heaters

GL2.5 for 1 sink; GL4 for 2 sinks; GL6+ for 2 or more sinks.

Features

- · Glass-lined tank for longer life
- 6-year warranty on tank
- All models plug into standard 120-volt outlet
- Easy installation
- Temperature/pressure relief valve included
- GL6+ model can be mounted horizontally or vertically
- Meets ASHRAE 90.1 standard
- Mounts on wall or floor
- Three sizes to choose from
- Elegant Italian design



Technical Specifications			
ARISTON	GL2.5	GL4	GL6+
Tank Volume	2.75 gallons	3.85 gallons	7.0 gallons
Dimensions	13 ¾" x 13 ¾" x 10 ¼"	13 ¾" x 13 ¾" x 13 ½"	17 ½" x 17 ½" x 14 ½"
Voltage	120V	120V	120V
Amperage	12.5 amps	12.5 amps	12.5 amps
Wire Type	Plug-in	Plug-in	Plug-in
Heating Capacity	1500 watts	1500 watts	1500 watts
Recovery at 90°F Rise	7 gph	7 gph	7 gph
Temperature Range	65-145°F	65-145°F	65-145°F
Water Connections	½" NPT	½" NPT	34" NPT
Operating Pressure	150 PSI	150 PSI	150 PSI
Relief Valve	Installed	Installed	Included








gph: gallons per hour

Easy Installation

Simply tap into the cold water line and install the water heater directly at the sink. All models plug into a standard 120 volt outlet. And when you want to eliminate the wait for hot water but need more volume, install the Ariston water heater in-line with a larger hot water source.





Bosch Thermotechnology Corp. 340 Mad River Park Waitsfield, VT 05673

Telephone: 1-866-642-3199 www.boschhotwater.com