



PR1000LCDRTXL2U Smart App Sinewave UPS

Cost-effective feature-rich power protection for networking, servers and telecommunications equipment.

The CyberPower Smart App Sinewave PR1000LCDRTXL2U uninterruptible power supply (UPS) with LCD panel and pure sine wave output is Active PFC compatible for safeguarding mission-critical servers, telecom equipment, and VoIP and internetworking hardware that require seamless pure sine wave power.

The PR1000LCDRTXL2U allows for the addition of up to five (5) BP48V45ART2U external battery packs to increase the runtime of the unit.

This UPS unit incorporates microprocessor-based digital control and includes PowerPanel® Business Edition Software providing the user unsurpassed flexibility and control.

This UPS system is ENERGY STAR® qualified with patented GreenPower UPS™ Bypass circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$400,000 Connected Equipment Guarantee.

Typical Applications

- Servers
- Workstations
- Network Devices
- Telecom Equipment

Features

- 1000VA / 900W
- Line-Interactive Topology
- Full AVR Buck/Boost
- GreenPower UPS™
- 2U Rack Mount/Tower Convertible
- Multifunction Rotatable LCD
- SNMP/HTTP Remote Management
- 8 Outlets / USB, Serial, and EPO Ports
- EMI/RFI Filters
- PowerPanel® Business Software
- 3-Year Warranty

PR1000LCDRTXL2U Smart App Sinewave UPS

Cost-effective feature-rich power protection for networking, servers and telecommunications equipment.

GENERAL	
UPS Topology	Line-Interactive
Energy Saving	GreenPower UPS™ Bypass Technology
ENERGY STAR® Qualified	Yes
Active PFC Compatible	Yes
INPUT	
Voltage	Nominal 120V
Frequency	47Hz - 63Hz (auto-sensing)
Input Voltage Range	80Vac - 150Vac
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45 Degree Offset Right
Cord Length	10'
OUTPUT	
VA	1,000
Watts	900
Automatic Voltage Regulation	Boost 1 +30%-Boost 2 +14% / Buck -12%
On Battery Voltage	120Vac ± 5%
On Battery Frequency	50/60Hz ± 0.1Hz
On Battery Waveform	Sine Wave
Outlet Type	NEMA 5-15R
Outlets - Total	8
Outlets - Critical Load	4
Outlets - Battery & Surge Protected	8
Outlets - Surge-Only Protected	0
Rated Power Factor	0.9
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms
BATTERY	
Runtime at Half Load (min)	23
Runtime at Full Load (min)	9
Battery Type	Sealed Lead-Acid
Battery Size	12V/7AH
Hot-Swappable	Yes
Battery Quantity	4
User Replaceable	Yes
Typical Recharge Time	Less than 6 Hours (90% charged)
Extended Runtimes Available	Yes, with optional BP48V45ART2U Battery Pack
SURGE PROTECTION & FILTERING	
Surge Suppression	2,060 Joules
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS	
Multifunction LCD Panel	Load/Current Level, Runtime, Battery Level, Temperature (F & C), Battery In Use, Input Voltage, Output Voltage, Output Frequency, Overload, Wiring Fault, Battery Shutdown Voltage, Static Frequency Tolerance, Slew Rate, Silent Mode, Normal Mode
HID Compliant USB Port	Yes
Serial Port	Yes
Emergency Power Off (EPO) Port	Yes
Contact Closure	Yes
Management Cable	USB Cable, Serial Cable, EPO Cable
LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload
Software	PowerPanel® Business Edition
SNMP / HTTP Remote Monitoring	Yes, with optional RMCARD202 or RMCARD302
PHYSICAL	
Rack Size	2U
Form Factor	Rack/Tower
Dimensions (WxHxD) (in.)	17.25 x 3.5 x 15.75
Weight (lbs.)	54.0
Shipping Dimensions (WxHxD) (in.)	22 x 9.8 x 20.5
Shipping Weight (lbs.)	61
ENVIRONMENTAL	
Operating Temperature	32 °F to 104 °F / 0 °C to 40 °C
Operating Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45 °C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL1778, CSA C22.2 NO.1073, FCC DOC Class A
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$400,000