







ENERGY-SAVING ECO MODE

Ecologic UPS systems offer energy-conserving ECO Mode functionality with surge protected ECO outlets. When the ECO Mode outlets are activated and the computer is connected to the UPS, the UPS can detect when the connect computer is off or in Sleep mode. The UPS will then safely remove power to the ECO outlets, shutting down connected devices, which reduces power usage and provides energy cost savings.

Ecologic Series EC850LCD

Offering advanced energy-saving battery backup and surge protection against power surges and interruptions.

The CyberPower Ecologic EC85OLCD UPS safeguards PCs and other electronics from blackouts, brownouts, surges, spikes, sags, and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection. Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs and is an ENERGY STAR® listed product. The multifunction diagnostic LCD provides users the ability to check UPS operating status and assist in trouble-shooting power anomalies.

The CyberPower EC85OLCD has three surge protected ECO outlets. When ECO mode is on and the battery backup detects that your computer is off or in Sleep mode, computer peripherals connected to the ECO outlets will be turned off (USB connection required). This provides additional reductions in power usage and greater energy savings.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$100,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Workstations
- Personal Electronics
- Home Networking/VoIP

Features

- 850VA / 510W
- Standby Topology
- Selectable ECO Technology
- Multifunction Diagnostic LCD
- GreenPower UPS™
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Compact Form Factor
- 12 Outlets / USB Port / RJ11 Protection
- EMI/RFI Filters
- PowerPanel® Personal Edition

Ecologic EC850LCD UPS

Offering advanced energy-saving battery backup and surge protection against power surges and interruptions.

GENERAL		MANAGEMENT & COMMUNICAT
UPS Topology	Standby	Multifunction Diagnostic LCD
Energy Saving	GreenPower UPS [™] High Efficiency	HID Compliant USB Port
ENERGY STAR® Qualified	Yes	Management Cable
INPUT		LED Indicators
Voltage	96Vac – 140Vac	Audible Alarms
Frequency	47Hz – 63Hz	Software
Plug Type	NEMA 5-15P	PHYSICAL
Plug Style	Right angle - 45 degree offset	Form Factor
Cord Length	5'	Keyhole Mounting Slots
OUTPUT		Dimensions (WxHxD) (in.)
VA	850	Weight (lbs.)
Watts	510	Shipping Dimensions (WxHxD)
On Battery Voltage	120Vac ± 5%	Shipping Weight (lbs.)
On Battery Frequency	50/60Hz ± 1% (auto-sensing)	ENVIRONMENTAL
On Battery Waveform	Simulated Sine Wave	Operating Temperature
Outlet Type	NEMA 5-15R	Operating Humidity
Outlets - Total	12	Operating Elevation
Outlets - Eco Controlled	3	Storage Temperature
Outlets - Battery & Surge Protected	6	Storage Relative Humidity
Outlets - Surge-Only Protected	6	Storage Elevation
Outlets - Widely Spaced	4	CERTIFICATIONS
Overload Protection	Internal circuitry limiting / circuit breaker	Safety
Transfer Time	4ms	Environmental
BATTERY		WARRANTY
Runtimes	10.4 min. (210W), 2.15 min. (425W)	Product Warranty
Battery Type	Sealed lead-acid	Connected Equipment Guarante
Typical Recharge Time	8 Hours	CEG Amount
SURGE PROTECTION & FILTERING		CyberPov
Surge Suppression	526 Joules	of ENERG
Phone Protection RJ11	1-In, 1-Out	(350VA
EMI/RFI Filtration	Yes	ENERGY STAR

LED Indicators	Power on, ECO on/off	
Audible Alarms	On battery, low battery, overload	
Software	PowerPanel [®] Personal Edition	
PHYSICAL		
Form Factor	Compact	
Keyhole Mounting Slots	Yes	
Dimensions (WxHxD) (in.)	21.2 x 3.1 x 7	
Weight (lbs.)	7.7	
Shipping Dimensions (WxHxD) (in.)	15 x 4.3 x 9.5	
Shipping Weight (lbs.)	7.8	
ENVIRONMENTAL		
Operating Temperature	32 °F to 104 °F / 0 °C to 40 °C	
Operating Humidity	0% - 90% non-condensing	
Operating Elevation	0-10000 feet (0-3000 meters)	
Storage Temperature	5 °F to 113°F / -15°C to 45 °C	
Storage Relative Humidity	0% - 95% non-condensing	
Storage Elevation	0-50000 feet (0-15000 meters)	
CERTIFICATIONS		
Safety	UL1778, cUL 107.3, FCC DOC Class B	
Environmental	RoHS Compliant	
WARRANTY		
Product Warranty	3 Years Limited	
Connected Equipment Guarantee	Lifetime	
CEG Amount	\$100,000	

Yes

Yes USB Cable

IENT & COMMUNICATIONS



CyberPower features the largest selection of ENERGY STAR® qualified UPS systems (350VA- 10kVA).

