

# E30 SPINNAKER

# EDIFIER®

## Specifications

Testing Item	Result	Condition
RMS Output Power	Treble: 10W x 2	$THD+N=10\%, f_0=1KHz$
	Midrange: 10W x 2	$THD+N=10\%, f_0=1KHz$
	Bass: 25W x 2	$THD+N=10\%, f_0=80Hz$
Signal to Noise ratio dB (A)	≥90dBA	$THD+N=1\%$
Distortion (%)	≤0.5	$P_0=1/2 P_1$ ( $P_1$ equals the output power @ $THD=1\%$ )
Freq. Response	R/L: Treble :7.2KHz~20KHz R/L: Midrange :160Hz~1.8KHz SW: 60Hz~110Hz	
Channel Separation (dB)	≥45dBA	$THD+N=1\%$
Input Sensitivity	AUX: 650mV±50mV Optical: 650 mV±50mV	$THD+N=1\%$
Input Type	AUX, Bluetooth, Optical	
Output	Bass expand	
Adjustment	Remote control	
Transformer	20V / 60W	

## Audio Engineering Specification

Testing Item	Result	Condition
Treble unit	Φ19mm silk dome tweeter, Magnetically Shielded, 4Ω	
Midrange unit	2 ¾ inch(70mm), Magnetically Shielded, 4Ω	
Bass Unit	4 inch (116mm), Magnetically Shielded, 6Ω	
Full-range response	60Hz~20KHz +/-3dB	

## Mechanical Specification

Item	Sub-item	Data
Body Dim. (W×H×D)	Active speaker	140 mm (5.51") ×413 mm (16.26") ×189mm (7.44")
	Passive speaker	140 mm (5.51") ×413 mm (16.26") ×189mm (7.44")

## Box Content Checklist

Item	Quantity	Description
Speaker	1PCS (2 Speakers)	Active speaker & Passive speaker (2 Speakers)
Power adapter	1PCS	20V/60W
Remote control	1PCS	
Speaker connecting cable	1PCS	1.7M (3.5mm~3.5mm) Black
Audio connecting cable	1PCS	0.8M(3.5-3.5mm) Black
USB cable	1PCS	0.8M(USB - Micro USB) Grey
Optical cable	1PCS	1.5M Black
User manual	1PCS	English/French/Spanish/German/Italian