22" (21.5" viewable) Full HD Widescreen LED Monitor



Ergonomic Design for Flexibility and Productivity

VG2228wm-LED





With a focus on features to help reduce TCO, the ViewSonic® VG2228wm-LED 22" (21.5" viewable) monitor delivers ergonomic comfort and a big, bold view for a productivity boost in any business environment. Full HD 1920x1080 resolution and an energy efficient LED backlit panel deliver crisp, clear viewing while users enjoy a productivity-enhancing customizable fit thanks to adjustable tilt, swivel, pivot, and height. The 2-port USB hub and slim bezel design with built-in speakers reduce clutter and save space for a more efficient work environment. For added savings, this energy-efficient monitor features ViewSonic Eco-mode for up to 30%* less power consumption—making it a great long-term investment

Key Features:

Full HD resolution

Advanced ergonomic design

DVI, VGA, and dual-port USB hub

Slim bezel design with built-in dual speakers

VESA compliant for wall mount or monitor stands

Designed for:

Business

Government

Education

22" (21.5" viewable) Full HD Widescreen LED Monitor





Specifications

LCD Panel	Type Display Area Optimum Resolution Brightness Contrast Ratio namic Contrast Ratio Viewing Angles Response Time Panel Surface	22" (21.5" Viewable) wide color TFT Active Matrix LED 18.8" horizontal x 10.6" vertical; 21.5" diagonal 1920x1080 250 cd/m² (typ) 1000:1 (typ); 10,000,000:1 (dynamic) 10,000,000:1 170° horizontal, 160° vertical 5ms (typ) Anti-glare, hard-coating (3H)	ER
VIDEO INPUT	Analog Digital Frequency Sync	RGB analog (0.7 / 1.0 Vp-p, 75 ohms) DVI-D (TMDS, 100 ohms), Fh= 24 ~82 kHz ; Fv=50 ~75 Hz Separate Sync	OF CC DII
AUDIO	Speakers	Built-In Speakers 2x2W	— (W
COMPATIBILITY	PC Mac®	VGA up to 1920×1080 Non-Interlaced Up to 1920×1080	WI
CONNECTOR	Video Analog Video Digital USB Audio Power	15-pin mini D-sub (VGA) DVI-D (with HDCP) 2 Port USB Hub 3.5 mm Headphone Jack Internal Power Board, 3-pin plub (CEE22)	RE
POWER	Voltage Consumption Eco Mode Power Save Mode	AC 100–240V (universal), 50 / 60Hz (Switch) 30W (typ) 20W optimize/17w conserve 1W	WA

CONTROLS	OSD	Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB DVI), Audio adjust (Volume Mute), Audio Input, Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD, Background, Auto Power Off), Memory Recall
ERGONOMICS	Tilt	Down 5°, Up 20°, Swivel 360°, Height Adjust 0-80mm
OPERATING CONDITIONS	Temperature Humidity	32–104° F (0–40° C) 10–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand Physical without stand Packaging	20.11" x 16.2" x 9.1" (510.9mm x 412.02mm x 230mm) 20.11" x 12.0" x 2.48" (510.9mm x 305.9mm x 61.7mm) 22.9" x 19.7" x 6.3" (582mm x 500mm x 160mm)
WEIGHT	Net with stand Net without stand	9.76 lb. (4.24 kg) 7.68 lb. (3.48 kg)
REGULATIONS		CB, TCO'05, WEEE, RoHS, UL/cUL, FCC-B, IRAM, NOM, ENERGY STAR®, EPEAT Silver ERGO, CE, Ukraine, GOST-R+Hygienic, SASO, BSMI, PSB, C-TICK, KCC, CCC
RECYCLE / DISPOSAL		Please dispose of in accordance with local, state or federal laws.
WARRANTY		Three-year limited warranty on parts, labor and backlight.

Optional Accessories

DVI-D to DVI-D Cable, 6FT	CB-00008187
HDMI to DVI Cable, 6FT	CB-00008948

What's in the box?

VG2228wm-LED display, power cable, video cable, audio cable, USB cable, Quick Start Guide, ViewSonic Wizard CD-ROM, Quick Start Guide.







