

# FUJITSU Image Scanner fi-65F

**Compact Design, Versatile Operations** 



- Scan A6 sized document in one second \*
  \* Grayscale. Monochrome (at 200/300dpi)
- Compact Size
- Enhanced one-touch scan button
- Powered by USB
- Bundled with the latest software for superb image processing and user operation
  - PaperStream IP
  - PaperStream Capture

Visit the fi Series homepage for more information http://www.fujitsu.com/sg/products/peripherals/scanner/



# fi-65F Features

## High speed scanning

The fi-65F is capable of scanning an A6 sized document in one second\*. Furthermore, users can start scanning at a lightning speed of 0.5 seconds after pressing the scan button (4.5 seconds from power saving mode), this quick start up means less waiting time with high-quality results. \*Grayscale Monochrome (at 200/300 dpi)

#### Compact size

It is smallest and most compact business grade scanner among the fi Series models. The fi-65F can be installed anywhere and facilitates workflow processes from administrative, logistics, managerial to customer service and more.

#### Easy to use

### Enhanced with a scan button

- The one-touch scan button and latest image capturing software allows users to scan and save image data simply in one touch of a button.
- Powered by USB
- The fi-65F can be powered through the USB port of a computer therefore allowing it to be used easily at any place with limited power supply.
- Bundled with the latest software for superb image processing and operability
  - The fi-65F is bundled with the latest standard software for fi Series.
  - PaperStream IP
  - The new TWAIN/ISIS driver "PaperStream IP" produces high quality images in a fast and simple manner.

# PaperStream Capture

The new image capturing software "PaperStream Capture" improves the efficiency of batch scanning.







000 38		
opped ii	mage	
oppedin	noge	

		/stems	Windows Vista <sup>®</sup> (32-bit/64-bit), Windows <sup>®</sup> XP (32-bit/64-bit),		
			Windows Server <sup>®</sup> 2012, Windows Server <sup>®</sup> 2008 (32-bit/64-bit)		
Scanner type			Flatbed		
Scanning mo	des		Simplex, Color / Grayscale / Monochrome		
Image sensor	type		Color CIS (Contact Image Sensor) (CMOS CIS)		
Light source			R,G,B LED (variable light source)		
Document size			Maximum: A6 (105 x 148 mm)		
Scanning speed (A4,Portrait)*1		Color	1.7 seconds (200 dpi)		
	AC adapter	Grayscale	1.0 seconds (200/300 dpi)		
		Monochrome			
	USB bus powerd	Color	2.0 seconds (200 dpi)		
		Grayscale	2.0 seconds (200/300 dpi)		
		Monochrome			
Expected daily volume			100 times / day		
Background colors			Black		
Optical resolution			600 dpi		
Output resolution Color (24-bit) Grayscale (8-bit) Monochrome (1-bit)		-bit)			
			50 to 600 dpi (adjustable by 1 dpi increments)		
Output format			Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit		
AD converter			65,536 levels (16-bit)		
Interface			USB2.0/USB1.1		
Connector shape			B type		
Power requirements			AC 100 to 240 V ±10%		
Power cable connection		blo	Operating mode: 8 W or less		
			Sleep mode: Less than 2 W or less		
		UII	Auto standby (off) mode: 0.5 W or less		
consumption	LICD bur	power cable	Operating mode: 5 W or less		
connection			Sleep mode: Less than 2 W or less		
	connection		Auto standby (off) mode: 0.5 W or less		
Operating on	vironmon	F	Temperature: 5 to 35 °C (42 to 95 °F)		
Operating environment		L	Relative humidity: 20 to 80% (Non-condensing)		
Dimensions: Width x Depth x Height*2		pth x Height*2	145 x 234 x 40 mm (5.7 x 9.2 x 1.6 in.)		
Weight			0.9 kg (1.98 lb)		
			PaperStream IP (TWAIN) driver, PaperStream IP (TWAINx64) driver,		
Included soft	Included software / drivers		PaperStream IP (ISIS) driver, PaperStream Capture,		
			Software operation panel		
Environmental compliance		ince	ENERGY STAR® and RoHS		
Others	Document cover		Included (removable)		
	Document holding pad color		Black		
	Power button		Available (back of the equipment)		
Included items			AC cable, AC adapter, USB cable, USB bus-power cable,		
			Setup DVD-ROM, Safety Precautions		
*1 Actual scanning	g speeds are	affected by data tr	ansmission and software processing times.		

fi-65F

Windows® 8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit),

\*2 Projecting items are not included in these dimentions.

#### Options

Description Parts number		Comments	
2D Barcode for PaperStream	PA43404-A433	This option enables the scanner to recognize 2D Barcode. (PDF417, QR code)	

Fujitsu Philippines, Inc.

Tel: (63 2)812 4001 Fax: (63 2) 8177576

**Fujitsu India Pvt. Limited** Tel: +91 124 470 5100 Fax: +91 124 470 5198, 460 5199

© Fujitsu Asia Pte Ltd, 2013. All rights reserved. No part of this publication may be reproduced in any material form without the writen permission of Fujitsu. The name Fujitsu, the Fujitsu device and the slogan 'shaping tomorrow with you' are trademarks or registered trademarks of Fujitsu Limited.

Fujitsu Vietnam Limited +84 4 220 3113 Fax: +91 124 470 5198, 460 5199

#### Trademarks

- \* ISIS is a registered trademark of EMC Corporation in the United States.
  \* Microsoft, Windows, Windows Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
  \* PaperStream is a registered trademark of PFU LIMITED in Japan.
  \* Morther products or company names appearing in this document are the trademarks or registered trademarks or registered trademarks or registered trademarks or sensitive company names appearing in this document are the trademarks or registered trademarks or registered trademarks or registered trademarks or registered trademarks or the sensitive company names appearing in this document are the trademarks or registered trademarks or registered trademarks or trademarks or the sensitive company names appearing in this document are the trademarks or registered trademarks or registered trademarks or trad trademarks of the respective companies.



Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
 Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
 Be sure to limit the use of this product to listed power ratings.



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Fujitsu Asia Pte Ltd Tel: 6512 7446/7873 Fax: 6512 7499 PT Fujitsu Indonesia Tel: (62-21) 570 9330 Fax: (620-21) 573 5477 Fujitsu (Malaysia) Sdn Bhd Tel: (603) 8318 3700 Fax: (603) 83188700 **Fujitsu Systems Business (Thailand) Ltd.** Tel: +66 (0) 2302 1500 Fax: +66 2302 1555 Email: scanner@sg.fujitsu.com Website: http://sg.fujitsu.com/scanner

Specifications are subject to change without notice.

#### Technical Specifications

Description