



Typ / Type : DV/DH 450-6 D		Art.-No. : A00-45043 / A10-45043	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	0.270 kW	ΔI	- %
I _N	0.56 A	I _A / I _N	2.9
n	895 min ⁻¹		IP54
C _{400V}	- μ F		01.006
t _R	60 °C		26 kg

Typ / Type : DV/DH 450-6-6 D		Art.-No. : A00-45052 / A10-45052	
U	400V (50Hz)	Δp_{fa} min	- Pa
P ₁	0.27/0.18 kW	ΔI	- %
I _N	0.56/0.31 A	I _A / I _N	2.9
n	895/710 min ⁻¹		IP54
C _{400V}	- μ F		01.045
t _R	60 °C		26 kg

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

LWArel A-bewertet bei V=0,5*Vmax LWArel A-weighted at V=0,5*Vmax		fM [Hz]						
		125	250	500	1K	2K	4K	8K
LWA5 [dB(A)]	Ansaugseite / inlet side	-18	-13	-12	-9	-7	-14	-21
LWA6 [dB(A)]	Ausblasseite / outlet side	-16	-10	-6	-5	-6	-13	-22

