

**Reporting Form**  
**For Hewlett Packard LaserJet 2100/2200 – Cartridge Model C4096A**

Declaration of yield:

Toner cartridge yield: Average cartridge yield 5000 standard pages  
 Declared yield value in accordance with ISO/IEC 19752

Average: 5583  
 Standard Deviation: 207  
 90% LCL: 5447

Dates Tested: 2003/12/29-2003/01/05

Number of Cartridges used in testing: 9  
 Number of Cartridges used in calculations: 9  
 Shake Procedure Used? Yes, at 1<sup>st</sup> and 2<sup>nd</sup> fades  
 Print Mode Continuous (200 pages/job)  
 Number of engines used in testing: 3  
 Media used Xerox 4024  
 Paper Size Letter  
 Paper feed orientation Short edge feed  
 Driver version HP 2200 Series PCL5  
 Test page version 3.2  
 Power (off/on) everyday No

**Cartridge Testing Data**

Cartridge	Lot Code	Engine	Temperature			Humidity			Cartridge Yield	Used in calculation?
			Min	Avg	Max	Min	Avg	Max		
C4096A-001	3D22H8	FRCGL01214	23.1	23.1	23.1	46.7	50.6	54.0	5935	Y
C4096A-002	3E08H9	FRCGL01214	23.1	23.1	23.1	48.2	50.6	53.0	5596	Y
C4096A-003	3E08H9	FRCGL01214	19.1	23.0	23.6	46.9	49.3	53.1	5689	Y
C4096A-004	3E08H9	JPGGB46742	23.1	23.1	23.1	46.7	50.6	54.0	5429	Y
C4096A-005	3E08H9	JPGGB46742	23.1	23.1	23.1	48.2	50.6	53.0	5396	Y
C4096A-006	3E08H9	JPGGB46742	19.1	23.0	23.6	47.0	49.3	53.1	5694	Y
C4096A-007	3E08H9	JPGGC45031	23.1	23.1	23.1	46.7	50.6	54.0	5643	Y
C4096A-008	3E07M1	JPGGC45031	23.1	23.1	23.1	48.3	50.7	53.0	5222	Y
C4096A-009	3E08H9	JPGGC45031	19.1	23.0	23.6	46.7	49.3	53.1	5642	Y