

## **Reporting Form** **For Hewlett Packard LaserJet 4000/4050 - Cartridge Model C4127X**

Declaration of yield:

|                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------|
| Toner cartridge yield: Average cartridge yield 10,000 standard pages<br>Declared yield value in accordance with ISO/IEC 19752 |
|-------------------------------------------------------------------------------------------------------------------------------|

Average: 11848  
 Standard Deviation: 469  
 90% LCL: 11540

Dates Tested: 2003/01/07-2003/01/15

|                                           |                                                   |
|-------------------------------------------|---------------------------------------------------|
| Number of Cartridges used in testing:     | 9                                                 |
| Number of Cartridges used in calculations | 9                                                 |
| Shake Procedure Used?                     | Yes, at 1 <sup>st</sup> and 2 <sup>nd</sup> fades |
| Print Mode                                | Continuous (100 pages/job)                        |
| Number of engines used in testing         | 3                                                 |
| Media used                                | Xerox 4024                                        |
| Paper Size                                | Letter                                            |
| Paper feed orientation                    | Short edge feed                                   |
| Driver version                            | HP 4050 Series PCL5                               |
| Test page version                         | 3.2                                               |
| Power (off/on) everyday                   | No                                                |

### Cartridge Testing Data

| Cartridge  | Lot Code | Engine     | Temperature |      |      | Humidity |      |      | Cartridge Yield | Used in calculation? |
|------------|----------|------------|-------------|------|------|----------|------|------|-----------------|----------------------|
|            |          |            | Min         | Avg  | Max  | Min      | Avg  | Max  |                 |                      |
| C4127X-001 | 3F30M2   | USQA012503 | 19.3        | 23.4 | 23.6 | 26.3     | 50.1 | 58.5 | 11860           | Y                    |
| C4127X-002 | 3F30M2   | USQA012503 | 23.0        | 23.3 | 23.3 | 45.2     | 50.4 | 54.0 | 12157           | Y                    |
| C4127X-003 | 3B28M1   | USQA012503 | 22.6        | 22.9 | 23.3 | 33.5     | 50.4 | 53.3 | 12390           | Y                    |
| C4127X-004 | 3F30M2   | USQC019895 | 19.3        | 23.4 | 23.6 | 26.3     | 50.1 | 58.5 | 12132           | Y                    |
| C4127X-005 | 3F30M2   | USQC019895 | 23.0        | 23.3 | 23.3 | 45.2     | 50.4 | 54.0 | 12446           | Y                    |
| C4127X-006 | 3F30M2   | USQC019895 | 22.6        | 22.9 | 23.3 | 33.5     | 50.4 | 53.3 | 11675           | Y                    |
| C4127X-007 | 3F30M2   | USQC019064 | 19.3        | 23.4 | 23.6 | 26.3     | 50.1 | 58.5 | 11551           | Y                    |
| C4127X-008 | 3F18M1   | USQC019064 | 23.0        | 23.3 | 23.3 | 45.2     | 50.4 | 54.0 | 11275           | Y                    |
| C4127X-009 | 3F30M2   | USQC019064 | 22.6        | 22.9 | 23.3 | 33.5     | 50.4 | 53.3 | 11150           | Y                    |