

Reporting Form **For Hewlett-Packard LaserJet 5100 – Cartridge Model C4129X**

Declaration of yield:

Toner cartridge yield: Average cartridge yield 10,000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average: 10520
 Standard Deviation: 193
 90% LCL: 10394

Dates Tested: 2003/12/04-2003/12/09

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations	9
Shake Procedure Used?	Yes, at 1 st and 2 nd fades
Print Mode	Continuous (100 pages/job)
Number of engines used in testing	3
Media used	Xerox 4024
Paper Size	Letter
Paper feed orientation	Short edge feed
Driver version	HP 5100 PCL5
Test page version	3.2
Power (off/on) everyday	No

Cartridge Testing Data

Cartridge	Lot Code	Engine	Temperature			Humidity			Cartridge Yield	Used in calculation?
			Min	Avg	Max	Min	Avg	Max		
C4129X-010	3F05N4	CNBF100002	23.0	23.0	23.1	46.6	50.7	54.1	10599	Y
C4129X-011	3F05N4	CNBF101198	23.0	23.0	23.1	46.6	50.7	54.1	10278	Y
C4129X-012	3F05N4	CNBF100002	23.1	23.1	23.1	43.8	50.7	55.4	10686	Y
C4129X-013	3F05N4	CNBF100002	23.0	23.1	23.1	46.1	50.8	55.4	10484	Y
C4129X-015	3E08N2	CNBR100118	23.1	23.1	23.1	43.8	50.7	55.4	10679	Y
C4129X-016	3F05N4	CNBF203889	23.0	23.0	23.1	46.6	50.7	54.1	10183	Y
C4129X-017	3F05N4	CNBF203889	23.0	23.1	23.1	46.1	50.8	55.4	10770	Y
C4129X-018	2K07N2	CNBF203889	23.1	23.1	23.1	43.8	50.7	55.4	10480	Y
C4129X-019	3F05N4	CNBR100118	23.1	23.1	23.1	43.8	50.7	54.2	10524	Y