



Product End-of-Life Disassembly Instructions

Product Category: LaserJet Printers

Marketing Name / Model

[List multiple models if applicable.]

HP LaserJet Enterprise 600 M603n (CE994A)

HP LaserJet Enterprise 600 M603dn (CE995A)

HP LaserJet Enterprise 600 M603xh (CE996A)

Purpose: The document is intended for use by end-of-life recyclers or treatment facilities. It provides the basic instructions for the disassembly of HP products to remove components and materials requiring selective treatment, as defined by EU directive 2002/96/EC, Waste Electrical and Electronic Equipment (WEEE).

1.0 Items Requiring Selective Treatment

1.1 Items listed below are classified as requiring selective treatment.

1.2 Enter the quantity of items contained within the product which require selective treatment in the right column, as applicable.

Item Description	Notes	Quantity of items included in product
Printed Circuit Boards (PCB) or Printed Circuit Assemblies (PCA)	With a surface greater than 10 sq cm (all PCAs) All models	25
Batteries	All types including standard alkaline and lithium coin or button style batteries All models: - Carbon monofluoride lithium coin cell - on PCA	1
Mercury-containing components	For example, mercury in lamps, display backlights, scanner lamps, switches, batteries not present	0
Liquid Crystal Displays (LCD) with a surface greater than 100 sq cm	Includes background illuminated displays with gas discharge lamps not present	0
Cathode Ray Tubes (CRT)	not present	0
Capacitors / condensers (Containing PCB/PCT)	not present	0
Electrolytic Capacitors / Condensers measuring greater than 2.5 cm in diameter or height	all models	1
External electrical cables and cords	all models	1
Gas Discharge Lamps	not present	0
Plastics containing Brominated Flame Retardants weighing > 25 grams (not including PCBs or PCAs already listed as a separate item above)	Plastic parts installed in close proximity to heating/fusing units and paper path parts contain brominated flame retardants. Further, industry	molded plastic parts:

	standard parts including fans, motors, cables, connectors, wiring and printed circuit boards also typically contain these flame retardants. All modes:	3 all motors, fans, connectors, wiring and PC boards
Components and parts containing toner and ink, including liquids, semi-liquids (gel/paste) and toner	Include the cartridges, print heads, tubes, vent chambers, and service stations. toner cartridge	1
Components and waste containing asbestos	not present	0
Components, parts and materials containing refractory ceramic fibers	not present	0
Components, parts and materials containing radioactive substances	not present	0

2.0 Tools Required

List the type and size of the tools that would typically be used to disassemble the product to a point where components and materials requiring selective treatment can be removed.

Tool Description	Tool Size (if applicable)
Use standard hand tools	

3.0 Product Disassembly Process

3.1 List the basic steps that should typically be followed to remove components and materials requiring selective treatment:

1. Remove toner cartridge.
2. Remove the outer housing skins and sort according to markings.
3. Disassemble the chassis using appropriate tools and set aside items requiring selective treatment.
- 4.
- 5.
- 6.
- 7.
- 8.

3.2 Optional Graphic. If the disassembly process is complex, insert a graphic illustration below to identify the items contained in the product that require selective treatment (with descriptions and arrows identifying locations).

