

## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo		
Company name *	Lexmark International, Inc.			
Contact information *	Nadia Martin (USA)	LEXMARK		
Internet site *	www.lexmark.se / www.lexmark.com			
Additional information				

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.			
Type of product *	Type of product * Single Function Mono Laser Printer		
Commercial name *	exmark MS310d, Lexmark MS310dn		
Model number *	MS310d, MS310dn		
Issue date *	Rev. November 5, 2012		
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other		
Additional information			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			Requirement met		
Item		Yes	No		
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$			
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	bl 🔀			

Model nu	Imber *	MS310d, MS310dn				
Issue dat	te *	Rev. November 5, 2012 Logo	• ]	LEXM	ARI	K.
	environ	mental attributes - Legal requirements	ŀ	Require		
Item	·			Yes	No	n.a.
P1		bus substances and preparations	- I			
P1.1*	0.1% po	s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent of lybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See lega e and Note B1)				
P1.2*	Products	s do not contain Asbestos (see legal reference). ht: Legal reference has no maximum concentration value.		$\boxtimes$		
P1.3*		s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),		$\boxtimes$		
	trichloro	pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximu ration values.				
P1.4*	Products	s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinat / (PCT) in preparations (see legal reference).	ed	$\boxtimes$		
P1.5*	Products	s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon ato ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	oms in the	$\boxtimes$		
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). nt: Legal reference has no maximum concentration values.	e (TRIS),			
P1.7*	Textile a	ind leather parts with direct skin contact do not contain more than 0.003% Azo colorants to amines. (See legal reference and Note B1)	hat split			$\boxtimes$
P1.8*	Wooden pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as lorophenol and derivatives (see legal reference). ht: Legal reference has no maximum concentration values.				
P1.9*	microgra	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm <sup>2</sup> /week (see legal reference). ht: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contac Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550	:t):	$\boxtimes$		
P2	Batterie	S				
P2.1*	more that marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it of an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it sh with the chemical symbol for the metal concerned, Hg or Pb. Information on proper dispose I in user manual. (See legal reference)	all be			
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batterie ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal re		$\square$		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)					
P3	Safety,	EMC connection to the telephone network and labeling				
P3.1*	The proc	duct complies with legally required safety standards as specified (see legal reference).		$\square$		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see legal r	eference).	$\times$		
P3.3*		t is intended for connection to a public telecom network or contains a radio transmitter, it ally required standards for radio and telecommunication devices (see legal reference).	complies	$\square$		
P3.4*	The proc	duct is labeled to show conformance with applicable legal requirements (see legal referen	ce).	$\boxtimes$		
P4		nable materials				
P4.1*		o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01 erence and Note B1).	% (see	$\square$		
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0.1% by weight (see legal refe	erence).	$\boxtimes$		
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable regulatic packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these tents is available (see legal reference).				
P5		packaging				
P5.1*	hexavale	ng and packaging components do not contain more than 0.01% lead, mercury, cad ent chromium by weight of these together.				
P5.2*	Plastic p	ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal refere	nce).	$\boxtimes$		
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the (see legal reference). nt: Legal reference has no maximum concentration values.	e Montreal			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu				
Issue dat	te * Rev. November 5, 2012	Logo	LEXM	RK
Product	environmental attributes - Market requirements	- Environmental conscious design	Requireme	nt mot
Item	roduct environmental attributes - Market requirements - Environmental conscious design m *=mandatory to fill in. Additional information regarding each item may be found under P14.		Yes N	
P6	Treatment information		100 11	0 11.u.
P6.1*	Information for recyclers/treatment facilities is available	(see legal reference).		
P7	Design			
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separ	able		
P7.2*	Plastic materials in covers/housing have no surface coa	ting.		
P7.3*	Plastic parts >100g consist of one material or of easily s	eparable materials.		
P7.4*	Plastic parts >25g have material codes according to ISC	0 11469 referring ISO 1043.		
P7.5	Plastic parts are free from metal inlays or have inlays that	at can be removed with commonly available tools.		
P7.6*	Labels are easily separable. (This requirement does not	apply to safety/regulatory labels).		1 8
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, ca	rds or drives		
P7.8*	Upgrading can be done using commonly available tools			╡┝┥
P7.9.	Spare parts are available after end of production for: 5 y	ears		-
P7.10	Service is available after end of production for: 5 years	Gaio		
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
	Material type: <b>ABS</b> Material type: <b>F</b>	HPS Material type: PC/ABS		
P7.12	Electrical cable insulation materials of power cables are			
P7.13	Electrical cable insulation materials of signal cables are	PVC free		
P7.14	All cover/housing plastic parts >25g are free from chlori	ne and bromine.		1 1
P7.15	All printed circuit boards (without components) >25g a Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings a Marking:	are marked according ISO 1043-4:		
P7.17	Alt. 1 Chemical specifications of flame retardants in printed cir TBBPA (additive) , TBBPA (reactive) , Other; che			
	Alt. 2 Chemical specifications of flame retardants in printed cir ISO 1043-4: <i>FR(16)</i>	cuit boards (without components) >25g according		
P7.18	Alt. 1 Flame retarded plastic parts >25g contain the follo concentrations above 0.1%:	с	in 🗌 🗌	
	Comment: No legal limits exist, this is a mark   1. Chemical name: , CAS #:   2. Chemical name: , CAS #:   3. Chemical name: , CAS #:   Alt. 2 Chemical specifications of flame retardants in plastic pa			
P7.19	FR(40), FR(17), FR(16), FR(50) Plastic parts >25g are free from flame retardant substan			
D7 00	R40, R46, R48, R50, R51, R53, R60, R61 and any com			
P7.20	Of total plastic parts' weight >25g, recycled material con			
P7.21 P7.22	Of total plastic parts' weight >25g, biobased material con Light sources are free from mercury	ntent is %.		
F 1.22		max. mercury content per lamp: mg		
P8	Batteries			
P8.1*	Battery chemical composition: Lithium Manganese Dio	xide, LiMnO2		
	Batteries meet the requirements of the following volunta			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model nu			MS310dn							
Issue dat	e *	Rev. November 5, 2012								
Product	environn	nental att	ributes - Market re	quirements (cor	ntinued)			Require	ement m	et
Item	duct environmental attributes - Market requirements (continued) Requirement me Yes No n.:									
P9	Energy	consumpti	on							
9.1	For the p	product the	following power levels	or energy consum	ptions are report	ed:				
Energy m	ode *		Power level at 100 V AC	Power level at 115 V AC	t Power level 230 V AC		ence / Star s and test met		energy	
Printing			<b>480</b> W	<b>477</b> W	<b>447</b> W	Corpo	Corporate Standard			
Ready M	lode		7.7 W	7.8 W	7.8 W	Energ	y Star I E V1	.2	[	
Sleep Mo	ode		<b>4.9</b> W	5.0 W	5.0 W		y Star I E V1	.2		
Hibernate	e Mode		0.4 W	0.4 W	0.5 W	IEC 6	2301		[	
Off Mode			0.00 W	0.00 W	0.00 W	IEC 6	2301		[	
			W	W	W					
charger p	power sup lugged in the disconnect	ne wall	W	W	W					$\square$
PTEC * Typical Er	nergy Cons	sumption	W	W	W					$\mathbf{X}$
TEC * Typical Er	nergy Cons	sumption	2.02 kWh/week	1.97 kWh/week	1.95 kWh/wee	k Energ	ly Star I E V1	.2	[	
ETEC * Annual Er	ETEC * Annual Energy Consumption		kWh/year	kWh/year	kWh/ye	ar				$\mathbf{X}$
Display re	solution*	: Me	gapixels							$\times$
Print Spee	ed *	: 35 Images	s per minute			Corpo	orate Standar	d		
Default tir	ne to enter	energy sav	ve mode: 30 minutes			Energ	y Star I E V1	.2		5
P9.2*	Informati	ion about th	ne energy save functio	n is provided with th	he product.			$\boxtimes$		
P9.3*	ENERG		the energy requiremen rersion: <b>1.2</b> Tier: <b>1</b> Pro L <b>UZ 122</b>							
P10	Emissio									
P10 1			Declared according to	ISO 9296	Declared		Declared A-w	roightod		
r IV.1	P10.1 Mode M		Mode description		A-weighted sound power		I pressure leve	•	)	
					level $L_{WAd}$ (B)	Operator po De or Desi	sktop	Bystander po only if product operator atte	t is not	
	Idle	*	Ready		* 3.3		15			
			* Simplex Monochrome Printing, Normal Mode		* 6.7	53			Ī	
	Other me	ode	ormai mode Simplex Monochrom Iode	e Printing, Quiet	6.4		50			
	Measure	ed accordine		ECMA-74 (only if not covered	by ECMA-74 wit	h L <sub>nam</sub> measu	urement distar	nce m)		
P10.2	The proc	duct meets	the acoustic noise req							-

Model nu	nber * MS310d, MS310dn			
Issue date	* Rev. November 5, 2012 Logo	LEXMARK		
Product	environmental attributes - Market requirements (continued)	Requirement r	met	
Item		Yes No	n.a.	
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard 🗌, other specify: RAL-UZ-122	$\boxtimes$		
P10.4	Typical emission rate (print phase) is (mg/h):			
	Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 2.0			
P10.5	Chemical emission requirements of the following voluntary program/s are met for :			
	Dust 🛛 Ozone 🖾 Styrene 🖾 Benzene 🖾 TVOC 🔀			
	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:			
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	$\boxtimes$		
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.	of 🔀 🗌		
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.		$\square$	
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): Corrugated weight (kg): 2.04   Product packaging material type(s): Polystyrene, Expanded weight (kg): 0.2858   Product packaging material type(s): weight (kg):			
P13.2*	Product plastic packaging is free from PVC.			
P13.3*	Specify media for user and product documentation (tick box): Electronic , Paper , Other			
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
Rev. P13.5	User and product documentation do not contain chlorine bleached paper			
P14	Additional information (See Note B4)			
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.			
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE			
	disposal symbol and instructions for such disposal is listed in the product User's Guide.			
P2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the however, is designed for easy removal by recyclers and service providers.	the customer;		
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine w in the processing of these parts.	as intentionally ad	lded	
P9.1	Print speed listed is Letter speed; A4 speed is 33 ppm.			
	Additional company information and company environmental policy may be found at http://lexmark.com/environm Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Lexmark Sweden is connected to REPA and El-kretsen	ient		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19