

## Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DAZNA A DIZ
Contact information *	Nadia Martin (USA)	<b>LEXM</b> ARK <sub>™</sub>
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *						
Commercial name *	exmark MS610dn, Lexmark MS610dtn					
Model number *	MS610dn, MS610dtn					
Issue date *	Rev. February 24, 2014					
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MS610dn, MS610dtn		
Issue date *	Rev. February 24, 2014	Logo	LEXMARK

Product	environmental attributes - Legal requirements	Require	men	t met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.	$\boxtimes$		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\boxtimes$		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	$\boxtimes$		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).  Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).  Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	$\square$		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\square$		П
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the			
25	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	ı 🖂		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).	l 🔀		
	Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu	ımber *	MS610dn, MS610dtn				
Issue dat		Rev. February 24, 2014	Logo	LEXM	ARK	-
		<u> </u>		LEXIVI	11/1	
Product	environ	mental attributes - Market requirements - Environmental conscious	design	Require	ment	met
Item		atory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.
P6		nt information				
P6.1*		on for recyclers/treatment facilities is available (see legal reference).		$\boxtimes$		
P7	Design Disasse	mbly, recycling				
P7.1*		at have to be treated separately are easily separable				
P7.2*	Plastic m	naterials in covers/housing have no surface coating.		X	$\Box$	
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.			Ħ	
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.			Ħ	
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly	available tools.		Ħ	
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).			Ħ	Ħ
	Product					
P7.7*	Upgradir	ng can be done e.g. with processor, memory, cards or drives				П
P7.8*	Upgradir	ng can be done using commonly available tools		$\overline{\mathbb{X}}$	Ħ	
P7.9.	Spare pa	arts are available after end of production for: 5 years				
P7.10		s available after end of production for: 5 years				
		and substance requirements				
P7.11*	Product	cover/housing material type:				
		71	al type: PC/ABS			
P7.12		I cable insulation materials of power cables are PVC free.			$\boxtimes$	
P7.13		I cable insulation materials of signal cables are PVC free			$\boxtimes$	
P7.14		/housing plastic parts >25g are free from chlorine and bromine.			$\boxtimes$	
P7.15	All printe Note B2	ed circuit boards (without components) >25g are halogen free. as defined in IEC6 )	61249-2-21. (Se	е		
P7.16	Flame re	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:				
P7.17	Alt. 1					
		al specifications of flame retardants in printed circuit boards >25g (without component additive), TBBPA (reactive), Other; chemical name:, CAS #:	ents):			
	ISO 104	al specifications of flame retardants in printed circuit boards (without components) : 3-4: <i>FR(16)</i>	>25g according			
P7.18		etarded plastic parts >25g contain the following flame retardant substance: ations above 0.1%:	s/preparations i	n 🔲		
	Comme 1. Chem 2. Chem 3. Chem Alt. 2 Chemica FR(40),	ent: No legal limits exist, this is a market requirement.  ical name: , CAS #: ical name: , CAS #: ical name: , CAS #: il specifications of flame retardants in plastic parts >25g according ISO 1043-4:  FR(17), FR(16), FR(50)		$\boxtimes$		
P7.19	Plastic p	arts >25g are free from flame retardant substances/ preparations above 0.1% clas 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	sified as R45,			

and max. mercury content per lamp:

mg

Of total plastic parts' weight >25g, recycled material content is up to 8%.

Battery chemical composition: Lithium Manganese Dioxide, LiMnO2

Batteries meet the requirements of the following voluntary program/s:

Of total plastic parts' weight >25g, biobased material content is

Light sources are free from mercury If mercury is used specify: Number of lamps:

P7.20

P7.21

P7.22

**P8** 

P8.2

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	MS610dn, MS610dtn			
Issue date *	Rev. February 24, 2014	Logo	]	LEXMARK

Item	Part   Fortie product the following power levels or energy consumptions are reported:	Product e	Product environmental attributes - Market requirements (continued)  Requirement met							ireme	
9.1 For the product the following power levels or energy consumptions are reported:  Energy mode * Power level at 100 V AC	For the product the following power levels or energy consumptions are reported:								Υe	s N	o n.a.
Power level at 100 V AC	Power level at 100 V AC   115 V AC   230 V AC   127   128 V AC										
100 V AC	100 V AC	9.1	For the product the	following power levels	or energy consump	tions are report	ted:				
Ready Mode 6.6 W 6.7 W 6.7 W Energy Star IE V2.0    Sleep Mode   2.5 W   2.5 W   2.5 W   Energy Star IE V2.0     Hibernate Mode   0.34 W   0.44 W   0.41 W   IEC 62301	Ready Mode 6.6 W 6.7 W 6.7 W Energy Star IE V2.0	Energy mod	le *				at			energ	iy 🗌
Sleep Mode   2.5 W   2.5 W   2.5 W   Energy Star IE V2.0	Siep Mode   2.5 W   2.5 W   2.5 W   Energy Star IE V2.0	Printing		<b>616</b> W	606 W	<b>577</b> W		Corporate Standard	I		
Hibernate Mode 0.34 W 0.44 W 0.41 W IEC 62301  Off Mode 0.00 W 0.00 W IEC 62301  W W W W  EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  TEC * Typical Energy Consumption  ETEC * Typical Energy Star IE V2.0  ETEC * Typ	### Hibernate Mode	Ready Mod	de	6.6 W	6.7 W	<b>6.7</b> W		Energy Star IE V2.0			
Off Mode    Default time to enter energy save mode: 30 minutes   Print Speed * : 50 Images per minute   Species   Sp	Off Mode    O.00 W	Sleep Mode	9	2.5 W	2.5 W	2.5 W		Energy Star IE V2.0			
W   W   W   W   W   W   W   W   W   W	EPS No-load (External power supply / Charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption	Hibernate I	Mode	0.34 W	0.44 W	0.41 W		IEC 62301			
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  ETEC * Annual Energy Consumption  ETEC * ENERGY STAR® version: 30 minutes  Energy Star IE V2.0  P9.2*  Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission - Declared according to ISO 9296  P10.1 Mode Mode description  Declared Declared A-weighted	EPS No-load (External power supply / Charger plugged in the wall outlet but disconnected from the product.)   W   W   W   W   W   W   W   W   W	Off Mode		0.00 W	0.00 W	<b>0.00</b> W		IEC 62301			
(External power supply / charger plugged in the wall outlet but disconnected from the product.)   PTEC * Typical Energy Consumption	External power supply / charger plugged in the wall outlet but disconnected from the product.)			W	W	W					
Typical Energy Consumption  TEC * Typical Energy Consumption  ETEC * Typical Energy Consumption  ETEC * Typical Energy Consumption  kWh/year kWh/year kWh/year kWh/year  Annual Energy Consumption  Display resolution*: Megapixels  Print Speed * : 50 Images per minute  Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description  Declared Declared A-weighted	Typical Energy Consumption  TEC Typical Energy Consumption  ETEC Annual Energy Consumption  ETEC Nanual Energy Consumption  Energy Star IE V2.0  Energy Star	(External po charger plug outlet but dis the product.	ower supply / gged in the wall sconnected from								
Typical Energy Consumption  ETEC *	Typical Energy Consumption  ETEC * Annual Energy Consumption		rgy Consumption	W	W	W					
Annual Energy Consumption  Display resolution*: Megapixels  Print Speed * : 50 Images per minute  Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description  Declared Declared A-weighted	Annual Energy Consumption  Display resolution*: Megapixels  Print Speed * : 50 Images per minute  Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound power level L <sub>WAd</sub> (B)  Operator position Desk side Operator attended)  Idle Ready 3.3 15  Operation Simplex Monochrome Printing, Normal Mode  Other mode Simplex Monochrome Printing, Ouiet Mode  Measured according to: ISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)		rgy Consumption	2.3 kWh/week	2.3 kWh/week	2.3 kWh/week		Energy Star IE V2.0			
Print Speed * : 50 Images per minute  Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared Declared A-weighted	Print Speed * : 50 Images per minute  Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode		rgy Consumption	kWh/year	kWh/year	kWh/ye	ar				
Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared Declared A-weighted	Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission — Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound power level L <sub>WAd</sub> (B)  Idle *Ready Operation Simplex Monochrome Printing, Normal Mode  Other mode Simplex Monochrome Printing, Quiet Mode  Measured according to: SISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>PAm</sub> measurement distance m)	Display reso	olution* : Me	egapixels	ı	l .					
P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared Declared A-weighted	P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound power level L_pAm (dB)  Operator position Desktop Operator attended)  Idle Ready Simplex Monochrome Printing, Normal Mode  Other mode Simplex Monochrome Printing, Quiet Mode  Measured according to: ISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L_pAm measurement distance m)	Print Speed	* : <b>50</b> Image	s per minute				ISO 24374			
P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared Declared A-weighted	P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound pressure level L_pAm (dB) Operator position Desktop or Desk side Operator attended)  Idle *Ready *3.3 Operator position Operator attended) Operation Simplex Monochrome Printing, Normal Mode Other mode Simplex Monochrome Printing, Quiet Mode  Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)	Default time	to enter energy sa	ve mode: 30 minutes				Energy Star IE V2.0			
ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared Declared A-weighted	ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode	P9.2*	Information about the	he energy save functio	n is provided with th	e product.		I			
Noise emission - Declared according to ISO 9296	$ \begin{array}{ c c c c c } \hline \textbf{Noise emission} - \textbf{Declared according to ISO 9296} \\ \hline \textbf{P10.1} & \textbf{Mode} & \textbf{Mode description} & \textbf{Declared} & \textbf{Declared} & \textbf{Sound pressure level } L_{p\text{Am}} \text{ (dB)} \\ \hline \textbf{Sound power} & \textbf{Sound pressure level } L_{p\text{Am}} \text{ (dB)} \\ \hline \textbf{Operator position} & \textbf{Desktop} & \textbf{Operator position} & \textbf{Operator positions} \\ \hline \textbf{Idle} & *\textbf{Ready} & *\textbf{3.3} & \textbf{15} \\ \hline \textbf{Operation} & *\textbf{Simplex Monochrome Printing,} & *\textbf{7.0} & \textbf{55} \\ \hline \textbf{Other mode} & \textbf{Simplex Monochrome Printing,} & \textbf{6.5} & \textbf{50} \\ \hline \textbf{Measured according to:} & \textbf{ISO7779} & \textbf{ECMA-74} \\ \hline \textbf{Other} & \textbf{(only if not covered by ECMA-74 with L_{pAm} measurement distance} & \textbf{m}) \\ \hline \end{array} $		ENERGY STAR® v	version: 2.0 Tier: Prod			m/s:		D D		
P10.1 Mode Mode description Declared Declared A-weighted	$ \begin{array}{ c c c c c c }\hline P10.1 & Mode & Mode description & Declared A-weighted sound power level $L_{WAd}$ (B) & Declared A-weighted sound pressure level $L_{pAm}$ (dB) & Operator position & Desktop or Desk side & Operator attended) & Operator attended & Operator attended) & Operator attended & Operator attended$	P10	Emissions							<u> </u>	
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$				ISO 9296						
		P10.1	Mode N	lode description		A-weighted			-	iB)	
level $I_{\text{max}}$ (R) Operator position Bystander positions	Desktop   Or Desk side   Only if product is not operator attended     Idle					•	Ope	rator position B	ystander		
Desktop Only if product is not Only if product is not	Idle       * Ready       * 3.3       15         Operation       * Simplex Monochrome Printing, Normal Mode       * 7.0       55         Other mode       Simplex Monochrome Printing, Quiet Mode       6.5       50         Measured according to:       ☒ ISO7779 ☐ ECMA-74         ☐ Other       (only if not covered by ECMA-74 with LpAm measurement distance m)					,,,,,		or Dock side (OI		uct is no	ot
	Normal Mode  Other mode Simplex Monochrome Printing, 6.5 50  Quiet Mode  Measured according to: ☐ ISO7779 ☐ ECMA-74  ☐ Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)		Idle *	Ready	4	<b>3.3</b>			operator c	ttoriact	<del>"</del>
	Quiet Mode         Measured according to: ☐ ISO7779 ☐ ECMA-74         ☐ Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)				e Printing,	7.0		55			
	Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)				e Printing,	6.5		50			
			Measured accordin	· = -		bv ECMA-74 wit	th L na.	measurement distan	ce	m)	
Other (only if not covered by ECMA-74 with Lnam measurement distance m)	P10.2 The product meets the acoustic noise requirements of the following voluntary program/s: RAL-UZ 122/RAL-										]

Model number *	MS610dn, MS610dtn			
Issue date *	Rev. February 24, 2014	Logo	]	LEXMARK

Product	environmental attributes - Market requirements (continued)	Require	ment	met		
Item		Yes	No	n.a.		
	Chemical emissions from printing products					
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122/RAL-UZ 171					
P10.4	Typical emission rate (print phase) is (mg/h):					
	Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 2.9					
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122/RAL-UZ 171 are met for :					
	Dust ☑ Ozone ☑ Styrene ☑ Benzene ☑ TVOC ☑					
	Electromagnetic emissions					
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:					
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	$\boxtimes$				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.					
P12	Ergonomics for computing products					
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.					
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			$\boxtimes$		
P13	Packaging and documentation					
P13.1*	Product packaging material type(s): Corrugated weight (kg): 1.78 Product packaging material type(s): Polystyrene, expanded Product packaging material type(s): weight (kg): 0.2858  weight (kg): 0.2858					
P13.2*	Product plastic packaging is free from PVC.	X				
P13.3*	Specify media for user and product documentation (tick box):  Electronic , Paper , Other					
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%					
Rev. P13.5	User and product documentation do not contain chlorine bleached paper					
P14	Additional information (See Note B4)					
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.					
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly lad disposal symbol and instructions for such disposal is listed in the product User's Guide.	beled with	the V	/EEE		
P.2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by to however, is designed for easy removal by recyclers and service providers.	he custom	er;			
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine we in the processing of these parts.	ns intentio	nally (	added		
P7.20	Per IEEE 1680.2 PCR calculation.					
P9.1	Information provided in P9.1 is for products with firmware FW LW30.PR2.P307 or higher. Print speed listed is Letter; The following table provides energy data for products with lower levels of firmware:	A4 speed i	is 47 p	рт.		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Printing	616 W	606 W	577 W	Corporate Standard	
Ready Mode	8.2 W	8.2 W	8.4 W	Energy Star I E V1.2	
Sleep Mode	4.0 W	4.0 W	4.0 W	Energy Star I E V1.2	
Hibernate Mode	0.34 W	0.44 W	0.41 W	IEC 62301	
Off Mode	0.00 W	0.00 W	0.00 W	IEC 62301	
	W	W	W		
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	w	W	w		
PTEC * Typical Energy Consumption	W	W	W		
TEC * Typical Energy Consumption	2.6 kWh/week	2.45 kWh/week	2.46 kWh/week	Energy Star I E V1.2	
ETEC* Annual Energy Consumption	kWh/year	kWh/year	kWh/year		
Display resolution* : Me	gapixels				
Print Speed * : 50 Image:	s per minute			Corporate Standard	$\overline{\Box}$
Default time to enter energy say	ve mode: 30 minutes			Energy Star I E V1.2	$\overline{\Box}$
P9.2* Information about the energy save function is provided with the product.					
P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment  Others specify: RAL UZ 122					

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19