

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo				
Company name *	Lexmark International, Inc.					
Contact information *	Nadia Martin (USA)	LEXM				
Internet site *	vww.lexmark.se / www.lexmark.com					
Additional information						

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Type of product * Single Function Mono Laser Printer			
Commercial name *	exmark MS811n, Lexmark MS811dn, Lexmark MS811dtn			
Model number *	IS811n, MS811dn, MS811dtn			
Issue date *	Rev. February 25, 2014			
Intended market *	Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information	Additional information			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requireme	nt met	
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model nu		MS811n, MS811dn, MS811dtn			
Issue da	te *	Rev. February 25, 2014 Logo	LEXM	ARI	ζ
Product	environr	nental attributes - Legal requirements	Require	ment	met
Item					n.a.
P1	Hazardo	us substances and preparations	Yes	No	
P1.1*					
P1.2*	Products	rence and Note B1) do not contain Asbestos (see legal reference). t: Legal reference has no maximum concentration value.	\square		
P1.3*		\boxtimes			
1 1.0	hydrobror trichloroe	do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), nofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- thane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ation values.			
P1.4*	Products	do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products	do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile ar Tris-(aziri	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), dinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). t: Legal reference has no maximum concentration values.			
P1.7*		Id leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split amines. (See legal reference and Note B1)			\square
P1.8*	pentachlo Commen	parts do not contain arsenic and chromium as a wood preservation treatment as well as prophenol and derivatives (see legal reference). t: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH A	Article 33 information about substances in articles is available at (add URL or mail contact): Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550	\square		
P2	Batteries				
P2.1*	more that marked w	duct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains n 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be <i>i</i> th the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is in user manual. (See legal reference)			
P2.2*	Button ce	Ils used in the product do not contain more than 2% by weight of mercury. Other batteries or ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	design of	and accumulators are easily removable by either users or service providers (as dependent on the the product). Exception: Batteries that are permanently installed for safety, performance, medica tegrity reasons do not have to be "easily removable". (See legal reference)			
P3		MC connection to the telephone network and labeling			
P3.1*		uct complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The produce	uct complies with legally required standards for electromagnetic compatibility (see legal			
P3.3*	If product	is intended for connection to a public telecom network or contains a radio transmitter, it complies ly required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The prod	uct is labeled to show conformance with applicable legal requirements (see legal reference).	\square		
P4	Consum	able materials			
P4.1*		conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see rence and Note B1).	\square		
P4.2*		er is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		
P4.3*	product/p requireme	toner formulation/preparation is classified as hazardous according to applicable regulations, the ackaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these ents is available (see legal reference).			
P5		packaging			
P5.1*	hexavale	g and packaging components do not contain more than 0.01% lead, mercury, cadmium and nt chromium by weight of these together.	d 🔀		
P5.2*	Plastic pa	ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\square		
P5.3*	Protocol	luct packaging material is free from ozone depleting substances as specified in the Montrea (see legal reference). t: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number * MS811n, MS811dn, MS811dtn							
Issue date *		Rev. February 25, 2014	Logo	LEXMARK			
1						2	
Product	oduct environmental attributes - Market requirements - Environmental conscious design Requirement m						
Item		*=mandatory to fill in. Additional information regarding each item may be found under P14.			No	n.a.	
P6	Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						
P7	Design						
	Disasse	mbly, recycling					
P7.1*	Parts that	t have to be treated separately are easily separable		\boxtimes			
P7.2*	Plastic m	aterials in covers/housing have no surface coating.			\boxtimes		
P7.3*							
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.			Ħ		
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly a	available tools.		H		
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).			╞		
17.0	Product						
P7.7*		g can be done e.g. with processor, memory, cards or drives					
P7.8*		g can be done using commonly available tools			╞	\dashv	
P7.9.						┝┝	
P7.10		rts are available after end of production for: 5 years					
P7.10		s available after end of production for: 5 years					
		and substance requirements					
P7.11*		cover/housing material type: https://www.app.cover/housing/material/type://w	tuno: DC/APS				
P7.12		type: ABS Material type: HIPS Materia I cable insulation materials of power cables are PVC free.	I type: PC/ABS		\square		
P7.12						──┤┤	
		I cable insulation materials of signal cables are PVC free		<u> </u>		<u> </u>	
P7.14		/housing plastic parts >25g are free from chlorine and bromine.		<u> </u>		<u> </u>	
P7.15	All printe Note B2	d circuit boards (without components) >25g are halogen free. as defined in IEC6	51249-2-21. (See	э	\boxtimes		
P7.16	Flame re Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:		\boxtimes			
P7.17		I specifications of flame retardants in printed circuit boards >25g (without compone additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	ents):				
_	ISO 104	l specifications of flame retardants in printed circuit boards (without components) > 3-4: <i>FR</i> (16)	25g according				
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances ations above 0.1%: ent: No legal limits exist, this is a market requirement.	/preparations ir	ו 🗌			
	1. Chem 2. Chem 3. Chem Alt. 2	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:					
D7 10	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) Image: Constraint of the second						
P7.19	R40, R4	arts >25g are free from flame retardant substances/ preparations above 0.1% class 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	silied as K45,				
P7.20		plastic parts' weight >25g, recycled material content is <i>up to 16%</i> .					
P7.21		plastic parts' weight >25g, biobased material content is %.					
P7.22	Light sources are free from mercury						
P8	Batterie	y is used specify: Number of lamps: and max. mercury content per lamp:	mg				
P8.1*		hemical composition: Lithium Manganese Dioxide, LiMnO2					
P8.2	Batteries meet the requirements of the following voluntary program/s:						
10.2	Datteries						

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model numb		MS811n, MS811dn, MS811dtn					
Issue date *	Rev.	February 25, 2014 Logo LEXMARK					
Product environmental attributes - Market requirements (continued) Requirement met							
Item							
	1 For the product the following power levels or energy consumptions are reported:						
Energy mode	*	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at Reference / Standard for energy modes and test method *		
Printing		755 W	752 W	759 W	Corporate Standard		
Ready 1 Mode		44.6 W	44.6 W	47 W	Energy Star I E V2.0		
Ready 2 Mod	le	21.2 W	24.7 W	25.3 W	Energy Star I E V2.0		
Sleep Mode		2.7 W	2.7 W	2.8 W	Energy Star I E V2.0		
Hibernate Mo	ode	0.42 W	0.44 W	0.45 W	IEC 62301		
Off Mode		0.1 W	0.1 W	0.1 W	IEC 62301		
EPS No-load (External pow charger plugg outlet but disc the product.)	ed in the wall		W	W			
PTEC * Typical Energ	y Consumptio	W	W	W			
TEC * Typical Energ	y Consumptio	3.9 kWh/week	3.9 kWh/week	4.0 kWh/week	Energy Star I E V2.0		
ETEC * Annual Energ	y Consumptio	kWh/year	kWh/year	kWh/ye	ar 🛛		
Display resolu	ution* :	Megapixels					
Print Speed *	: <mark>63</mark> lm	ages per minute			ISO 24734 (US Letter)		
Default time to	o enter energ	y save mode: 30 minutes			Energy Star I E V2.0		
P9.2* In	formation abo	out the energy save function	on is provided with th	ne product.			
E	NERGY STA	eets the energy requireme R® version: 2.0 Tier: Proc RAL-UZ 171			n/s:		
	missions		100 0000				
	oise emissio lode	n – Declared according to Mode description	150 9296	Declared	Declared A-weighted		
1 10.1	loue	Mode description		A-weighted sound power	sound pressure level L_{pAm} (dB)		
				level L_{WAd} (B)	Operator position Bystander positions		
				WAd	Desktop (only if product is not operator attended)		
Id	lle	* Ready		* 4.7	32		
0	peration	* Simplex Monochron Normal Mode	ne Printing,	* 7.3	58		
0	ther mode	Simplex Monochron Quiet Mode	ne Printing,	6.8	53		
М	leasured acco	ording to: 🔀 ISO7779 🗌	ECMA-74 (only if not covered	by ECMA-74 wit	h L _{pAm} measurement distance m)		
	The product meets the acoustic noise requirements of the following voluntary program/s: RAL-UZ 122/RAL-						

Model nu	mber *	MS811n, MS811dn, MS811dtn						
Issue date	e *	Rev. February 25, 2014	Logo	LEXM	NRK			
	Product environmental attributes - Market requirements (continued) Requirement met							
Item	Ohamia	- I		Yes	No	n.a.		
P10.3*		al emissions from printing products	117 400/DAL	-UZ 🛛				
1 10.5	Test performed according to ECMA-328 (ISO/IEC 28360) standard , other specify: RAL-UZ-122/RAL-UZ							
P10.4	Typical emission rate (print phase) is (mg/h):							
		Dust <0.9 Ozone <0.06 Styrene <0.2 Benzene <0.03 TVOC 5.8						
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122/RAL-UZ 171 are met for :							
	Dust 🔀 Ozone 🔀 Styrene 🔀 Benzene 🔀 TVOC 🔀							
		Dust 🛛 Ozone 🖾 Styrene 🖾 Benzene 🖂						
P10.6		er display meets the requirement for low frequency electromagnetic fields of the fo	llowing volunta	ary				
	program		-	·		-		
P11		nable materials for printing products		0)		_		
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally req	,	· 🔼	<u> </u>			
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the target the target of the target the target of	ne requiremer	nts of 🔀				
P11.3*		(duplex) printing/copying is an integrated product function.		\square				
P12		mics for computing products						
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technological	ogies.			\boxtimes		
P12.2*	The phy	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				\boxtimes		
P13		ng and documentation						
P13.1*		packaging material type(s): Corrugated weight (kg): 2.654						
		packaging material type(s): <i>Polystyrene, expanded</i> weight (kg): 0.634 packaging material type(s): <i>Low Density Polyethylene</i> weight (kg): 0.081						
		pylene – 0.065 kg						
P13.2*	Product	plastic packaging is free from PVC.		\square				
P13.3*		media for user and product documentation (tick box):						
		ic 🔀, Paper 🔀, Other 🗌						
P13.4*	For pape fiber: 0	er user and product documentation, please specify contained percentage of post-c	onsumer recyc	cled				
Rev.		J product documentation do not contain chlorine bleached paper						
P13.5								
P14		nal information (See Note B4)						
P1.1		luct uses RoHS exemptions for lead used in small amounts for specific applications.	voduct is avons	why lack alord with	+ + + + + + + + + + + + + + + + + + + +			
P2.1		ery contained within this product should be disposed of properly with the product. The p symbol and instructions for such disposal is listed in the product User's Guide.	roduct is prope	riy labelea witi	i the we			
		,,,,,,,,,,,,,,						
P2.3		${f e}$ ry contained within this product meets the exception listed. The battery is not intended	d to be removed	d by the custom	er;			
	however	is designed for easy removal by recyclers and service providers.						
P7.2	Special p	art: Small op panel screen (less than 25g) is backpainted.						
	- p p							
P7.14		mount of bromine may be present in covers due to sourcing post consumer recycled con	tent. No bromi	ine was intentio	onally ac	lded		
	in the pro	ocessing of these parts.						
P7.20	Per IFFF	1680.2 PCR calculation.						
P9.1	-	ion provided in P9.1 is for products with firmware FW LW30.DN2.P311 or higher. Print s	peed listed is Le	etter; A4 speed	is 60 ppı	n.		
	The follo	wing table provides energy data for products with lower levels of firmware:						

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

	P9 Energy consumpt	ion					
	9.1 For the product the following power levels or energy consumptions are reported:						
	Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *		
	Printing	755 W	752 W	759 W	Corporate Standard		
	Ready 1 Mode	40.3 W	41.1 W	51.5 W	Energy Star I E V1.2		
	Ready 2 Mode	27.3 W	28 W	30.3 W	Energy Star I E V1.2		
	Sleep Mode	4.0 W	4.0 W	4.0 W	Energy Star I E V1.2		
	Hibernate Mode	0.42 W	0.44 W	0.45 W	IEC 62301		
	Off Mode	0.1 W	0.1 W	0.1 W	IEC 62301		
	EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	W	W	W			
	PTEC * Typical Energy Consumption	w	w	W			
	TEC * Typical Energy Consumption	4.38 kWh/week	4.34 kWh/week	4.21 kWh/week	Energy Star I E V1.2		
	ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year			
	Display resolution* : Me	gapixels					
	Print Speed * : 63 Images per minute				Corporate Standard		
	Default time to enter energy save mode: 30 minutes				Energy Star I E V1.2		
	P9.2* Information about the energy save function is provided with the product.						
	P9.3* The product meets ENERGY STAR® v Others specify: RA	the energy requiremer version: 1.2 Tier: 1 Pro L UZ 122	nts of the following v oduct category: Imag	oluntary program/s: ging Equipment		R	
	Lexmark MS811n mode	el does not have	2-sided (duple	x) printing/cop	ying as an integrated function	1	
	Packaging data display Packaging data for MS	811dtn:					
P11.3	Product packaging mat		-	weight (kg): 2.			
]	Product packaging mat				ight (kg): 0.7247		
P13.1	Product packaging mat Polypropylene – 0.065		w Density Poly	vethylene wei	ight (kg): 0.081		
			ompany enviro	onmental policy	may be found at http://lexm	ark.com/environment	
	Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle						
	Lexmark Sweden is con					-	
L							

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19