

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXMARK
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product				
conforms to the statemen	ts given in this declaration.			
Type of product *	Type of product * Multi Function Mono Laser Printer			
Commercial name *	Lexmark MX510de, Lexmark MX511de, Lexmark MX511dte, Lexmark MX511dhe, Lexmark XM1145			
Model number *	MX510de, MX511de, MX511dte, MX511dhe, XM1145			
Issue date *	Rev. November 5, 2012			
Intended market *	🛛 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requirement met		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model nu		MX510de, MX511de, MX511dte, MX511dhe, XM1145			1	7
Issue dat	te *	Rev. November 5, 2012 Logo		LEXM	ARF	5
Product	onviron	mental attributes - Legal requirements		Require	mont	mot
Item		mental attributes - Legal requirements	ľ	Yes	No	n.a.
	Horordo	we substances and preparations		Tes	INU	n.a.
P1 P1.1*		bus substances and preparations s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chro			_	
F1.1	0.1% po	lybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal e and Note B1)	Jinium,			
P1.2*		s do not contain Asbestos (see legal reference).				
1 1.2		t: Legal reference has no maximum concentration value.		\bowtie		
P1.3*						
	hydrobro trichloroe	mofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1, ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.	,1-			
P1.4*		s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated (PCT) in preparations (see legal reference).		\square		
P1.5*		do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	s in the	\square		
P1.6*	Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (T ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). nt: Legal reference has no maximum concentration values.	RIS),			
P1.7*	Textile a	nd leather parts with direct skin contact do not contain more than 0.003% Azo colorants that amines. (See legal reference and Note B1)	split			\boxtimes
P1.8*	Wooden pentachl	parts do not contain arsenic and chromium as a wood preservation treatment as well as orophenol and derivatives (see legal reference). ht: Legal reference has no maximum concentration values.				
P1.9*	microgra	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm²/week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550		\square		
P2	Batterie					
P2.1*	If the pro more tha marked	duct contains a battery or an accumulator, it is labeled with the disposal symbol and if it con an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal i l in user manual. (See legal reference)	be			
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batteries o ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal references the second se		\square		
P2.3*	design o	s and accumulators are easily removable by either users or service providers (as dependent f the product). Exception: Batteries that are permanently installed for safety, performance, m ntegrity reasons do not have to be "easily removable". (See legal reference)				
P3	Safety, I	EMC connection to the telephone network and labeling				
P3.1*	The proc	duct complies with legally required safety standards as specified (see legal reference).		\boxtimes		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see legal refe	rence)		F	F
P3.3*	If produc	t is intended for connection to a public telecom network or contains a radio transmitter, it cor	,			
P3.4*	The proc	ally required standards for radio and telecommunication devices (see legal reference). duct is labeled to show conformance with applicable legal requirements (see legal reference)	•	\square		
P4		nable materials				
P4.1*	legal refe	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% erence and Note B1).	`			
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0.1% by weight (see legal referer	nce).	\bowtie		
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable regulations, packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).	the			
P5	Product	packaging				
P5.1*		ng and packaging components do not contain more than 0.01% lead, mercury, cadmit ent chromium by weight of these together.	im and			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).					
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal					

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu	Imber *	MX510de, MX511de, MX511dte, MX511dhe, XM1145			
Issue dat	te *	Rev. November 5, 2012 Logo	LEXM	ARK	
	environ	mental attributes - Market requirements - Environmental conscious design	Require		
Item P6		tory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6.1*		on for recyclers/treatment facilities is available (see legal reference).			
P7	Design				
•••		mbly, recycling			
P7.1*	Parts that	t have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic m	aterials in covers/housing have no surface coating.	\boxtimes		
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.	\square		
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product	lifetime			
P7.7*	Upgradir	g can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgradir	g can be done using commonly available tools	\boxtimes		
P7.9.	Spare pa	rts are available after end of production for: 5 years			
P7.10	Service i	s available after end of production for: 5 years			
		and substance requirements			
P7.11*		cover/housing material type:			
P7.12		type: ABS Material type: HIPS Material type: PC/ABS I cable insulation materials of power cables are PVC free.			_
P7.12		I cable insulation materials of signal cables are PVC free	<u> </u>		\mathbf{H}
P7.13			<u> </u>		<u>⊢</u>
		/housing plastic parts >25g are free from chlorine and bromine.			<u>⊢</u>
P7.15	Note B2	d circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (Se	e	\boxtimes	Ш
P7.16		tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:	\boxtimes		
P7.17	Alt. 1 Chemica TBBPA (I specifications of flame retardants in printed circuit boards >25g (without components): additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	ISO 1043	I specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: <i>FR(16)</i>			
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances/preparations ations above 0.1%: ent: No legal limits exist, this is a market requirement.	in 🗌		
	1. Chem 2. Chem 3. Chem Alt. 2	ical name:, CAS #:ical name:, CAS #:ical name:, CAS #:			
D7 10	FR(40),	I specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50) arts >25g are free from flame retardant substances (properations above 0.1% classified as P45			
P7.19	R40, R46	arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20		lastic parts' weight >25g, recycled material content is %.			
P7.21 P7.22		elastic parts' weight >25g, biobased material content is %.			
11.22	0	y is used specify: Number of lamps: and max. mercury content per lamp: mg	\bowtie		
P8	Batterie				
P8.1*	Battery c	hemical composition: Lithium Manganese Dioxide, LiMnO2			
P8.2	Batteries	meet the requirements of the following voluntary program/s:			Π

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Issue date * Rev. November 5, 2012 Logo LEXMARK Product environmental attributes - Market reguirements (continued) Requirement met		del number * MX510de, MX511de, MX511dte, MX511dhe, XM1145											
tem Yes No n.a. 9 Energy consumption Site For the product the following power levels or energy consumptions are reported: Reference / Standard for energy Copy 586 W 569 W 537 W Corporate Standard Images and test method: Copy 586 W 569 W 537 W Corporate Standard Images and test method: Steep Mode 5.7 W 5.8 W 6.0 W Energy Star I E V1.2 Images and test method: Steep Mode 0.26 W 0.27 W 0.39 W IEC 62301 Images and test method: Off Mode 0.0 W 0.0 W W W W IEC 62301 Images and test method: Charger plagod in the wall oconnected from the product. W W W IEC 62301 Images and test method: TEC : Nonal Energy Consumption W W W IEC 62301 Images and test method: Images a	Issue date	* Rev. November 5, 2012 Logo											
tem Yes No n.a. 9 Energy consumption Site For the product the following power levels or energy consumptions are reported: Reference / Standard for energy Copy 586 W 569 W 537 W Corporate Standard Images and test method: Copy 586 W 569 W 537 W Corporate Standard Images and test method: Steep Mode 5.7 W 5.8 W 6.0 W Energy Star I E V1.2 Images and test method: Steep Mode 0.26 W 0.27 W 0.39 W IEC 62301 Images and test method: Off Mode 0.0 W 0.0 W W W W IEC 62301 Images and test method: Charger plagod in the wall oconnected from the product. W W W IEC 62301 Images and test method: TEC : Nonal Energy Consumption W W W IEC 62301 Images and test method: Images a	Product	Product environmental attributes - Market requirements (continued)						met					
9.1 For the product the following power level at Power level at Power level at Reference / Standard for energy mode* Power level at Power level at Power level at Reference / Standard for energy mode* Printing 586 W 569 W 537 W Corporate Standard Copy 596 W 618 W 541 W Corporate Standard Ready Mode 13.2 W 12.8 W 13.5 W Energy Star IE V1.2 Steep Mode 5.7 W 5.8 W 6.0 W Energy Star IE V1.2 Hibernate Mode 0.26 W 0.27 W 0.39 W IEC 62301 Off Mode 0.0 W 0.0 W 0.0 W IEC 62301 Off Mode 0.26 W 0.27 W 0.39 W IEC 62301 Off Mode 0.0 W 0.0 W W W X Extend power supply / charge plugged in the wall W W W X PTIC * W W W W X Tec * Noise energy Consumption KWh/week 2.7 kWh/week Energy Star I E V1.2 X Display resolution* : Megapixels Corporate Standard X X Print Speed* : 45													
Energy mode * Power level at 10 v AC Power level at 10 v AC Power level at 230 v AC Reference 7 Standard for energy modes and test method * Printing 566 W 569 W 618 W 541 W Corporate Standard Image: Standard for energy modes and test method * Ready Mode 13.2 W 12.8 W 13.5 W Energy Star IE V1.2 Image: Standard for energy Star IE V1.2 Hibernate Mode 0.26 W 0.27 W 0.39 W IEC 62301 Image: Standard for energy Star IE V1.2 Hibernate Mode 0.26 W 0.27 W 0.39 W IEC 62301 Image: Star IE V1.2 Cherry Star IE V1.2 W W W W Image: Star IE V1.2 Image: Star IE V1.2 EPS No-load W W W W Image: Star IE V1.2 Image: Star IE V1.2 Image: Star IE V1.2 Eps No-load W W W W Image: Star IE V1.2 Image: Star IE V1.2 <td>P9</td> <td>Energy</td> <td>consumpti</td> <td>on</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	P9	Energy	consumpti	on									
100 VAC 115 VAC 230 VAC modes and lest method * Image Printing 586 W 569 W 537 W Corporate Standard Image Imag	9.1	9.1 For the product the following power levels or energy consumptions are reported:											
Copy 596 W 618 W 541 W Corporate Standard Ready Mode 13.2 W 12.8 W 13.5 W Energy Star I E V1.2 Steep Mode 6.7 W 5.8 W 6.0 W Energy Star I E V1.2 Hibernate Mode 0.26 W 0.27 W 0.39 W IEC 62301 IEC 62301 GM Mode 0.0 W 0.0 W 0.0 W IEC 62301 IEC 62301 EPS No-load W W W W IEC 62301 IEC 62301 Charger plugged in the wall outlet but disconnected from the product.) W W W IEC 7 Typical Energy Consumption W W W W IEC 7 Typical Energy Consumption KWh/year KWh/year Energy Star I E V1.2 IEC 7 Typical Energy Consumption KWh/year KWh/year Energy Star I E V1.2 IEC 7 Display resolution* : Megapixels IEnergy Star I E V1.2 IEC 7 IEC 7 Print Speed* : 45 Images per minute Corporate Standard IEC 7 IEC 7 IEC 7 Polation about the energy save function is provided with the product. IEC 7	Energy mo	de *						modes and test method *			energy		
Ready Mode 13.2 W 12.8 W 13.5 W Energy Star I E V1.2 Steep Mode 5.7 W 5.8 W 6.0 W Energy Star I E V1.2 Hibernate Mode 0.26 W 0.27 W 0.39 W IEC 62301 IEC 62301 Off Mode 0.0 W 0.0 W 0.0 W IEC 62301 IEC 62301 IEC 62301 Off Mode 0.0 W 0.0 W W W W W IEC 62301	Printing		586 W	569 W	537 W		Corporate Standard						
Steep Mode 5.7 W 5.8 W 6.0 W Energy Star I E V1.2 Hibernate Mode 0.26 W 0.27 W 0.39 W IEC 62301 IEC 62301 Off Mode 0.0 W 0.0 W 0.0 W IEC 62301 IEC 62301 IEC 62301 EPS No-load W W W W W IEC 62301	Сору			596 W	618 W	541 W	С	orpora	ate Star	ndard			
Hibernate Mode 0.26 W 0.27 W 0.39 W HEC 62301 Off Mode 0.0 W 0.0 W 0.0 W IEC 62301 IEC 62301 EPS No-load W W W W W IEC 62301 IEC 62301 (External power supply/ charger plugged in the wall outle but disconnected from the product.) W W W W X PTEC * Typical Energy Consumption 2.8 kWh/week 2.7 kWh/week 2.7 kWh/week Energy Star I E V1.2 Image: Star A and	Ready Mo	ode		13.2 W	12.8 W	13.5 W	E	nergy	Star I E	E V1.2			
Off Mode 0.0 W 0.0 W 0.0 W IEC 62301 EPS No-load W W W W W W M charger plugged in the wall outlet but disconnected from the product) W W W W M<	Sleep Moo	le		5.7 W	5.8 W	6.0 W	E	nergy	Star I E	E V1.2			
EPS No-load W <td< td=""><td>Hibernate</td><td>Mode</td><td></td><td>0.26 W</td><td>0.27 W</td><td></td><td>IE</td><td>C 623</td><td>01</td><td></td><td></td><td></td><td></td></td<>	Hibernate	Mode		0.26 W	0.27 W		IE	C 623	01				
(External power supply / charger plugged in the wall outle but disconnected from the product.) N N N N PTEC * Typical Energy Consumption W W W W X TEC * Typical Energy Consumption 2.8 kWh/week 2.7 kWh/week Energy Star I E V1.2 Image: Consumption Erec * Annual Energy Consumption kWh/year kWh/year KWh/year X Display resolution* : Megapixels X X X P10 Emergy Star I E V1.2 Images per minute Corporate Standard Images per X P10 Emissions X Images per X Images per X Images per X P10 Emission - Declared according to ISO 9296 Declared A-weighted sound power level L _{WAd} (B) Declared A-weighted sound power or Desk side Images per position Idle * Ready * 3.3 15 Images per position Images per position Images per position Idle * Ready * 3.3 15 Images per position Images per position Images per position Images per position Mode Mode description Declared A-weighted sound power Images per position Images per pos	Off Mode			0.0 W	0.0 W	0.0 W	IE	C 623	01				
charger plugged in the wall outlet but disconnected from the product.) W W W PTEC * Typical Energy Consumption 2.8 kWh/week 2.7 kWh/week 2.7 kWh/week Energy Star I E V1.2 TEC * Typical Energy Consumption 2.8 kWh/week 2.7 kWh/week 2.7 kWh/week Energy Star I E V1.2 TEC * Typical Energy Consumption kWh/year kWh/year kWh/year Annual Energy Consumption kWh/year kWh/year kWh/year Display resolution* : Megapixels Pint Speed * : 45 Images per minute Corporate Standard Default time to enter energy save mode: 30 minutes Energy Star I E V1.2 P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 P10 Emission – Declared according to ISO 9296 P10.1 Mode	EPS No-loa	ad		W	W	W	Ì						\square
Typical Energy Consumption 2.8 kWh/week 2.7 kWh/week 2.7 kWh/week Energy Star I E V1.2 TEC * Typical Energy Consumption 2.8 kWh/week 2.7 kWh/week Energy Star I E V1.2 Image: Consumption image: Consumptimanter image: Consumption image: Consumptim	charger plu outlet but d	igged in th	e wall										
Typical Energy Consumption kWh/year kWh/year kWh/year x ETEC * Annual Energy Consumption kWh/year kWh/year x x Display resolution* : Megapixels X X X Print Speed * : 45 Images per minute Corporate Standard X Default time to enter energy save mode: 30 minutes Energy Star I E V1.2 X X P9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 X X X P10 Emissions Noise emission – Declared according to ISO 9296 Declared A-weighted sound pressure level L _{pAm} (dB) X X X P10.1 Mode Mode description Declared A-weighted sound pressure level L _{pAm} (dB) X X X X Idle * Ready * 3.3 15 X	-	ergy Cons	umption	W	W	W							\square
Annual Energy Consumption Images in the second		ergy Cons	umption	2.8 kWh/week	2.7 kWh/week	2.7 kWh/week	E	Energy Star I E V1.2					
Print Speed* : 45 Images per minute Corporate Standard Default time to enter energy save mode: 30 minutes Energy Star I E V1.2 P9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 Image: Component Star Star Star Star Star Star Star Sta	-	ergy Cons	umption	kWh/year	kWh/year	kWh/year							
Print Speed* : 45 Images per minute Corporate Standard Default time to enter energy save mode: 30 minutes Energy Star I E V1.2 P9.2* Information about the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 Image: Component Star Star Star Star Star Star Star Sta	Display res	olution* :	Me	gapixels									
P9.2* Information about the energy save function is provided with the product. Imaging Equipment P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 Imaging Equipment P10 Emissions Imaging Equipment Imaging Equipment Noise emission – Declared according to ISO 9296 Declared A-weighted sound power Declared A-weighted sound pressure level L _p Am (dB) P10.1 Mode Mode description Declared A-weighted sound power Declared A-weighted sound pressure level L _p Am (dB) Idle * Ready * 3.3 15 Operation * Simplex Monochrome Printing, Normal Mode * 7.1 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 ECMA-74 with LpAm measurement distance m)	Print Speed	d* :	45 Images	s per minute			С	orpora	ate Star	ndard			
P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 □ P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode Mode description Declared sound power Declared A-weighted sound pressure level L _{pAm} (dB) Operator position Bystander positions (only if product is not operator attended) Idle * Ready * 3.3 Operation * Simplex Monochrome Printing, Normal Mode * 7.1 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	Default time	e to enter	energy sav	e mode: 30 minutes			E	nergy	Star I E	V1.2			Ē
ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122 P10 Emissions Noise emission - Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L_{WAd} (B) Operator position Desktop or Desk side Idle * Ready * 3.3 Idle * Ready * Simplex Monochrome Printing, Mode Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51	P9.2*	Informati	on about th	e energy save function	n is provided with th	e product.					\boxtimes		
P10 Emissions Noise emission - Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L_{pAm} (dB) P10.1 Idle * Ready * 3.3 Desktop or Desk side Idle * Ready * 3.3 15 Operation * Simplex Monochrome Printing, Normal Mode * 7.1 56 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)	P9.3*	ENERGY	STAR® v	ersion: 1.2 Tier: 1 Pro							\boxtimes		
Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Declared A-weighted sound pressure level L _{pAm} (dB) Idle * Ready * 3.3 15 Operation * Simplex Monochrome Printing, Normal Mode * 7.1 56 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	P10												
A-weighted sound power level L_{WAd} (B)sound pressure level L_{pAm} (dB)Operator positionBystander positions (only if product is not operator attended)Idle* Ready* 3.3Operation* Simplex Monochrome Printing, Normal Mode* 7.1Other modeSimplex Monochrome Printing, Quiet Mode6.5Other modeSimplex Monochrome Printing, Quiet Mode6.5Other modeSimplex Monochrome Printing, Quiet Mode6.5Other modeSimplex Monochrome Printing, Quiet Mode6.5Other modeSimplex Monochrome Printing, Quiet Mode6.5Measured according to:ISO7779ECMA-74 (only if not covered by ECMA-74 with Lpam measurement distance m)		Noise er	nission – [Declared according to	ISO 9296								
Idle * Ready * 3.3 15 Operation * Simplex Monochrome Printing, Normal Mode * 7.1 56 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)	P10.1	Mode	М	Node description		A-weighted	d sound pressure level L_{nAm}						
Idle * Ready * 3.3 15 Idle * Simplex Monochrome Printing, Normal Mode * 7.1 56 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if product is not operator attended)						•				-			-
Operation * Simplex Monochrome Printing, Normal Mode * 7.1 56 Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)						iever L _{WAd} (B)		Desk	top	(only if	produ	ct is not	
Normal Mode Normal Mode Other mode Simplex Monochrome Printing, Quiet 6.5 51 Mode Mode ECMA-74 Other Other Measured according to: ISO7779 ECMA-74 ECMA-74 with LpAm measurement distance m)		Idle	*	Ready	1	* 3.3				15			
Other mode Simplex Monochrome Printing, Quiet Mode 6.5 51 Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)					e Printing,	* 7.1		56					
Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)		Other mode		Simplex Monochrom	e Printing, Quiet	6.5	51				1		
		Measure	d according							- 4		、	
	P10.2	The prod	uct meeter										

Model nu	mber *	MX510de, MX511de, MX511dte, MX511dhe, XM1145					
Issue date *		Rev. November 5, 2012 Logo	EXM	RK			
Product	environn	nental attributes - Market requirements (continued)	Require	ment	met		
Item			Yes	No	n.a.		
	Chemica	al emissions from printing products					
P10.3*	Test per	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122	\square				
P10.4		emission rate (print phase) is (mg/h):					
P10.5		Dust 1.3 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 3.4 al emission requirements of the following voluntary program/s RAL-UZ-122 are met for :					
F 10.5		Dust Ozone Styrene Benzene TVOC	\boxtimes				
	Electron	nagnetic emissions					
P10.6	Compute program	er display meets the requirement for low frequency electromagnetic fields of the following voluntary /s:					
P11	Consum	nable materials for printing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\square				
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the requirements o 1.	f 🔀				
P11.3*	2-sided ((duplex) printing/copying is an integrated product function.	\boxtimes				
P12		mics for computing products					
P12.1*	-	play meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes		
P12.2*		sical input device meets the requirements of ISO 9995 and ISO 9241-410.			\square		
P13		ing and documentation					
P13.1*	Product Product	packaging material type(s): Corrugated weight (kg): 2.167 packaging material type(s): Polystyrene, expanded weight (kg): 0.595 packaging material type(s): Low Density Polyethylene weight (kg): 0.081					
P13.2*		plastic packaging is free from PVC.	\boxtimes				
P13.3*	Electron	media for user and product documentation (tick box): ic ⊠, Paper ⊠, Other □					
P13.4*	fiber: 0						
Rev. P13.5	User and	d product documentation do not contain chlorine bleached paper					
P14		nal information (See Note B4)					
P1.1 P2.1	The batte	luct uses RoHS exemptions for lead used in small amounts for specific applications. ery contained within this product should be disposed of properly with the product. The product is properly lai symbol and instructions for such disposal is listed in the product User's Guide.	beled with	the W	'EEE		
P2.3		ery contained within this product meets the exception listed. The battery is not intended to be removed by the is designed for easy removal by recyclers and service providers.	he custom	er;			
P9.1	The print	speed listed is letter speed; A4 speed is 42 ppm.					
P7.14		mount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine was pocessing of these parts.	is intentio	nally a	dded		
P13.1	Packagin Product Product Product	g displayed in P13.1 is for MX510de, MX511de, MX511dhe, and XM1145. g for MX511dte: packaging material type(s): Corrugated weight (kg): 3.016 packaging material type(s): Polystyrene, expanded weight (kg): 0.6 packaging material type(s): Low Density Polyethylene weight (kg): 0.081 al company information and company environmental policy may be found at http://lexmark.com/environmental	ent				
		printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Sweden is connected to REPA and El-kretsen					

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19