



## GEFORCE® GTX 760 2GB

## VCGGTX7602XPB

### BORN TO PERFORM

GeForce® GTX 760 XLR8 by PNY is the new graphics card of choice for gamers—a powerful graphics card that gives you the fast, smooth, quiet gaming you're looking for in all your favorite titles. It's packed with next-gen features like NVIDIA GeForce Experience™ and GPU Boost 2.0 that let you crank up the settings in today's most graphics-intensive games.

### PACKAGE INCLUDES

- GeForce® GTX 760 2GB graphics card
- Quick Installation Guide
- Installation DVD, which includes:
  - Detailed installation guide
  - NVIDIA® Graphics Drivers
  - NVIDIA® GeForce® Demos
  - PhysX™ System Software
- DVI-to-VGA adapter
- 6-pin PCIe to Molex Power Adapter

### KEY FEATURES

- NVIDIA® GPU Boost 2.0
- NVIDIA® Adaptive Vertical Sync
- NVIDIA® TXAA Technology
- NVIDIA® FXAA Technology
- NVIDIA® Surround™
- Support for four concurrent Displays\* including:
  - Two Dual-Link DVI
  - HDMI 1.4b
  - DisplayPort 1.2
- Microsoft® DirectX® 11.1 (feature 11\_0)
- NVIDIA® PhysX® technology
- NVIDIA® 3D Vision®-Ready
- NVIDIA® SLI®-Ready
- NVIDIA® Shield™ -Ready

- NVIDIA® CUDA® technology
- PCI Express 3.0 support
- OpenGL 4.3 support
- OpenCL™ support

### REQUIREMENTS

- PCI Express compliant motherboard with one dual-width x16 graphics slot
- Two 6-pin PCI Express supplementary power connectors
- Minimum 500W or greater system power supply (with a minimum 12V current rating of 30A)
- 300 MB of available hard-disk space
- 2GB system memory (4GB or higher recommended)
- Microsoft Windows 8, Windows 7, Windows Vista, or Windows XP Operating System (32 or 64-bit)
- DVD-ROM drive or Internet connection for installation
- DVI, HDMI, DisplayPort or VGA compatible monitor

### PRODUCT SPECIFICATIONS

|                                    | GPU | GeForce® GTX 760                              |
|------------------------------------|-----|---|
| <b>CUDA Cores</b>                  |     | 1152  |
| <b>Core Speed</b>                  |     | 980 MHz                                       |
| <b>Boost Speed</b>                 |     | 1033 MHz                                      |
| <b>Memory Size</b>                 |     | 2048 MB GDDR5                                 |
| <b>Memory Interface</b>            |     | 256-bit                                       |
| <b>Memory Frequency</b>            |     | 6008 MHz (effective)                          |
| <b>TDP</b>                         |     | 170W-Active                                   |
| <b>SLI</b>                         |     | 3-Way SLI                                     |
| <b>Multi-Screen</b>                |     | 4 Concurrent Screens*<br>NVIDIA 3D Surround** |
| <b>Outputs</b>                     |     | Two Dual-Link DVI, HDMI 1.4b, DisplayPort 1.2 |
| <b>Resolution</b>                  |     | 2560×1600 (Digital)                           |
| <b>Power Input</b>                 |     | 2 × 6-pin Aux Input                           |
| <b>Bus Type</b>                    |     | PCI-Express 3.0 16×                           |
| <b>UPC</b>                         |     | 751492567068                                  |
| <b>Card Dimensions</b>             |     | 9.5" × 4.376" Dual-Slot                       |
| <b>Box Dimensions &amp; Weight</b> |     | 12.5" × 6.38" × 2.63"<br>2.15 lbs.            |

\* 4- & 3- Screen Support only in Windows 8, Windows 7 and Windows Vista. Windows XP or earlier version will only support dual monitors.

\*\* NVIDIA® 3D SURROUND requires additional hardware, please see <http://www.nvidia.com/get3d> for detail information

\*\*\* PNY One-Year warranty will be extended to Lifetime of the original purchaser upon completion of product registration. Product must be registered on PNY's website <http://www.pny.com> within 90 days of purchase. Features and specifications subject to change without notice.

