


Manual operated press Mod. ST-702-U, utility shape boards



Universal ironing Press with padded buck and head . The movement of the upper head is operated by a pressure pedal, producing excellent results whilst being very easy to use and maintain . Buck and head are both steaming and buck is also vacuum . Available either for connection to external steam and vacuum supplies or self-contained. The built-in boiler can be powered to be connected to a second machine .

Available extras:

- Boiler
- Vacuum
- GFV iron assembly
- Sleeve spotting arm and shape.

Technical Characteristics

Required power	220/380 V./1ø3/50 Hz
Water feeding	rubber hose ø 12 mm
Steam inlet	1/2"
Return outlet	1/2"
Air inlet	
Steam working pressure	5 bar
Air working pressure	
Steam consumption	18÷20 Kg/h
Air consumption	
Central vacuum connect.	ø 100 mm
Vacuum depression	250 mm H ² o
Vacuum air consumption	400 m ³ /h
Boiler drain	1/2"
Vacuum outlet	ø 100 mm
Boiler heating	10÷12÷15÷18 KW
Iron heating element	0,8 Kw
Vacuum motor	0,4 Kw
Pump motor	0,4 Kw
Compressor motor	
Encumbrance	1300x1100 mm
Net weight with boiler	370 Kg
Gross weight	430 Kg
Overall dimensions	1400x1150x1400 mm
