

# HDR-AS100V/W

## **POV Action Cam**

Step it up with the Action Cam that brings pro-quality features along for the ride. Keep things smooth with Advanced Steady Shot™ and enjoy the convenience of built-in Wi-Fi® with remote viewing and control from your Live View Remote. All in a housing-free, splash-proof body that packs XAVC S HD recording and high frame rates in 120/240p. It's ready for the big time, are you?



## **Key Features**

## Advanced image stabilization adjusts to vibration

SteadyShot™ image stabilizing function allows smooth image shooting while the user is in motion. With the new Action Cam, the image stabilizer powerfully compensates for minute rapid vibrations typically caused by bicycle/motorcycle motion.

# New splash proof body with tripod mount

The HDR-AS100V was built with an all new splash proof body (IPX4-class). Enjoy carefree use of the Action Cam outside of its included housing3, even in rainy weather or splash-prone situations. With a universal tripod screw mount on the body of the Action Cam itself, you can easily attach the camera directly to a tripod. SteadyShot<sup>TM</sup> image stabilizing function allows smooth image shooting while the user is in motion. With the new Action Cam, the image stabilizer powerfully compensates for minute rapid vibrations typically caused by bicycle/motorcycle motion.

## View and control via smartphone/ Live View Remote<sup>1</sup>

Turn compatible smart phones and tablets in to remote control viewing devices via Wi-Fi® with One Touch Near Field Communication (NFC). Users can now control up to 5 Action Cams (HDR-AS100V) at the same time using the optional Live View Remote.

### Shoot pro quality video in XAVC-S 60p(50 Mbps)

Pro quality XAVC-S recording with 50Mbps high bit rate data transfer enables HDR-AS100V to capture quick action with smooth image motion. HDR-AS100V also supports 24p high-speed 120 fps and 240 fps shooting with sound. Additionally, users can shoot the easily shareable MP4 HD video, ideal for web.

## Plot location and display telemetry with built-in GPS

Built in GPS can be used in conjunction with the included PlayMemories™ Home software to make viewing and sharing videos fun and easy. Location and trail information as well as speed information add more layers to your ability to analyze your performance that can be captured and displayed on your video.

#### Built-In stereo mic for quality sound recording

A built-in stereo microphone allows you to capture all the exciting sounds of your adventure.

## Exmor R® CMOS sensor for superb low light shooting

Experience stunning low-light sensitivity with improved image clarity and drastically reduced grain with Sony's back-illuminated Exmor R® CMOS sensor.

### Ultra wide 170° pro quality Carl Zeiss® Vario-Tessar® lens

With an ultra-wide angle Carl Zeiss® Vario-Tessar® lens, you will increase your perspective (170-degree viewing angle) while you venture out on breathtaking views of dynamic terrain to include ski slopes and mountain trails.

#### Capture high quality 13.5MP still images in photo mode

Put your HDR-AS100V in still image mode and capture amazing high quality 13.5MP still images with a single press of the button.

# Memory Stick Micro™ and Micro SD/SDHC compatible

Expandable memory with Memory Stick Micro™ and Micro SD/SDHC card slot.

### HDMI® output for easy file transfer



With HDMI® output, you'll be able to share your Sony® HDR-AS100V video with friends and family on your HDTV (HDMI cable required/not included).

# **Specifications**

Camera	
Camera Type	Splashproof POV Action Cam
Imaging Sensor	
Imaging Sensor	1/2.3" (7.77mm) back-illuminated Exmor® R CMOS Sensor
Processor	BIONZ® X image processor
Pixel Gross	Approx.18,900K pixels
Effective Picture Resolution	Approx.13,500K pixels(16:9)
Color Filter System	RGB primary color filters
Recording	
Media Type	Memory Stick Micro $^{™}$ (Mark 2), Micro SD/SDHC Memory Card (Class 4 or Higher)
Microphone/Speaker	Built-in Microphone, Monoral Speaker
Optics/Lens	
Lens Type	Carl Zeiss® Tessar® Lens
Lens Stabilization	SteadyShot(TM) Image Stabilization
Aperture	F2.8
Focal Length (35mm equivalent)	f=17.1mm f= 11/16 inch, f=21.8mm f=7/8inch
Minimum Focus Distance	Approx.11 7/8inch (Approx.30cm)
Angle of View	170° (without SteadyShot), 120° (with SteadyShot)
Focal Distance	f=2.8mm, f=1/9inch
Steady Shot Mode:Active	21.8mm
Exposure System	
Metering Modes	Multi-segment
Exposure Settings	Auto
Scene Mode(s)	Auto/Underwater
Noise Reduction	Yes
White Balance Mode	Auto
Minimum Illumination	6 lux
Backlight Compensation	Yes (Auto)
Drive System	
Shutter Speeds	Auto Control Range: 1/30 - 1/10,000 (30fps)
Convenience Features	
Date / Time Stamp	Yes
Media/Battery Indicator	Yes (recordable time) / Yes (remaining capacity)
Multiple Language Display	English
Remote Control	Yes (REC S/S, and TC Reset only)
Advanced Features	
Waterproof	Yes (In use with Waterproof Case (SPK-AS2))
Dustproof	Yes (In use with Waterproof Case (SPK-AS2))
Airplane Mode	Yes
Embedded GPS	Yes
Image Stabilization	SteadyShot™ image stabilization w/ Active mode
Shockproof	Yes (In use with Waterproof Case (SPK-AS2))
Wi-Fi	Control with Smartphone
Interface	



Memory Card Slot       Memory Stick Micro™ and Micro SD/SDHC compatible         NFC       Yes (NFC forum Type 3 Tag compatible)         Wi-Fi       Yes (IEEE 802.11b/g/n(2.4GHz band))         SD Output       Composite Video Out(AV CABLE VMC-15MR2(sold separately))         USB Port(s)       micro-B/USB2.0 Hi-speed (mass-storage)         BRAVIA® Sync™       Yes         Microphone Input       Stereo Minijack         HDMI Terminal       HDMI Out(mini)(sold separately)         Multi/Micro USB Terminal       Yes         Wi-Fi (Opt. Acc)       Yes (NFC forum Type 3 Tag compatible)         Weights and Measurements       Approx.31/32inch x 1 7/8inch x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)         Dimensions (Approx.)       Approx.2.4oz (Approx.67g)         Accessories       Rechargeable Battery Pack(NP-BX1) Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1) Tripod Adapter (1)		
Wi-Fi Yes (IEEE 802.11b/g/n(2.4GHz band))  SD Output Composite Video Out(AV CABLE VMC-15MR2(sold separately))  USB Port(s) micro-B/USB2.0 Hi-speed (mass-storage)  BRAVIA® Sync™ Yes  Microphone Input Stereo Minijack  HDMI Terminal HDMI Out(mini)(sold separately)  Multi/Micro USB Terminal Yes  Wi-Fi (Opt. Acc) Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.) Approx.31/32inch x 1 7/8inch	Memory Card Slot	Memory Stick Micro™ and Micro SD/SDHC compatible
SD Output Composite Video Out(AV CABLE VMC-15MR2(sold separately)) USB Port(s) micro-B/USB2.0 Hi-speed (mass-storage)  BRAVIA® Sync™ Yes Microphone Input Stereo Minijack HDMI Terminal HDMI Out(mini)(sold separately)  Multi/Micro USB Terminal Yes Wi-Fi (Opt. Acc) Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.) Approx.31/32inch x 1 7/8inch x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.) Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1) Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1)	NFC	Yes (NFC forum Type 3 Tag compatible)
USB Port(s)  micro-B/USB2.0 Hi-speed (mass-storage)  BRAVIA® Sync <sup>TM</sup> Yes  Microphone Input  Stereo Minijack  HDMI Terminal  HDMI Out(mini)(sold separately)  Multi/Micro USB Terminal  Yes  Wi-Fi (Opt. Acc)  Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.)  Approx.31/32inch x 1 7/8inch  x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1)  Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	Wi-Fi	Yes (IEEE 802.11b/g/n(2.4GHz band))
BRAVIA® Sync™  Microphone Input  Stereo Minijack  HDMI Terminal  HDMI Out(mini)(sold separately)  Multi/Micro USB Terminal  Yes  Wi-Fi (Opt. Acc)  Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.)  Approx.31/32inch x 1 7/8inch  x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1)  Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	SD Output	Composite Video Out(AV CABLE VMC-15MR2(sold separately))
Microphone Input  Stereo Minijack  HDMI Terminal  HDMI Out(mini)(sold separately)  Multi/Micro USB Terminal  Yes  Wi-Fi (Opt. Acc)  Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.)  Approx.31/32inch x 1 7/8inch  x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1)  Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	USB Port(s)	micro-B/USB2.0 Hi-speed (mass-storage)
HDMI Terminal  HDMI Out(mini)(sold separately)  Multi/Micro USB Terminal  Yes  Wi-Fi (Opt. Acc)  Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.)  Approx.31/32inch x 1 7/8inch  x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1)  Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	BRAVIA® Sync™	Yes
Multi/Micro USB Terminal  Wi-Fi (Opt. Acc)  Yes (NFC forum Type 3 Tag compatible)  Weights and Measurements  Dimensions (Approx.)  Approx.31/32inch x 1 7/8inch  x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1)  Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	Microphone Input	Stereo Minijack
Wi-Fi (Opt. Acc)  Weights and Measurements  Approx.31/32inch x 1 7/8inch	HDMI Terminal	HDMI Out(mini)(sold separately)
Weights and Measurements  Approx.31/32inch x 1 7/8inch x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1) Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1)	Multi/Micro USB Terminal	Yes
Dimensions (Approx.)  Approx.31/32inch x 1 7/8inch x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1) Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1)	Wi-Fi (Opt. Acc)	Yes (NFC forum Type 3 Tag compatible)
Dimensions (Approx.)  x 3 1/4inch (Approx.24.2mm x 46.5mm x 81.5mm)  Weight (Approx.)  Approx.2.4oz (Approx.67g)  Accessories  Rechargeable Battery Pack(NP-BX1) Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1)	Weights and Measurements	
Accessories  Rechargeable Battery Pack(NP-BX1) Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1)	Dimensions (Approx.)	
Rechargeable Battery Pack(NP-BX1)  Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	Weight (Approx.)	Approx.2.4oz (Approx.67g)
Micro USB Cable (1)  "Operating Guide"(1)  Waterproof Case (SPK-AS2)(1)  Adhesive Mount (VCT-AM1)(1)	Accessories	
	Supplied Accessories	Micro USB Cable (1) "Operating Guide"(1) Waterproof Case (SPK-AS2)(1) Adhesive Mount (VCT-AM1)(1)

<sup>1.</sup> Requires NFC-compatible mobile device. Check device's user manual for compatibility. Device cases may prevent connection. Live View Remote is an optional purchase.
3. Supplied housing Waterproof down to 3 meters (15feet)
© 2014 Sony Bectonics ine. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, SteadyShot, Exmor R and the Sony logo are trademarks of Sony Corporation. Carl Zeiss is a registered trademark of Carl Zeiss, inc. All other trademarks are trademarks of their respective owners. Features and specifications subject to change without notice. J UPC:027240869738 / Updated: January 3, 2014