

StarTech.com HSB3SATSASBA disk array (HSB3SATSASBA)

StarTech.com 3 Drive Bay Aluminum Trayless Hot Swap Mobile Rack Backplane with Fan & Lock for 3.5in SAS II / SATA III - 6 Gbps Hard Drive



Price details:

Price excl. VAT: 82.79 €

Eco fees: 0.38 €

VAT 21 %: 17.47 €

Product details:

Product code: HSB3SATSASBA

EAN: 5054484575689

Manufacturer: StarTech.com

100.64 €

* VAT included

PDF generated on: 4 August, 2016

StarTech.com
Hard-to-find made easy

Easily connect and hot swap up to three 3.5" SATA/SAS hard drives from two 5.25" bays. The HSB3SATSASBA Removable 3-drive backplane lets you quickly install and hot-swap 3.5" drives from the front of your computer, by turning two 5.25" bays into a hot-swappable interface for you to connect up to three 3.5" SATA or SAS hard drives (HDD). For added versatility, the hard drive bay can interface with SATA I/II/III and SAS I/II hard drives -- an ideal accommodation for enterprise system applications. For a quick and secure method of installing and removing drives, the backplane features ejection levers and a key-lock design. To help prevent drive failure, the bay provides excellent heat dissipation with a built-in fan, and a vented solid aluminum enclosure. The HSB3SATSASBA is backed by a StarTech.com 2-year warranty and free lifetime technical support. The StarTech.com Advantage- Delivers peak drive performance, with support for full SATA III/SAS II data transfer speeds up to 6Gbps- Flexible drive options with support for both SATA and SAS drive interfaces- Helps maintain ideal drive operating temperatures by providing excellent heat dissipation, vented aluminum housing and a built-in fan

Main specifications:

Storage

Storage drives installed:	N
Supported storage drive types:	HDD
Number of storage drives supported:	3
Maximum supported storage capacity:	12 TB
Storage drive interface:	Serial ATA, Serial ATA II, Serial ATA III, Serial Attached SCSI
Storage drive size:	3.5 "
Data transfer rate:	6 Gbit/s
Hot-swap drive bays:	Y

Design

Internal:	N
Colour of product:	Black
LED indicators:	Activity, Power
Number of fans:	1
RoHS compliance:	Y

Weight & dimensions

Width:	145 mm
Depth:	194.1 mm
Package width:	125 mm
Package depth:	254 mm
Package height:	180 mm
Package weight:	1200 g

Packaging content

Cables included:

SATA

Operational conditions

Operating temperature (T-T):

0 - 55 °C

Operating relative humidity (H-H):

5 - 85 %

Storage temperature (T-T):

-20 - 60 °C

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.