

HDMI® over IP Extender with Audio


StarTech ID: IPUSB2HD2



The IPUSB2HD2 HDMI® over IP Extender delivers a versatile HDMI-IP link between PCs on your network and an HDMI monitor/projector, at full high definition (1080p, 1920x1080) video resolution. Accompanying audio signals are transmitted directly through the HDMI output, or separately through the built-on 3.5mm stereo output port.

An ideal solution for sharing a display or projector over an Ethernet network so that even PCs lacking digital video output can still connect, the IP/HDMI adapter can communicate through a network router at transmission distances up to 100m (300ft). Plus, it offers 2 USB 2.0 ports on the display side, to connect and share peripherals such as USB storage or keyboard/mouse input with the connected PC.

Alternatively, the device can be used directly connected as a USB to HDMI adapter.



Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connect multiple PCs to one display/projector on a Local Area Network and toggle between computers for presentations in your business
- With the HDMI® over IP option, distance is no longer an issue for delivering high definition video and audio content to your target audience, in retail and digital signage applications
- Home theater and media center applications include streaming movies, photos, and Internet browsing to your HDTV
- Control your PC from a remote location by connecting a keyboard or mouse to the integrated USB ports
- Use in educational settings for students to connect and display their work on a central display or projector screen for all to see

Features

- HDMI® over IP conversion for shared access over a network
- Supports resolutions up to 1920x1080 (1080p)
- Audio over HDMI, or 3.5mm connection
- Easy to use software and IP configuration utility
- Supports Windows Aero themes
- 2 USB ports for peripheral connection on the display side
- Extend or mirror your primary desktop / display

Technical Specifications

Warranty	2 Years
Ports	1
Cabling	Cat 5 UTP or better
Audio	Yes
Chipset ID	DisplayLink – DL165
Daisy-Chain	No
Output Signal	HDMI
Connector Type(s)	1 - HDMI (19 pin) Female
Connector Type(s)	1 - RJ-45 Female
Connector Type(s)	1 - USB Mini-B (5 pin) Female
Connector Type(s)	2 - 3.5 mm Mini-Jack (3 Position) Female
Connector Type(s)	2 - USB A (4 pin) Female
Maximum Data Transfer Rate	USB - 480Mbps Ethernet - 1Gbps (1000Mbps)
Max Distance	100 m / 330 ft
Maximum Digital Resolutions	1080p / 1920x1080
Wide Screen Supported	Yes
OS Compatibility	Windows® XP(32bit)/ Vista(32/64bit)/ 7(32/64bit) Aero themes supported
Microsoft WHQL Certified	Yes
Color	Black
Enclosure Type	Plastic
Product Length	5.2 in [132 mm]
Product Width	2.8 in [71 mm]
Product Height	1.1 in [28 mm]
Product Weight	4.7 oz [134 g]
Input Voltage	110 ~ 240 AC
Input Current	0.3A
Output Voltage	5 DC
Output Current	2A
Center Tip Polarity	Positive
Operating Temperature	0°C ~ 70°C (32°F ~ 158°F)
Storage Temperature	0°C ~ 85°C (32°F ~ 185°F)
Humidity	10~80% RH
Shipping (Package) Weight	1 lb [0.5 kg]
Included in Package	1 - IP or USB to HDMI Converter
Included in Package	1 - Universal Power Adapter (US/UK/EU/AUS)
Included in Package	1 - Driver and Software CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

