



Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

## StarTech.com MPEXSATA22I (MPEXSATA22I)

StarTech.com 2 Port Mini PCI Express Internal SATA II Controller Card



Price details:

Price excl. VAT: 50.12 €
Eco fees: 0.00 €
VAT 21 %: 10.53 €
Product details:

Product code: MPEXSATA22I EAN: 0065030842501 Manufacturer: StarTech.com

60.65 €

\* VAT included

PDF generated on: 4 August, 2016



Add 2 SATA ports to a small form factor or embedded system, through a Mini PCIe slotThe MPEXSATA22I 2-Port Mini PCIe to SATA Controller Card lets you add 2 SATA 3Gbps connectors to a small form factor or embedded system, through a Mini PCI Express (Mini Card) expansion slot. Perfect for upgrading the capabilities of a system that would typically have a very limited number of internal ports, the Mini PCIe to SATA controller card is compatible with all types of Serial ATA devices, including hard drives (HDDs), Solid State Drives (SSD), and optical drives (CD/DVD/BD). A versatile solution for internal storage applications, this PCI Express to SATA controller card features built-in RAID support (JBOD, BIG, RAID 0, RAID 1), and is backed by a StarTech.com 2-year warranty and free lifetime technical support. The StarTech.com Advantage- Maximizes space-efficiency by adding two independent SATA ports through Mini PCI Express, an ideal solution for embedded systems and very small form factor systems- 48-bit LBA support for large capacity hard drives and built-in RAID for either performance or redundancy- Backed by a StarTech.com 2-year warranty and free lifetime technical support

## Main specifications:

Ports & interfaces

Host interface: PCle
Output interface: SATA

Performance

Chipset: Silicon Image Sil3132CNU

RAID levels: 0,1,JBOD

Operational conditions

Operating temperature (T-T): 0 - 70 °C Storage temperature (T-T): -65 - 150 °C

Weight & dimensions

30 mm Width: Depth: 50 mm Height: 4 mm 7.8 g Weight: Package width: 145 mm 210 mm Package depth: 40 mm Package height: Package weight: 131 g

Other features

Data transfer rate: 3000 Mbit/s

Ports quantity: 2
Connectivity technology: Wired
Mac compatibility: Y

Compatible operating systems: Windows 2000/ XP(32/64-bit)/ Server 2003(32/64-bit)/ Vista(32/64-bit)/ Server 2008 R2/ 7(32/64-bit) Mac OS 10.4.9/10.4.10/10.5.1. Linux \*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed of implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.