

Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

StarTech.com MSTMDP124DP (MSTMDP124DP)

StarTech.com Mini DisplayPort to DisplayPort Multi Monitor Splitter - 4-Port MST Hub - mDP 1.2 to 4x DP MST Hub



Price details: Price excl. VAT: 111.52 € Eco fees: 0.04 € VAT 21 %: 23.43 € Product details: Product code: MSTMDP124DP EAN: 0065030861502 Manufacturer: StarTech.com PDF generated on: 21 September, 2016



134.99 €

* VAT included

This MST hub lets you connect four monitors to your Mini DisplayPort (mDP) 1.2 equipped Windows® tablet, laptop or desktop.

Increase productivity with multiple screens

The newest generations of computers are more portable than ever, which often means that you're left with fewer video outputs and smaller integrated screens. This MST hub solves both of these problems by letting you connect four additional displays to your computer, which makes multitasking much easier.

Connect to any display

With the MST hub, you can use Mini DisplayPort video adapters and cable adapters that enable you to connect HDMI, VGA or DVI displays. This ensures that your MST hub will be compatible with virtually any television, monitor or projector. The hub is VESA and DisplayPort certified to support DP 1.2 enabled systems, for seamless integration with your existing video equipment.

Configure your displays for any environment

Using the MST hub, you can extend your desktop onto additional monitors and stream independent content to each display, giving you the freedom to multitask and increase your productivity. You can also mirror the same image onto multiple displays for remote viewing applications such as digital signage.

Enjoy amazing video quality, without draining system resources

MST technology uses your existing video card to minimize the use of system resources while delivering Ultra HD 4K resolutions. This unprecedented performance makes MST perfect for high-resolution applications such as graphic design, gaming and medical imaging.

Note: When using a DisplayPort 1.1 video card the MSTMDP123DP will act as a splitter, automatically mirroring your video source across all displays. Resolution limitations apply.

The MSTMDP124DP supports plug-and-play installation for a hassle-free setup, and is backed by a StarTech.com 2year warranty and free lifetime technical support.

Notes: MST shares 21.6 Gbps across all attached displays. Higher resolutions can restrict the available bandwidth with the remaining ports, please see our guideline below for determining an ideal resolution for your setup. Certain graphics adapters have limited MST support and will only output to three displays in total. If more than three monitors are attached, the fourth will be disabled.

The surface Pro 3 only supports the use of three displays in total. If this device is used with the Surface Pro 3, and three external monitors, the built-in touch screen on your Surface will be disabled. If four monitors are attached, the fourth monitor will not display any content.

Average resolution bandwidth allocation 1920x1080 (High-definition 1080p) @60hz - 22% 1920x1200 @60hz - 30% 2560x1440 @60hz - 35% 2560x1600 @60hz - 38% Main specifications:

Ports & interfaces Host interface: Ports quantity: Hub interfaces:	Mini DisplayPort 4 DisplayPort
Performance Plug and Play: Certification:	Y CE, FCC, RoHS
Power Input voltage: Input current: Output voltage: Output current: Plug type:	100 - 240 V 0.5 A 5 V 3 A Type N (BR)
Design Colour of product:	Black
System requirements Windows operating systems supported:	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Operational conditions Operating temperature (T-T): Storage temperature (T-T):	0 - 45 °C -20 - 70 °C
Weight & dimensions Width: Depth: Height: Weight: Package width: Package depth: Package height: Package weight:	65 mm 105 mm 15 mm 127 g 65 mm 242 mm 15 mm 118 g
Packaging content AC adapter included: Included power plug types: Quick installation guide:	Y AU,EU,NA,UK Y
Other features Chipset: Maximum resolution:	STDP4320 3840 x 2160 pixels

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.