

StarTech.com PEX4S232485 (PEX4S232485)

StarTech.com 4 Port PCI Express PCIe Serial Combo Card with Breakout Cable - 2 x RS232 2 x RS422 / RS485 - Dual Profile



Price details:

Price excl. VAT: 106.19 €
Eco fees: 0.00 €
VAT 21 %: 22.30 €

PDF generated on: 24 February, 2017

Product details:

Product code: PEX4S232485
EAN: 0065030849357
Manufacturer: StarTech.com



128.49 €

* VAT included

Add two RS232, and two RS422/485 serial ports to your PC through a PCI-Express expansion slot. The PEX4S232485 4 Port PCI Express PCIe Serial Combo Card - 2 x RS232 2 x RS422 / RS485 lets you add two RS232, and two RS422/485 serial ports to your PC through a PCI-Express expansion slot. This PCI express serial card is a single card solution that is compatible with nearly any serial communication protocol, supporting RS-232, RS-422, RS-485 2-wire or RS-485 4-wire operating modes. A flexible solution for adding serial ports to full-sized, or small form factor systems, the 4-port serial card includes both low and full profile brackets while the included breakout cable helps to avoid cluttered connections. Backed by a StarTech.com lifetime warranty and free lifetime technical support. The StarTech.com Advantage- This single PCI Express combo card is compatible with any serial device protocol (RS232, RS422, and RS485), allowing for communication with multiple devices over mixed protocols- Includes both low profile/half-height and full profile brackets to ensure fitment into a broad range of system form factors- The included breakout cable saves expense as an all-in-one solution, and allows the addition of multiple serial ports through a single PCI Express slot

Main specifications:

Ports & interfaces

Internal:	Y
Host interface:	PCIe
Output interface:	Serial
Serial interface type:	RS-232/422/485
Serial ports quantity:	4

Performance

Chipset:	SystemBase SB16C1052PCI
FIFO (First In, First Out):	256 B

Design

RoHS compliance:	Y
------------------	---

System requirements

Windows operating systems supported:	Windows 2000, Windows 2000 Professional, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
--------------------------------------	---

Linux operating systems supported:	Y
------------------------------------	---

Operational conditions

Operating temperature (T-T):	0 - 100 °C
Storage temperature (T-T):	0 - 150 °C
Operating relative humidity (H-H):	20 - 80 %

Weight & dimensions

Width:	125 mm
Depth:	70 mm
Height:	20 mm
Weight:	67.4 g
Package width:	210 mm
Package depth:	145 mm
Package height:	38 mm
Package weight:	400 g

Packaging content

User guide:	Y
-------------	---

Other features

Data transfer rate:	0.4608 Mbit/s
Connectivity technology:	Wired