

Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

StarTech.com PCI Express USB 2.0 Adapter Card (PEXUSB7LP)

StarTech.com 7 Port PCI Express Low Profile High Speed USB 2.0 Adapter Card - PCIe USB 2.0 Card - PCI-E USB 2.0 Card



Price details:

Price excl. VAT: 57.32 €
Eco fees: 0.04 €
VAT 21 %: 12.05 €
Product details:

Product code: PEXUSB7LP EAN: 0065030837408 Manufacturer: StarTech.com

69.41 €

* VAT included

PDF generated on: 4 August, 2016



Add six external and one internal high speed USB 2.0 ports to any PCIe compatible PCThe PEXUSB7LP Low Profile PCIe USB 2.0 Adapter Card offers a cost-effective way to add seven USB 2.0 ports to a small form factor computer for enhanced versatility and performance. The card adds 6 external USB 2.0 slots and 1 internal USB 2.0 header port, with support for high speed USB 2.0 data transfer rates of up to 480 Mbps; to help save time, this versatile PCIe USB card includes WHQL-certified drivers and easy plug and play installation. Capable of adapting to virtually any PC case form factor, the low profile USB card includes a standard profile bracket for installation in full form factor cases. The StarTech.com Advantage- Unique design layout allows for the maximum number of USB ports to be mounted to the external bracket, while still being able to fit both small form factor and full desktop systems- Backed by a StarTech.com lifetime warranty and free lifetime technical support

Main specifications:

Ports & interfaces

Host interface: PCle
Output interface: USB 2.0
Internal: Y
USB 2.0 ports quantity: 7

Design

RoHS compliance:

Certification: CE, FCC

System requirements

Windows operating systems supported: Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7

Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows Vista

Business, Windows Vista Business x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista

Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64

Linux operating systems supported:

Server operating systems supported: Windows Server 2003, Windows Server 2003 x64, Windows Server 2008

R2

Operational conditions

Operating temperature (T-T): 0 - 60 °C Storage temperature (T-T): -20 - 85 °C Operating relative humidity (H-H): 5 - 95 %

Weight & dimensions

 Width:
 64 mm

 Depth:
 91 mm

 Height:
 18 mm

 Weight:
 57.8 g

 Package width:
 41 mm

 Package depth:
 212 mm

 Package height:
 145 mm

Other features

Data transfer rate: 480 Mbit/s

Ports quantity: 7
Connectivity technology: Wired
Quantity outer carton: 50 pc(s)

^{*}PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.