

2.5in SATA Removable Hard Drive Bay for PC Expansion Slot

Product ID: S25SLOTR



The S25SLOTR Trayless Hard Drive Rack can be installed into an available (full profile) PCI expansion card slot, providing easy access to a bare 2.5" SATA hard drive or solid state drive (SSD) from the rear panel of a computer case.

Unlike conventional hard drive enclosures, the S25SLOTR hard drive rack doesn't require that a drive be installed in a drive tray, saving the time and hassle involved in having to mount or install the hard drive for access to drive contents.

To maximize performance and utilize the full speed potential of your SATA III hard drives, this HDD Backplane supports SATA III for transfer speeds up to 6 Gbps when paired with a compatible controller.

Once installed in a PCI slot (and accompanying rear panel bracket), installing a 2.5" SATA HDD is as simple as inserting it into the trayless rack. To remove the hard drive, simply hit the eject button to unlock the access door, allowing the drive to be pulled out of the computer without having to dismount the drive.

www.startech.com/m 1 800 265 1844



Data Sheet

* This unique design of the mobile rack enables you to use any available full profile expansion slot to mount a removable 2.5in SATA hard drive.



Certifications, Reports and Compatibility

StarTechcom

Hard-to-find made easy*







Applications

- Add additional storage capabilities to a computer with no more internal or external drive bays
- Add removable storage to the rear of a system, where it is less noticeable or accessible to unauthorized users
- Add removable storage to small form factor chassis' with no standard 3.5/5.25" drive bays
- Add additional hot-swap bays to a server or workstation computer
- System builders who need to image drives quickly and efficiently
- Environments where drives need to be replaced/removed regularly, without external protection for the drives required after removal
- Be able to replace/remove individual drives from a storage array with minimal or no system down time

Features

- Fits a 2.5" SATA drive into a rear full profile expansion card slot
- Trayless design: drive is not mounted into a tray or enclosure
- Latching drive door
- 50,000+ insertion rating
- Vented aluminum and steel construction
- Door mounted Power/Activity LED indicator
- Support for SATA revision I/II/III (1.5/3.0/6.0 Gbps)
- Supports 2.5" form factor SATA hard drives (HDD) and solid state drives (SSD)
- Plug-and-Play and Hot-Swap compatible

StarTechcom

Hard-to-find made easy*

Data Sheet

Hardware Waranty 2 Years Auge bille Drive Types SATA Drive Installation Removable Drive Size 2.5/n Fan(s) No Performance Hot Swap Capability Yes Max Drive Capacity Tested up to 500 GB 1 Connector(s) Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Host Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Max Drive Explore 1 - SATA (2 pin, Molex Large Drive Power) Male 1 - SATA Power (15 pin) Ruceptacle 1 - SATA (2 pin, Molex Large Drive Power) Male Max Drive Explore Solid - Power On Binking Activity Solid - Power On Solid - Power On Solid - Power On Binking Activity			
Drive Installation Removable Drive Size 2.Sin Fan(s) No Number of Drives 1 Performance Hot Swap Capability Yes Max Drive Capacity Tested up to 500 GB Connector(s) Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Host Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug Software OS Compatibility OS independent; No software or drivers required Indicators LED Indicators Solid - Power On Bilinking - Activity Bilinking - Activity Forger Temperature OP conspect of SPC (23PF to 131PF) Softage Temperature Soft of SPC (23PF to 131PF) Softage Temperature Soft of SPC (23PF to 131PF) Product Height Aluminum and Steel Max Drive Height Alum [9.5 mm] Product Height Soft or SPC (12PF to 131PF) Product Weight Soft or SPC (12PF to 131PF) Product Weight Soft or SPC (12PF to 131PF) Product Weight Soft or SPC (23PF to 131PF) Product Weight <t< th=""><th></th><th>Warranty</th><th>2 Years</th></t<>		Warranty	2 Years
Drive Size 2.5in Fan(s) No Number of Drives 1 Performance Hot Swap Capability Yes Max Drive Capacity 1 = SATA Data & Power Combo (7+15 pin) Receptacle Formance Hot Sconnectors 1 = SATA Data & Power Combo (7+15 pin) Receptacle Formance Hot Connectors 1 = SATA Data & Power Combo (7+15 pin) Receptacle Formance Hot Connectors 1 = SATA Optic & Power One Formance Software OS Compatibility OS independent; No software or drivers required Formance Minidity Software On Software OC to SSPC (32°F to 131°F) Foroage Temperature OC to SSPC (32°F to 131°F) Software Foroage Temperature OC to SSPC (32°F to 131°F) Software Foroage Temperature OPorating Temperature OC to SSPC (32°F to 131°F) Foroage Temperature Oforuct Height Aluminum and Steel Max Drive Height OL in [0.5 mm] Software Product Height Soft ISS (120° mm] Software Product Weight Soft ISS (110° mm] Soft ISS (110° mm]	Hardware	Compatible Drive Types	SATA
Fan(s) No Number of Drives 1 Performance Hot Swap Capability Yes Max Drive Capacity Tested up to 500 GB Onnector(s) Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Host Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug Tore 1 - SATA Data & Power Combo (7+15 pin) Receptacle Max Drive Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug 1 - SATA Power (15 pin) Plug Software OS Compatibility OS Independent; No software or drivers required Indicators Humidity 80% RH Operating Temperature -90 Cto 55°C (23°F to 131°F) Storage Temperature -90 Cto 55°C (23°F to 131°F) Max Drive Height 04 in [9.5 mm] Product Length 5.6 oz [158.4 g] Product Length 5.6 oz [158.4 g] Product Weight 5.6 oz [158.4 g] Product Weight 0.6 ls [1 mm]		Drive Installation	Removable
Number of Drives 1 Performance Not Swap Capability Yes Max Drive Capacity Tested up to 500 GB Onnector(s) Prive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Not Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug 1 - SATA (7 pin, Data) Plug 1 - SATA Power (15 pin) Plug 1 - SATA Power (15 pin) Plug Software OS Compatibility OS Independent; No software or drivers required Indicators LED Indicators 0% RH Operating Temperature 0% C to 55°C (23°F to 131°F) Storage Temperature -Soft to 55°C (23°F to 163°F) Max Drive Height 04 in [9.5 mm] Max Drive Height 04 in [9.5 mm] Max Drive Height 04 in [9.5 mm] Product Length 5.6 or [158.4 g] Product Length 5.6 or [158.4 g] Product Weight 5.6 in [21 mm] Product Weight 0.6 in [21 mm] Product Weight 5.6 in [21 mm] <td></td> <td>Drive Size</td> <td>2.5in</td>		Drive Size	2.5in
Performance Hot Swap Capability Yes Max Drive Capacity Tested up to 500 GB Connector(s) Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Hot SC Onnectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug 1 - SATA Power (15 pin) Plug 1 - SATA Power (15 pin) Plug 1 - SATA Power (15 pin) Plug Software OS Compatibility OS independent; No software or drivers required Indicators LED Indicators Binking - Activity Environmental Humidity 80% RH Operating Temperature 0°C to 55°C (32°F to 131°F) Storage Temperature -5°C to 75°C (23°F to 167°F) Physical Max Drive Height Aluminum and Steel Max Drive Height 0.4 in [9.5 mm] Product Height 5.6 oz [158.4 g] Product Weight 5.6 oz [158.4 g] Product Weight 0.3 lb [0.1 kg] Thermation Shipping (Package) Weight 0.3 lb [0.1 kg] Physical Included in Package 1 - Expansion Slot Removable HDD bracket 1 - 200 SATA cable 1 - UP4 SATA brekotu cable <td></td> <td>Fan(s)</td> <td>No</td>		Fan(s)	No
Max Drive Capacity Tested up to 500 GB Connector(s) Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Host Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug 1 - SATA Power (15 pin) Plug 1 - SATA Power (15 pin) Plug Software OS Compatibility OS independent; No software or drivers required Indicators LED Indicators Binking: - Activity Environmental Humidity 80% RH Operating Temperature 0°C to 55°C (32°F to 157°F) Storage Temperature -5°C to 75°C (23°F to 167°F) Physical Color Black Color Aluminum and Steel Max Drive Height 0.4 in [9.5 mm] Product Height 5.7 in [145 mm] Product Weight 5.6 oz [158.4 g] Product Weight 0.3 lb [0.1 kg] Thormation Shipping (Package) Weight 0.3 lb [0.1 kg] Lexpansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable		Number of Drives	1
Connector(s) Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle Host Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA Power (15 pin) Plug Software OS Compatibility Divice Tommental LED Indicators Humidity So% RH Operating Temperature 0°C to 55°C (32°F to 131°F) Storage Temperature -5°C to 75°C (23°F to 131°F) Storage Temperature -5°C to 75°C (32°F to 131°F) Physical Color Max Drive Height 0.4 in [9.5 mm] Product Height 4.7 in [120 mm] Product Weight 5.6 oz [158.4 g] Product Width 0.8 in [21 mm] Packaging Shipping (Package) Weight 0.3 lb [0.1 kg] What's in the Box Include in Package 1 - Expansion Slot Removable HDD bracket 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable	Performance	Hot Swap Capability	Yes
Host Connectors 1 - LP4 (4 pin, Molex Large Drive Power) Male 1 - SATA (7 pin, Data) Plug - SATA Power (15 pin) Plug - SATA Power (15 pin) Plug - SATA Power (15 pin) Plug - SATA Power On - SATA Power On - Software Software OS Compatibility OS independent; No software or drivers required Indicators ED Indicators - Solid - Power On - Solid - Solid - Solid - Power On - Solid - Soli		Max Drive Capacity	Tested up to 500 GB
1 - SATA (7 pin, Data) Plug 1 - SATA Power (15 pin) PlugSoftware0S CompatibilityOS independent; No software or drivers requiredIndicatorsLED Indicators1 - Solid - Power On Blinking - ActivityEnvironmentalHumidity80% RH Operating TemperatureOperating Temperature0°C to 55°C (32°F to 131°F) Storage TemperaturePhysical CharacteristicsColorBlackEnclosure TypeAluminum and Steel Max Drive Height0.4 in [9.5 mm] Product HeightProduct Length5.7 in [145 mm] Product Uwight5.6 oz [158.4 g] 0.8 in [21 mm]Packaging InformationShiping (Package) Weight0.3 lb [0.1 kg]What's in the BoxIncluded in Package1 - Expansion Slot Removable HDD bracket 1 - Deri SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film	Connector(s)	Drive Connectors	1 - SATA Data & Power Combo (7+15 pin) Receptacle
Software0S Compatibility0S independent; No software or drivers requiredIndicatorsLED Indicators1 - SOId - Power On Blinking - ActivityEnvironmentalHumidity80% RHOperating Temperature0°C to 55°C (32°F to 131°F) Storage TemperaturePhysical CharacteristicsColorBlackEnclosure TypeAluminum and Steel Max Drive Height0.4 in [9.5 mm] 9.7 in [145 mm]Product Height5.7 in [145 mm]Product Udith5.6 oz [158.4 g] 9.8 in [21 mm]Packaging InformationShiping (Package) Weight0.8 in [21 mm]What's in the BoxIncluded in Package 4.1 in Package1 - Expansion Slot Removable HDD bracket 1 - EVPA ATA breakout cable 1 - Hard Drive Protective Film		Host Connectors	1 - LP4 (4 pin, Molex Large Drive Power) Male
SoftwareOS CompatibilityOS independent; No software or drivers requiredIndicatorsLED Indicators1 - Solid - Power On Blinking - ActivityEnvironmentalHumidity80% RHOperating Temperature0°C to 55°C (32°F to 131°F) -5°C to 75°C (23°F to 167°F)Physical CharacteristicsColorBlackEnclosure TypeAluminum and Steel Max Drive Height0.4 in [9.5 mm] -5°C in [145 mm]Product Height5.7 in [120 mm]Product Weight5.6 oz [158.4 g] -0.8 in [21 mm]Product Width0.3 lb [0.1 kg]What's in the BoxIncluded in Package) Weight1 - Expansion Slot Removable HDD bracket - 20in SATA cable - 1 - LP4 SATA breakout cable - 1 - Hard Drive Protective Film			1 - SATA (7 pin, Data) Plug
Indicators LED Indicators 1 - Solid - Power On Blinking - Activity Environmental Humidity 80% RH Operating Temperature 0°C to 55°C (32°F to 131°F) Storage Temperature -5°C to 75°C (23°F to 167°F) Physical Characteristics Color Black Enclosure Type Aluminum and Steel Max Drive Height 0.4 in [9.5 mm] Product Height 5.7 in [120 mm] Product Height 5.6 oz [158.4 g] Product Weight 5.6 oz [158.4 g] Product Weight 0.3 lb [0.1 kg] Mat's in the Box Included in Package 1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film			1 - SATA Power (15 pin) Plug
Binking - Activity Environmental Humidity 80% RH Operating Temperature 0°C to 55°C (32°F to 131°F) Storage Temperature -5°C to 75°C (23°F to 167°F) Physical Characteristics Color Black Physical Characteristics Findosure Type Aluminum and Steel Max Drive Height 0.4 in [9.5 mm] 1 Product Height 0.4 in [9.5 mm] 1 Product Length 5.7 in [145 mm] 1 Product Length 5.6 oz [158.4 g] 1 Product Weight 0.3 lb [0.1 kg] 1 Product Weight 0.3 lb [0.1 kg] 1 Product Weight 1.2 in SATA cable 1 Humit's in the Box Included in Package 1 Hut's in the Box Include in Package 1 Hut's in the Box Include in Package 1	Software	OS Compatibility	OS independent; No software or drivers required
Operating Temperature Storage Temperature0°C to 55°C (32°F to 131°F) 50°C to 75°C (23°F to 167°F)Physical CharacteristicsColorBlackEnclosure TypeAluminum and SteelMax Drive Height0.4 in [9.5 mm]Product Height4.7 in [120 mm]Product Length5.7 in [145 mm]Product Weight5.6 oz [158.4 g]Product Width0.8 in [21 mm]Packaging InformationShipping (Package) Weight1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film	Indicators	LED Indicators	
Storage Temperature-5°C to 75°C (23°F to 167°F)Physical CharacteristicsColorBlackEnclosure TypeAluminum and SteelMax Drive Height0.4 in [9.5 mm]Product Height4.7 in [120 mm]Product Length5.7 in [145 mm]Product Weight5.6 oz [158.4 g]Product Width0.8 in [21 mm]Packaging InformationShipping (Package) Weight0.3 lb [0.1 kg]What's in the BoxIncluded in PackageIncluded in Package1 - Expansion Slot Removable HDD bracket1 - 20in SATA cable1 - Hard Drive Protective Film	Environmental	Humidity	80% RH
Physical Characteristics Color Black Enclosure Type Aluminum and Steel Max Drive Height 0.4 in [9.5 mm] Product Height 4.7 in [120 mm] Product Length 5.7 in [145 mm] Product Weight 5.6 oz [158.4 g] Product Width 0.8 in [21 mm] Packaging Information Shipping (Package) Weight 0.3 lb [0.1 kg] What's in the Box Included in Package 1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable		Operating Temperature	0°C to 55°C (32°F to 131°F)
Characteristics Enclosure Type Aluminum and Steel Max Drive Height 0.4 in [9.5 mm] Product Height 4.7 in [120 mm] Product Length 5.7 in [145 mm] Product Weight 5.6 oz [158.4 g] Product Width 0.8 in [21 mm] Product Width 0.3 lb [0.1 kg] Phat's in the Box Included in Package) Weight 1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable		Storage Temperature	-5°C to 75°C (23°F to 167°F)
Max Drive Height 0.4 in [9.5 mm] Product Height 4.7 in [120 mm] Product Length 5.7 in [145 mm] Product Weight 5.6 oz [158.4 g] Product Width 0.8 in [21 mm] Packaging Information Shipping (Package) Weight 0.3 lb [0.1 kg] What's in the Box Included in Package 1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable	•	Color	Black
Product Height4.7 in [120 mm]Product Length5.7 in [145 mm]Product Weight5.6 oz [158.4 g]Product Width0.8 in [21 mm]Packaging InformationShipping (Package) Weight0.3 lb [0.1 kg]What's in the BoxIncluded in Package1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film		Enclosure Type	Aluminum and Steel
Product Length5.7 in [145 mm]Product Weight5.6 oz [158.4 g]Product Width0.8 in [21 mm]Packaging InformationShipping (Package) Weight0.3 lb [0.1 kg]What's in the BoxIncluded in PackageIncluded in Package1 - Expansion Slot Removable HDD bracket1 - 20in SATA cable1 - LP4 SATA breakout cable1 - Hard Drive Protective Film		Max Drive Height	0.4 in [9.5 mm]
Product Weight Product Width5.6 oz [158.4 g]Packaging InformationShipping (Package) Weight0.3 lb [0.1 kg]What's in the BoxIncluded in Package1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film		Product Height	4.7 in [120 mm]
Product Width0.8 in [21 mm]Packaging InformationShipping (Package) Weight0.3 lb [0.1 kg]What's in the BoxIncluded in Package1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film		Product Length	5.7 in [145 mm]
Packaging Information Shipping (Package) Weight 0.3 lb [0.1 kg] What's in the Box Included in Package 1 - Expansion Slot Removable HDD bracket I - 20in SATA cable 1 - LP4 SATA breakout cable 1 - LP4 SATA breakout cable I - Hard Drive Protective Film 1 - Hard Drive Protective Film		Product Weight	5.6 oz [158.4 g]
Information What's in the Box Included in Package 1 - Expansion Slot Removable HDD bracket 1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film		Product Width	0.8 in [21 mm]
1 - 20in SATA cable 1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film		Shipping (Package) Weight	0.3 lb [0.1 kg]
1 - LP4 SATA breakout cable 1 - Hard Drive Protective Film	What's in the Box	Included in Package	1 - Expansion Slot Removable HDD bracket
1 - Hard Drive Protective Film			1 - 20in SATA cable
			1 - LP4 SATA breakout cable
1 - Mounting Screws			1 - Hard Drive Protective Film
			1 - Mounting Screws

www.startech.com/m 1 800 265 1844



Data Sheet

1 - Instruction Manual

Product appearance and specifications are subject to change without notice.

www.startech.com/m 1 800 265 1844