

StarTech.com SDOCKU313 (SDOCKU313)

StarTech.com USB 3.1 (10Gbps) Single-Bay Dock for 2.5"/3.5" SATA SSD/HDDs - Supports SATA I, II, III and UASP - Top-loading design



Price details:

Price excl. VAT: 54.31 €

Eco fees: 0.00 €

VAT 21 %: 11.41 €

Product details:

Product code: SDOCKU313

EAN: 0065030861656

Manufacturer: StarTech.com

65.72 €

* VAT included

PDF generated on: 24 February, 2017

StarTech.com
Hard-to-find made easy

Unleash the power of USB 3.1 Gen 2 (10 Gbps) with this single-drive docking station. It supports both 2.5" and 3.5" form factors for solid-state and hard drives, with a high drive capacity of 6TB.

Harness the speed of USB 3.1 Gen 2

USB 3.1 Gen 2 gives you greater bandwidth and speed with file transfer rates of up to 10 Gbps - twice the speed of USB 3.0 (USB 3.1 Gen 1) technology. It lets you leverage the high performance of the latest SSDs and hard drives, while alleviating bottlenecks in your data transfers.

Top-loading design for easy drive access

It's never been easier to dock and swap drives from your desktop computer or laptop. Simply insert your drives into the top loading slot, with no tools or trays required. The HDD ejection button allows fast and simple drive removal.

Convenient compatibility

The docking station comes with a USB Type-A to B cable, providing backward compatibility with your existing USB 3.0, 2.0 and 1.x devices. It also supports UASP for enhanced performance.

The SDOCKU313 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Main specifications:

Hard drive

Storage media type:	HDD,SSD
Storage drive interface:	Serial ATA III
Storage drive sizes supported:	2.5,3.5 "
Number of storage drives supported:	1
Maximum storage capacity:	6 TB

Ports & interfaces

Host interface:	USB 3.1 (3.1 Gen 2) Type micro-B
USB 3.1 (3.1 Gen 2) ports quantity:	1
DC-in jack:	Y

Technical details

Maximum data transfer rate:	10 Gbit/s
Colour of product:	Black
Material:	Plastic
UASP support:	Y
Chipset:	ASMedia - ASM1351

Cooling

Fan:	N
------	---

Power

AC input voltage:	110-240 V
Input current:	0.8 A
Output voltage:	12 V
Output current:	2 A
Plug type:	Type M

Weight & dimensions

Width:	92.7 mm
Depth:	144.8 mm
Height:	63.6 mm
Weight:	398 g

Packaging data

Package dimensions (WxDxH):	91.52 x 160 x 170 mm
Package weight:	804 g

Packaging content

AC adapter included:	Y
Cables included:	USB
Included power plug types:	AU,EU,NA,UK
Quick installation guide:	Y

Indication

LED indicators:	Activity,Power
-----------------	----------------

Operational conditions

Operating temperature (T-T):	5 - 35 °C
Storage temperature (T-T):	-20 - 50 °C
Operating relative humidity (H-H):	20 - 80 %

Certificates

Certification:	CE, FCC
RoHS compliance:	Y