

StarTech.com SFPC1110 network transceiver module (SFPC1110)

StarTech.com Cisco Compatible Gigabit RJ45 Copper SFP Transceiver Module Mini-GBIC - 10/100/1000Base-T Copper SFP Module



Price details:

Price excl. VAT: 65.56 €

Eco fees: 0.00 €

VAT 21 %: 13.77 €

Product details:

Product code: SFPC1110

EAN: 0065030846202

Manufacturer: StarTech.com

79.33 €

* VAT included

PDF generated on: 24 February, 2017

StarTech.com
Hard-to-find made easy

The SFPC1110 Cisco Compatible Gigabit RJ45 Copper SFP Transceiver Module (Mini-GBIC) is built to comply with MSA (Multi-Sourcing Agreement) standards to offer a cost-effective way to add, replace or upgrade a copper Ethernet port on your 1000 Base-T networking equipment.

Featuring Digital Diagnostics Monitoring support and 1000 Mbps Auto-negotiation at distances up to 100m (330 feet), this Ethernet SFP module can be installed into any fiber networking devices with an MSA or Cisco compliant SFP port. Delivering convenience and scalability, this copper transceiver is fully hot-pluggable, allowing you to install the module without interrupting network traffic or requiring a device reboot.

This SFP module is compatible with the Cisco SFP-GE-T transceiver.

Backed by a StarTech.com lifetime warranty and free lifetime technical support.

The StarTech.com Advantage

- Fully compliant with MSA standards, this hot pluggable module can be installed into any networking device with an MSA compliant or Cisco compliant port
- A convenient way to add a copper connection to an SFP type switch that would typically be used for fiber SFPs

Main specifications:

Networking

Data transfer rate (max):	1250 Mbit/s
Interface type:	SFP
Fiber optic connector:	SFP
Networking standards:	IEEE 802.3ab
Ethernet LAN (RJ-45) ports:	1
Cabling technology:	1000BASE-T

Performance

Colour of product:	Silver
Hot-Plug support:	Y
Auto-negotiation:	Y
Auto MDI/MDI-X:	Y
Maximum transfer distance:	100 m
Cable type:	Copper
Digital Diagnostics Monitoring (DDM):	Y

Operational conditions

Operating temperature (T-T):	0 - 70 °C
------------------------------	-----------

Storage temperature (T-T):	-40 - 85 °C
Operating relative humidity (H-H):	30 - 70 %

Weight & dimensions

Width:	13 mm
Depth:	70 mm
Height:	13 mm
Weight:	21 g
Package width:	90 mm
Package depth:	118 mm
Package height:	30 mm
Package weight:	100 g

Certificates

Certification:	CE, FCC, UL
RoHS compliance:	Y

Packaging content

Number of products included:	1 pc(s)
------------------------------	---------