





Interface		RS-232 / Printer	
Model		UTM1925B	UTP1025B
Product			
Description		USB to RS-232 / Printer Hub	USB to Printer Adapter
Controller		Moschip MCS7715 16C550 UART Compatible	Prolific 2305
Bus Interface		Universal Serial Bus (USB) 2.0 / 1.1	
IRQ & IO		Assigned by system	
Serial Communication	No. of Port	1-port	—
	Board Connector	DB9 Male	—
	FIFO	16byte (Hardware)	—
	Signal	TxD,RxD,RTS,CTS,DTR,DSR,DCD,GND, RI	—
	Baud rate	50bps ~ 115.2Kbps	—
	Data bit	5,6,7,8	—
	Stop bit	1,1.5,2	—
	Parity	None, Even,Odd, Space,Mark	—
	Flow Control	RTS/CTS(Hardware) XON/XOFF(Software)	—
ESD Protection for RS-232 I/O		±15KV Human Body Model (HBM)	—
Parallel Communication	No. of Port	1-port	1-port
	Mode	SPP Mode (Support Printer only)	SPP Mode (Support Printer only)
	Cable Connectors	DB25 Female	DB25 Female
	ESD Protection for Parallel I/O	±2KV Human Body Model (HBM)	±2KV Human Body Model (HBM)
Driver Support		Microsoft Windows 98/ME/2000/XP/ 2003/Vista (32bit) Microsoft Windows CE.5 Linux 2.6.x	Microsoft Windows 98/ME/2000/XP/ 2003/Vista (32bit)
Regulatory Approvals	Hardware	EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Part 15 Class B, RoHS	
	Software	N.A.	Microsoft WHQL Window XP / Vista
Environment	Operating Temperature	0 to 60°C (32 to 140°F)	
	Operating Humidity	5% to 95% RH	
	Storage Temperature	-20 to E28 (-4 to 185°F)	
Power	Input	USB Bus-power	
	Consumption	< 1W = 5V x 200mA	
Mechanical	Dimensions	75 (W) x 40 (D) x 22 (H) mm	
	Cable Length	1500mm (5ft)	
	Case	ABS	
	Weight	140 ± 5 g	95 ± 5 g