

PANBASE

SecurityMan®

Remote Control Pan Base for camera



Features

- Works great with wired/wireless security cameras
- 370° rotation range
- Convenient 12V DC output for security camera
- 2 button remote for power and rotation direction with red L.E.D. indicator
- 433MHz wireless remote
- Up to 150 ft remote distance
- Sleek compact design
- Easy installation

Mount on a flat surface



Mount upside-down on the ceiling



The SecurityMan **PANBASE** is a remote control pan base for wired/wireless camera. **PANBASE** allows you to rotate your wired/wireless video camera left and right with 370° viewing range and remotely position a camera to any desired angle with a remote control.

Package includes:

- Pan base body
- Remote controller
- Power adaptor
- Mounting bracket and accessories
- User manual

Specification

Remote Control:

RF Output Power	0dBm
RF Transmitter Frequency	433.92MHz
Battery	12V DC GP23A battery
Transmitter Current	20mA
Maintain Current	40nA
Dimension	3.7" x 1.9" x 1.1"
Weight	40g

Pan Base:

RF Receiver Sensible	-80dBm(excel)
RF Receiver frequency	433.92MHz
Auto/Remote scanning angle	370°
Manual Adjust angle	75°Max
Speed of Scanning	50 seconds/change
Max load	500g
Noise (away 30cm unload)	Less Than 40dB
Power Supply and Out Power:	Output 12VDC 200mA Input 15VAC 400mA
Dimension	3.9" x 3.9" x 3.9"
Weight	320 g
Operation temperature range	-10°~50°
Remote control range	Up to 150ft (line of sight)