



2 Port USB Cable KVM Switch

SY-KVM20051

**User Guide** 

Specifications and products are subject to change without prior notice

All trade name referenced are the registered trademark of their respective owners



# **Package Contents**

1 SY-KVM20051 2-Port USB Cable KVM Switch with 6 ft (1.8m) Remote Selection Switch

1 User Guide

## **Hardware Requirements**

#### Console


- · A VGA, SVGA, XGA, SXGA, or multisync monitor
- · A USB Keyboard
- · A USB Mouse

## Computers

The following must be installed on each computer that is connected to the system:

- · A VGA, SVGA, XGA, SXGA, or Multisync video port
- ·Two USB Type A port


#### **Hardware Review**



- 1. Console Monitor Port
- 2. Console USB Keyboard / Mouse Port
- 3. Port LEDs
- 4. KVM Cables
- 5. Remote Selection Switch
- 6. USB Keyboard and Mouse Connectors
- 7. Video Connector

# Hardware Installation

- · Before beginning the installation procedure, ensure that all equipment to be connected is powered off.
- To prevent damage to your installation, make sure that all devices are properly grounded



- 1. Plug your keyboard, monitor and mouse into their ports on the SY-KVM20051. The USB keyboard and USB mouse ports are labeled with an icon to distinguish them.
- 2. Plug the USB and video connectors of the attached KVM cables into their respective ports on the computers you are installing.
- 3. Position the Remote Switch within reach on your desktop.
- 4. Turn on the power to the computers.

Note: The SY-KVM20051 power on default is to link to the first computer you power on.

### Specifications

Function			SY-KVM20051
Computer Connections			2
Port Selection			Remote Selection Switch
Connectors	Console	Keyboard	1 x USB Type A Female (Black)
	Ports	Video	1 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (Black)
	KVM	Keyboard /	2 x USB Type A Male (Black)
	Ports	Mouse	
		Video	2 x HDB-15 Male (Blue)
LEDs	Selected		2
Cable Length	Computers		3 ft (0.9 m)
	Remote Selection Switch		6 ft (1.8 m)
Video			2048 x 1536, DDC2B
Environment	Operating Temp.		32 ~ 122°F (0 ~ 50°C)
	Storage Temp.		-4 ~ 140°F (-20 ~ 60°C)
	Humidity		0-80% RH, Non-condensing
Physical	Housing		Plastic
Properties	Weight		0.68 lb (0.31 kg)
	Dimensions		0.27 x 0.25 x 0.08 ft
	(L x W x H)		(8.24 X 7.71 X 2.46 cm)