



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: B123-001-60

1-ft. HDMI Active Signal Extender Cable (HDMI M/F)

Highlights



- Extend a 1080p (60Hz) HDMI signal up to 125 ft. from the source
- When extending a 1080p (60Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's B123-001-60 HDMI Signal Extender increases the distance a 1080p (60Hz) signal can be transmitted beyond the recommended 16 ft. (5 m.). It supports video resolutions up to 1080p, and a maximum distance of 125 ft. from the source. Use P568-Series HDMI cables in most applications. When extending a 1080p (60Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order) 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable. Simply connect the longer cable between the source and the B123-001-60, and the shorter cable (16 ft. or less) between the adapter and the monitor/TV. Software or drivers are not required. Built-in Equalization control to adjust the video image. HDCP compliant. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Package Includes



- B123-001-60 HDMI Active Extender
- External Power Supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- Screwdriver for Equalization adjustment

Features

- Extend a 1080p (60Hz) HDMI signal up to 125 ft. from the source
 - Use P568-Series HDMI cables in most applications
 - When extending a 1080p (60Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD.
 - Lengths over 100 ft. are available from Tripp Lite as a custom order)
 - 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
 - Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
 - Built-in Equalization control to adjust the video image
 - HDCP compliant
 - No software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Display Style	Signal Booster
INPUT	

Cable Length (ft.)	1
Cable Length (m)	0.30
CONNECTIONS	
Connector A	 HDMI (MALE)
Connector B	 HDMI (FEMALE)
Number of Connectors	2

Related Items

Required Products

Related Model	Description	Qty.
P568-025	25-ft. High Speed v1.3 HDMI Digital Video Gold Cable (HDMI M/M)	1
P568-050	50-ft. High Speed v1.3 HDMI Digital Video Gold Cable (HDMI M/M)	1
P568-100-HD	100-ft. 24AWG High Definition High Speed HDMI Digital Video Gold Cable (HDMI M/M)	1

Optional Products

Related Model	Description	Qty.
B123-001	1-ft. HDMI Active Signal Extender Cable (HDMI M/F)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5060.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.