



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B140-101-WP

DVI over Cat5 Passive Extender Wallplate Kit

Highlights

- Extend a DVI-D Single-Link signal up to 100 ft. at 1024 x 768 (60Hz), or up to 50 ft. at 1920 x 1080 (60Hz), when using 24Awg, solid wire Cat5e/6 cabling. (Tripp Lite N022-01K-GY or N222-01K-GY)
- Compatible with all operating systems; no software or drivers required.
- No external power required.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.



Description

The Tripp Lite B140-101-WP DVI over Cat5 Passive Extender Kit is the perfect solution for those who need a wallplate solution that extends a DVI-D Single-Link signal up to 100 ft. from the source. When using 24Awg, solid wire Cat5e/6 cabling (Tripp Lite N022-01K-GY or N222-01K-GY), the B140-101-WP can extend a 1024 x 768 (60Hz) signal up to 100 ft., or a 1920 x 1080 (60Hz) signal up to 50 ft.. Installation is quick and easy: Simply punch down Cat5e/6 bulk cabling between the two wallplates, and connect the wallplates to the source and monitor using standard DVI-D Single-Link cables (Tripp Lite P561-Series). The signal will be sent with perfect video quality. Wallplates mount in standard in-wall electrical boxes or surface mount boxes. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

- Computer with DVI video card, and monitor with DVI input.



Package Includes

- B140-101-WP local wallplate
- B140-101-WP remote wallplate
- 110 punchdown tool
- Wallplate screws
- Owner's manual

Features

- 2 piece kit includes both local transmitter and remote receiver wallplates
- Extend a DVI-D Single-Link signal up to 100 ft. at 1024 x 768 (60Hz), or up to 50 ft. at 1920 x 1080 (60Hz), when using 24Awg, solid wire Cat5e/6 cabling. (Tripp Lite N022-01K-GY or N222-01K-GY)
- No external power supply required.
- No software or drivers required.
- HDCP and DDC compatible
- Compatible with all operating systems.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Specifications

OVERVIEW	
Display Style	Cat5 Extender; Kit
LEDS ALARMS & SWITCHES	
LED Indicators	The LED on the local unit illuminates to indicate it is connected to, and receiving power from, the source. The LED on the remote unit illuminates to indicate it is connected to, and receiving power from, the monitor.
PHYSICAL	
Color	White
CONNECTIONS	
Connector A	 (X2) DVI-I (FEMALE)
Connector B	 (X2) 110 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Recommended Products

Related Model	Description	Qty.
N046-000	110/66 Punch Down Installation Tool for Cat6a/Cat6/Cat5e/Cat5/Network Cable	1
N022-01K-GY	1000-ft. Cat5e 350MHz Bulk Solid-core PVC Cable - Gray	1
N222-01K-GY	1000-ft. Cat6 Gigabit Bulk Solid PVC Cable - Gray	1

Optional Products

Related Model	Description	Qty.
N048-000	Round/Flat Cable Stripping Tool for Cat6a/Cat6/Cat5e/Cat5/Network Cable	1
N202-025-BL	25-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-050-BL	50-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-075-BL	75-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
N202-100-BL	100-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M) - Blue	1
P561-006	6-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
P561-010	10-ft. DVI Single Link TMDS Cable (DVI-D M/M)	1
B140-101	DVI Over CAT5 2pc Extender Kit	1
B140-101X	DVI Over CAT5 2pc Super - Extender Kit up to 200ft	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4458.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.