



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SRCOOLNET

External SNMP/Web Card Module for Remote Cooling Management and Monitoring of IT Equipment in Small Server Rooms and Network Closets

Highlights



- External SNMP/Web management accessory card module for use with the SRCOOL12K or SRXCOOL12K Portable Air Conditioning Unit
- Enables remote monitoring and management of cooling in back offices, computer rooms, small server rooms and network closets
- Monitor temperatures, receive alerts, review logs and control settings from any location
- Simple installation and setup

Description

The SRCOOLNET adds remote SNMP monitoring and management capabilities to the updated SRCOOL12K and SRXCOOL12K Portable Air Conditioning Units. The SRCOOLNET includes the EnviroSense temperature and humidity module and mounting hardware for easy installation. The unit provides the ability to remotely adjust fan speed, cooling temperature, and dehumidification modes. The included EnviroSense module can be used instead of the temperature sensor within the SR(X)COOL12K to monitor ambient conditions and to control the temperature set point of the SR(X)COOL12K. This helps ensure that supply air to important equipment is at or below a target temperature in cases where SR(X)COOL12K is indirectly supplying cold air to that equipment. The included AC power adapter supports 100-240V worldwide voltage capability with either the NEMA 1-15R or CEE7 SCHUKO snap-in plug adapters.

Note: the SRCOOLNET supports only the updated SRCOOL12K (AC8794 and newer sku's) and SRXCOOL12K (AC8842 and newer sku's)

Package Includes

- SRCOOLNET
- EnviroSense Module
- Mounting Hardware
- Software CD
- Manuals

Features

- Turns the SRCOOL12K and SRXCOOL12K Portable Air Conditioning Units into managed devices on the network using SNMP network management platform or a web browser
- Included ENVIROSENSE module provides remote monitoring of temperature and humidity
- Included PowerAlert Software provides a single interface for both the SRCOOL12K/SRXCOOL12K and the ENVIROSENSE module

Specifications

INPUT	
Nominal input voltage description	100-240 VAC ; 60Hz
Plug Type	NEMA 5-15P Adapter
LEDS ALARMS & SWITCHES	

LED Indicators	1 Link LED to confirm connection and indicate speed & 1 Status LED to indicate when the card is initialized
PHYSICAL	
Shipping Dimensions (HWD/in)	3.7 x 7.68 x 6.3
Shipping Dimensions (HWD/cm)	9.4 x 19.5 x 16
Shipping weight (lbs)	1.98
Shipping weight (kg)	.90
Unit Dimensions (HWD/in)	3.18 x 7.6 x 14.7
Unit Dimensions (HWD/cm)	9.4 x 19.5 x 16
Unit weight (lbs)	.71
Unit weight (kg)	.32
Material of construction	Sheet Metal
Color	Black
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
SRCOOL12K	Portable Air Conditioning Unit for IT Equipment in Server Rooms and Wiring Closets	1
SRXCOOL12K	230V, Self-Contained Portable Air Conditioning Unit	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5525.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.