



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: N422-03M

3M (10-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC)

Highlights



- 3 Meter LC/ST Mode Conditioning Cable
- 62.5/125 and 8.3/125
- Run 1000Base-LX Gigabit Ethernet over MMF by offsetting signal loss
- IEEE 802.3z Gigabit Ethernet Compliant

Description

Tripp Lites Mode Conditioning Cables are designed for use in Gigabit Ethernet 1000BASE-LX applications. They are fully compliant with IEEE 802.3z application standards. Mode Conditioning Cables are needed in applications where new high-speed Gigabit 1000BASE-LX routers and switches are being deployed into existing multimode plants. The need for this patch cord is due to the single-mode launch nature of the -LX or long-wave (1300 nm) transceiver modules used for Gigabit Ethernet. Launching a single-mode laser into the center of a multimode fiber can cause multiple signals to be generated that confuses the receiver at the other end of the fiber. These multiple signals, caused by Differential Mode Delay (DMD) effects, severely limit the cable distance lengths for operating Gigabit Ethernet. A mode conditioning patch cord eliminates these multiple signals by allowing the single-mode launch to be offset away from the center of a multimode fiber.

Applications

- Use when connecting a LX type fiber transceiver (Singlemode light) to a Multimode backbone

Package Includes

- 3 Meter LC/ST Mode Conditioning Cable

Features

- Use Singlemode Transceivers on Multimode Fiber Backbones
- 62.5/125 and 8.3/125
- Offsets the Singlemode Laser launch from the center of a Multimode fiber
- Available in a variety of connector combinations

Specifications

OVERVIEW	
Intended Application	Computer Networking (Fiber)
INPUT	
Cable Length (m)	3
PHYSICAL	

Color	Orange & Yellow
Style	Fiber Optic
CONNECTIONS	
Connector A	 LC
Connector B	 ST
Number of Connectors	4
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Fiber Optic Cables & Adapters	N422-01M	1M (3-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC)	1
Fiber Optic Cables & Adapters	N422-02M	2M (6-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC)	1
Fiber Optic Cables & Adapters	N422-10M	10M (33-ft.) Fiber Optic Mode Conditioning Patch Cable (ST/LC)	1
Fiber Optic Cables & Adapters	N424-01M	1M (3-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/LC)	1
Fiber Optic Cables & Adapters	N424-04M	4M (13-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/LC)	1
Fiber Optic Cables & Adapters	N424-05M	5M (16-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/LC)	1
Fiber Optic Cables & Adapters	N426-02M	2M (6-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC)	1
Fiber Optic Cables & Adapters	N426-03M	3M (10-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC)	1
Fiber Optic Cables & Adapters	N426-05M	5M (16-ft.) Fiber Optic Mode Conditioning Patch Cable (SC/SC)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3514.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.