



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: P606-003

### 3-ft. IEEE 1284 AB Parallel Gold Cable (DB25M to Cen36M)



#### Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- IEEE 1284 cables' gold-plated connectors provide superior conductivity and support high-speed bi-directional printing

#### Description

Tripp Lite's 3-ft. IEEE 1284 A-B gold parallel printer cable connects computers with a DB25 female parallel port to parallel printers with a Centronics 36 female parallel port. It supports high-speed IEEE 1284 bi-directional communication. The cable features gold plated DB25 male/Cent36 male connectors and gold plated copper contacts for superior conductivity. It is manufactured from superior molded cable with integral strain relief and double shielding for maximum EMI/RFI protection. It contains low-capacitance, impedance matched, twisted-pair conductors that protect against cross-talk and other transmission problems. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

#### System Requirements

- Computers with a DB25 Female parallel port
- Parallel printers with a Centronics 36 Female parallel port with high-speed IEEE 1284 Bi-Directional communication (although not essential).

#### Package Includes

- 3ft IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M

#### Features

- Supports high-speed IEEE 1284 bi-directional communication (modes: standard compatible nibble byte ECP and EPP)
- Length: 3-ft. Connectors: DB25 male/Cent36 male
- Gold plated connectors and gold plated copper contacts offer superior conductivity
- Superior molded cable with integral strain relief and double shielding (foil and braid) for maximum EMI/RFI protection
- Low-capacitance impedance matched twisted-pair conductors protect against cross-talk and other transmission problems
- Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- Molded ends with easy-grip textured overmold
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

#### Specifications

OVERVIEW	
Intended Application	Connecting Peripherals

<b>INPUT</b>	
Cable Length (ft.)	3
<b>PHYSICAL</b>	
Color	Black
Style	Printer Cables
<b>CONNECTIONS</b>	
Connector A	 DB25 (MALE)
Connector B	 CENTRONICS 36 (MALE)

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Switches	<a href="#">P606-006</a>	6-ft. IEEE 1284 AB Parallel Gold Cable (DB25M to Cen36M)	-
Switches	<a href="#">P606-010</a>	10-ft. IEEE 1284 AB Parallel Gold Cable (DB25M to Cen36M)	-
Switches	<a href="#">B170-002-R</a>	IEEE Rev 2 Pos Autoswitch - 3xDB25F	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2289](http://www.tripplite.com/en/products/model.cfm?txtModelID=2289).

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.