


# Model #: S502-20N

# 20-inch (0.5M) Internal SAS Cable - 4-in-1 32Pin (SFF-8484) to 4 x 7pin Cable



## **Highlights**

- 32-pin SFF-8484 to 4 x 7-pin internal SAS cable
- Supports data rates of up to 3.0Gbs
- Straight backshell configuration
- 0.5 meter in length (20 inch)

## **Description**

Tripp Lite's 32-pin SFF-8484 to 4 x 7-pin internal SAS cable (Serial Attached SCSI) cable is ideal for connecting SAS controllers to individual SAS/SATA disk drives. High-performance cable provides differential pair signaling with less than 5ps/m in pair skew, improved EMI protection, and 3.0Gbs data rate with rates up to 6.0Gbs. Thinner, flexible cable enables more efficient routing, with improved airflow and thermal mechanics. Configuration of storage devices is simplified. Tripp Lite SAS assemblies are RoHS compliant and feature a

#### Applications

• SAS Host Bus Adapters (HBA) such as LSI Logic SAS3442X-R and SAS3442E-R, utilizing internal SFF-8484 mating connectors

## System Requirements

• SAS Host Bus Adapter and Backplane with SFF-8484 mating connector

## Package Includes

• 0.5-Meter ( 20 inch ) Internal SAS 4-in-1 SFF-8484 to 4 x 7pin Cable

## **Features**

- SFF-8484 to 4 x 7pin SAS Cable 0.5 meter ( 20inch )
- Supports data rates up to 3.0Gbs
- Thin, flexible cable for easy routing and increased airflow
- RoHS Compliant

## **Specifications**

OVERVIEW	
Intended Application	Connecting Drives
Model Type	Internal
INPUT	
Cable Length (m)	0.5

PHYSICAL	
Red	
scsi	
SFF-8484	
7 PIN SATA STRAIGHT (MALE)	
5	
Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4276.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.