

Model #: TLP404

4 outlets, 4-ft cord, 450 joules Protect It! Surge Suppressor



Highlights

- 4 outlets / 4-ft. cord
- 450 joule rating
- \$1000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Description

Tripp Lite's TLP404 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP404 offers 4 total outlets, 4 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 450 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 1 designated transformer plug outlet offers convenient protection of desktop computer equipment and accessories. \$1,000 Ultimate Lifetime Insurance (USA & Canada Only). PLUG/OUTLETS: Input: NEMA5-15P/Output: 4 NEMA5-15R/4-ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle) FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet SUPPRESSION: AC: 150V RMS Clamping/450 joules/500V UL1449 3rd Edition

Applications

• Ideal for any desktop, network or home computing application requiring AC line protection

Package Includes

- TLP404 surge suppressor
- Instruction manual with warranty information

Features

- 4 outlets
- 4-ft. cord
- Surge suppression rating: 450 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Diagnostic LED confirms surge protection status
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 2 total transformers
- Keyhole supports for wall mounting
- · Lighted power switch
- \$1,000 Ultimate Lifetime Insurance (USA and Canada Only)

Specifications

OVERVIEW

Outlet orientation Single row of 4 outlets INPUT Nominal Input Voltage(s) 120V AC supported Service 120V (110-125V) Service	Intended Application	Home/Office	
Output watts 1800 Circuit Breaker (amps) 15 Overload protection 15A resettable combo switch / circuit breaker Outlet quantity / type 4 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 2 transformers total INPUT Nominal input Voltage(s) Supported 120V AC Supported Recommended Electrical Service 120V (110-125V) Input corn length (R) 4 Input cord length (R) 4 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 2500 LEDS ALARMS & SWITCHES Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression response in response 1 ns Protection medes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Veriffed	OUTPUT		
Discription 15 15 15 15 15 15 15 1	Frequency compatibility	50 / 60 Hz	
Overload protection 15A resettable combo switch / circuit breaker Outlet quantity / type 4 NEMA 5-15R Transformer accommodation Single row of 4 outlets NUTT	Output watts	1800	
Outlet quantity / type 4 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 2 transformers total Outlet orientation Single row of 4 outlets INPUT Nominal input Voltage(s) 120V AC Recommended Electrical Service 120V (110-125V) Recommended Electrical Service NEMA 5-15P Input connection type NEMA 5-15P Input cord length (ft.) 4 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Buill-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time < 1 ns Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/D	Circuit Breaker (amps)	15	
Transformer accommodation Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 2 transformers total Outlet orientation Single row of 4 outlets INPUT Nominal Input Voltage(s) 120V AC Supported Services NEMA 5-15P Recommended Electrical Services NEMA 5-15P Input cornection type NEMA 5-15P Input cord length (ft.) 4 Input cord length (ft.) 1.2 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Verbilled Supports SUPPRESSION AC suppression joule rating 450 AC suppression joule rating 450 AC suppression response Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL 1449 let through rating 500V - UL Verified DATALINE SUPPRESSION Telephone/DSL Protection No Notwork (Ethernet) No Privation of the surge suppression No Robovork (Ethernet) Protection No Notwork (Ethernet) Privation of the surge suppression No Robovork (Ethernet) Protection of No Notwork (Ethernet) Protection of No No Privatical Notwork (Ethernet) Protection of No No Protection of No No Privatical Notwork (Ethernet) Protection of No No Privatical New York (Ethernet) Protection of No No Privatical New York (Ethernet) Protection of No No Privatical New York (Privatical New York (Privatical New York (Privatical New York (Privatical New York (Priva	Overload protection	15A resettable combo switch / circuit breaker	
Outlet orientation Single row of 4 outlets INPUT Nominal Input Voltage(s) 120V AC supported Service 120V (110-125V) Service	Outlet quantity / type	4 NEMA 5-15R	
Nominal Input Voltage(s) Supported Recommended Electrical Service NEMA 5-15P Input connection type NEMA 5-15P Input cord length (ft.) 4 Input cord length (m) 1.2 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response circuit suppression response includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL 1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) No No Network (Ethernet) No Protection Holds Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Cable (Coax) Protection No No Notework (Ethernet) No	Transformer accommodation		
Recommended Electrical Service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.) 4 Input cord length (ft.) 12 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response 1 foliudes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Notwork (Ethernet) Protection No Network (Ethernet) No Network (Ethernet) No Protection Protection Protection No Protection Protection No Protection Protection Protection No Protection Protection Protection No Protection	Outlet orientation	Single row of 4 outlets	
Recommended Electrical service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.)	INPUT		
Service Input connection type Input cord length (ft.) Input cord length (ft.) Input cord length (m) Input cord gauge, type It gauge, SJT Voltage compatibility (VAC) It20 Maximum Surge Amps It2500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Biagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) InSOV UL1449 let through rating DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection		120V AC	
Input cord length (ft.) 4 Input cord length (m) 1.2 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No		120V (110-125V)	
Input cord length (m) 1.2 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL	Input connection type	NEMA 5-15P	
Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time 150V UCL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection No PHYSICAL	Input cord length (ft.)	4	
Voltage compatibility (VAC) 120 Maximum Surge Amps 22500 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL 1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) No Pertoection Place of the first of the protection of the pr	Input cord length (m)	1.2	
Maximum Surge Amps LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL	Input cord gauge, type	14 gauge, SJT	
Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) No PHYSICAL	Voltage compatibility (VAC)	120	
Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 450 AC suppression response time 1 normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) No Physical	Maximum Surge Amps	22500	
Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating	LEDS ALARMS & SWITCHES		
SURGE / NOISE SUPPRESSION AC suppression joule rating	Switches	Combination AC circuit breaker and 2 position on/off power switch	
AC suppression joule rating AC suppression response time Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL	Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status	
AC suppression response time AC suppression response time	SURGE / NOISE SUPPRESSION		
Protection modes Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression Clamping voltage (RMS) 150V UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) No Protection No	AC suppression joule rating	450	
Clamping voltage (RMS) UL1449 let through rating DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection PHYSICAL	AC suppression response time	< 1 ns	
UL1449 let through rating 500V - UL Verified DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) No Protection No	Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) No Protection No	Clamping voltage (RMS)	150V	
Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL	UL1449 let through rating	500V - UL Verified	
Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL	DATALINE SURGE SUPPRESSION		
Network (Ethernet) Protection No PHYSICAL	Telephone/DSL Protection	No	
Protection PHYSICAL	Cable (Coax) Protection	No	
		No	
Shipping weight (lbs) 1.2	PHYSICAL		
	Shipping weight (lbs)	1.2	

Shipping weight (kg)	.45
Unit Dimensions (HWD/in)	1.2 x 1.85 x 8.1
Unit Dimensions (HWD/cm)	3 x 4.7 x 20.6
Shipping Dimensions (HWD/in)	7.72 x 3.74 x 1.02
Shipping Dimensions (HWD/cm)	19.6 x 9.5 x 2.6
Unit weight (lbs)	1
Unit weight (kg)	.45
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
Housing Color	Light Gray
Receptacle Color	Light Gray
AC line cord color	Light Gray
Style	Strip
Outlets center to center measurement	28.6mm
Keyhole slot center to center measurement	Distance between slots = 57.5mm; Distance between slot height = 26mm
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$1,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2631.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.