



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLP66NET

6-outlet, 6ft cord, 1080 joules, RJ45 protection - Protect It! Surge Suppressor



Highlights

- 6 outlets / 6ft cord
- 1080 joule rating
- Ethernet Surge protection
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Canada & Puerto Rico only)

Description

Tripp Lite's TLP66NET surge suppressor has 6 outlets, a 6-ft. cord and diagnostic LEDs. The unit has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft network cable included). \$25,000 [Ultimate Lifetime Insurance](#) (USA, Canada & Puerto Rico only).

Applications

Personal computers, modems, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals and more.

Package Includes

- TLP66NET
- 6ft. network cable
- Instruction manual with warranty information

Features

- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- Lifetime product warranty
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Canada & Puerto Rico only)

Specifications

| OVERVIEW | |
|----------------------|--------------------------------|
| Intended Application | Home/Office, Computer Networks |

| OUTPUT | |
|-----------------------------------|--|
| Frequency compatibility | 60 Hz |
| Output watts | 1800 |
| Output volt amp capacity (amps) | 15 |
| Overload protection | 15A resettable illuminated combo switch / circuit breaker |
| Outlet quantity / type | 6 NEMA 5-15R |
| Transformer accommodation | Supports 2 large transformer plug accessories without covering remaining outlets, accepts up to 4 transformers total |
| Outlet safety covers | 6 |
| Outlet orientation | Block style with two rows of 3 outlets |
| INPUT | |
| Recommended Electrical Service | 120V (110-125V) |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 6 |
| Input cord gauge, type | 14 gauge, SJT |
| Voltage compatibility (VAC) | 120 |
| LEDS ALARMS & SWITCHES | |
| Switches | Combination AC circuit breaker and 2-position red illuminated on/off power switch |
| Diagnostic LEDs | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION | |
| AC suppression joule rating | 1080 |
| AC suppression response time | < 1 ns |
| Protection modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| Clamping voltage (RMS) | 150 |
| UL1499 let through rating | 400v |
| EMI / RFI filtering | Up to 40 dB |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | Yes |
| PHYSICAL | |
| Shipping weight (lbs) | 1.97 |
| Unit Dimensions (HWD/in) | 1.5 x 4.23 x 8.29 |
| Shipping Dimensions (HWD/in) | 11.02 x 7.08 x 1.77 |

| | |
|---|--|
| Unit weight (lbs) | 1.32 |
| Material of construction | Plastic |
| Integrated keyhole mounting tabs | Keyhole mounting tabs enable wall mounting |
| Housing Color | Gray |
| AC line cord color | Gray |
| Style | Block |
| SPECIAL FEATURES | |
| Right-Angle Plug | No |
| CERTIFICATIONS | |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd Edition |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| Industry Canada (Communications) | Industry Canada |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product Warranty Period (U.S., Canada & Puerto Rico) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 Ultimate Lifetime Insurance |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4840.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.