Model #: PDUMH20

Metered PDU / Power Distribution Unit- Safe, reliable power distribution with digital current meter

Highlights

- 1U rackmount metered PDU
- Digital current monitoring display
- 12 rear-facing 5-15/20R outlets
- 15-ft cord with L5-20P twist-lock input plug and L5-20R to 5-20P straight-blade plug adapter
- 20-amp breaker
- Switchless design

Description

Tripp Lite's PDUMH20 AC power distribution unit offers a digital current monitor and provides 20 amps of 120 volt capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter, or 1U/0U rackmount installation. Uses only 1U of rack space when installed in any 19-inch rack, with the potential for zero U mounting in the cable management area of most rack enclosures. Built-in digital ammeter display offers continuous visual power consumption data for the entire PDU. Attractive rackmount housing with 12 rear-facing outlets measures only 4.5 inches in depth. Unfiltered electrical pass-through without a power switch makes the PDUMH20 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets, and more. Includes 12 rear-facing NEMA 5-15/20R outlets, 15-ft. AC power cord with L5-20P input plug. Comes wih 6-inch L5-20P-to-5-20P adapter, 20 amp breaker, TVSS grounding lug, and rugged all-metal rackmount case design.

Applications

- Multi-outlet power distribution unit with digital current monitoring is the ideal means of powering multiple loads in 19 inch rackmount, wall-mount, and under-counter applications such as internetworking, PC systems, telecommunications, audio visual, security, sound reinforcement, and more. Ideal distribution of alternate and sinewave UPS and generator power or commercially derived AC power to connected equipment.

Package Includes

- PDUMH20 Metered rackmount PDU
- Owner's manual with warranty information

Features

- 120V/20A Metered rackmount AC power distribution unit with 20 amp capacity and 12 AC receptacles
- Front panel digital current monitoring display shows power consumption of connected equipment
- Versatile all-metal rackmount cabinet with detachable mounting flanges allows wall-mount, under-counter, and 19-inch rackmount mounting in both 1U and zero U formats
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 NEMA 5-15/20R output receptacles accept common NEMA 5-15P and 5-20P equipment plugs
- 15 foot AC power cord with NEMA L5-20P plug connection and 6-inch L5-20R-to-5-20P input plug adapter
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 20 amp electrical capacity with circuit breaker

- 120 VAC, 50/60 Hz electrical compatibility

Specifications

OVERVIEW	
Model Type	Metered

SYSTEM OVERVIEW	
Voltage compatibility	120V

OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	120V
Overload protection	20A
Outlet quantity / type	12 NEMA 5-15/20R

INPUT	
Recommended Electrical Service	120V
Maximum input amps	20A
Input connection type	NEMA L5-20P with NEMA 5-20P plug adapter
Input cord length (ft.)	15 feet

LEDS ALARMS & SWITCHES	
Front panel LEDs	Digital LED current meter

PHYSICAL	
Shipping weight (lbs)	3.6
Shipping weight (kg)	1.6
Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 4.5
Unit Dimensions (HWD/cm)	4.45 x 44.5 x 11.4
Shipping Dimensions (HWD/in)	2.25 x 20.5 x 10
Shipping Dimensions (HWD/cm)	5.7 x 52.1 x 25.4
Unit weight (lbs)	3
Unit weight (kg)	1.4
Material of construction	Sheet Metal
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
Form factors supported	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation

SPECIAL FEATURES	
Appearance	All black color scheme
TVSS grounding	Rear grounding lug

CERTIFICATIONS	
Certifications	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant

WARRANTY

Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	P007-002	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	P007-006	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	P007-010	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	P010-012	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	-
Power Cables	P012-006	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	-
Power Cables	P022-001	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	-
Power Cables	P023-001	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	-
Power Cables	P034-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	-
Power Cables	P043-002	2-ft. 10AWG Heavy Duty Power Cord with 20 AMP Breaker, (NEMA L5-30P to NEMA L5-20R)	-
Power Cables	P049-010	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at

www.tripplite.com/en/products/model.cfm?txtModelID=3867.