

Model Number: ISOBAR 4

Nominal Voltage/Frequency	120V 50/60Hz
Outlets	4
Input Plug Type	NEMA 5-15P
90 Degree Angle Plug	Yes
Cord Length	6 ft.
On/Off Power Switch	Lighted 2 position rocker
Joule Rating	2200
Maximum Surge Current (Amps)	85000.0
UL 1449 (Rev. '98) Rating	330 Volts
Protection Modes	Line to Neutral, Line to Ground and Neutral to Ground
IEEE 587 Category A Let Through Rating (NM)	< 35V
Clamping Voltage	140 Volts RMS
Response Time (CM/NM)	NM=0 ns. CM = < 1 ns.
Isolated Filter Banks	2
Housing Construction Material	Heavy Gauge Aluminum
Unit Dimensions (inches)	2.5 x 6 x 3.5
Format	Surge suppression strip with duplex outlet layout
Keyhole Supports for Mounting	Yes
Overload Protection	12 amp resettable circuit breaker
Line Noise Filtering Rating	UL1283
Temporary Power Tap Rating	UL1363
Canadian Standards	cUL
Immunity	IEEE 587 Cat. A + B
Warranty (US/Canada)	
Warranty Duration	Lifetime
Replacement Duration	Lifetime
High Speed Modem/Fax Protection	NA