Null Modem Serial RS232 Cable (DB9 to DB25 F/M) 6-ft.

MODEL NUMBER: **P456-006**

Highlights

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

System Requirements

- Two serial devices (one with a DB25 Male connector and the Other with a DB9 Female connector) requiring a null modem (cross-wired) configuration.

Package Includes

- 6-ft. Null Modem Gold Cable DB9F to DB25M

Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6ft cable has a DB9 female connector on one end and a DB25 male connector on the other. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

Features

- DB9 female to DB25 male
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	NULL MODEM
INPUT	
Cable Length (ft.)	6
Cable Length (m)	1.83
UPC ASSIGNMENT	
Unit Carton UPC#	037332013354

PHYSICAL	
Color	Black
Style	Null Modem Cables
CONNECTIONS	
Connector A	DB9 (FEMALE)
Connector B	DB25 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Model Number	Description	Qty.
P404-006	6-ft. AT Serial Modem Gold Cable (DB25M to DB9F)	1
P450-006	6-ft. Null Modem Gold Cable (DB9 F/F)	1
P454-006	6-ft. Null Modem Gold Cable (DB9 F/M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at:

http://www.tripplite.com/sku/P456-006.