

External SAS Cable, 4 Lane - mini-SAS (SFF-8088) to 4xInfiniband (SFF-8470), 2M (6-ft.)

MODEL NUMBER: \$520-02M



Highlights

- Hi-Performance 2 Meter SAS
 External Cable
- Mini-SAS SFF-8088 (iSAS) to SFF-8470
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

 SAS Controllers, SAS Chassis, SAS/SATA Hard Drives

Package Includes

 2 Meter SAS External SFF-8088 to SFF-8470 Cable

Description

Tripp Lite's S520-02M External SAS Cable features "mini-SAS" SFF-8088 to SFF-8470 connectors with heavy- duty metal backshells. This 4-channel cable is constructed with a high-performance Infiniband cable, which features individually shielded parallel pairs, double EMI/RFI shielding and 6.0 Gigabytes per second performance. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- External SAS Cable, Mini-SAS SFF-8088 (iSAS) to SFF-8470 2 Meter
- Made with High-Performance Infiniband Cable
- Supports data transfer rates from 3.0 up to 6.0 gigabytes per second
- SFF-8470 thumbscrew type connector and SFF-8088 connector in die cast zinc housing for durability
- · RoHS compliant
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
Intended Application	Connecting Drives	
Cable Type	SAS	
Model Type	External	
INPUT		
Cable Length (ft.)	6	
Cable Length (m)	1.83	





UPC ASSIGNMENT		
Unit Carton UPC#	037332151957	
PHYSICAL		
Color	Black	
Style	Serial Attached SCSI (SAS)	
CONNECTIONS		
Connector A	SFF-8088	
Connector B	SFF-8470	
Number of Connectors	2	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.