

## 6-outlet, 6-ft cord, 1080 joules, RJ45 protection - Protect It! Surge Suppressor

MODEL NUMBER: TLP66NET



### Highlights

- 6 outlets / 6-ft cord
- 1080 joule rating
- Ethernet surge protection
- \$25,000 Ultimate Lifetime Insurance (USA, Canada & Puerto Rico only)

### Applications

Personal computers, modems, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals and more.

### Package Includes

- TLP66NET
- 6-ft. network cable
- Instruction manual with warranty information

### Description

Tripp Lite's TLP66NET surge suppressor has 6 outlets, a 6-ft. cord and diagnostic LEDs. The unit has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6-ft network cable included). \$25,000 Ultimate Lifetime Insurance (USA, Canada & Puerto Rico only).

### Features

- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$25,000 Ultimate Lifetime Insurance (USA, Canada & Puerto Rico only)

## Specifications

OVERVIEW	
Intended Application	Home/Office, Computer Networks
OUTPUT	
Frequency compatibility	60 Hz



Output watts	1800
Circuit Breaker (amps)	15
Overload protection	15A resettable illuminated combo switch / circuit breaker
Outlet quantity / type	6 NEMA 5-15R
Transformer accommodation	Supports 2 large transformer plug accessories without covering remaining outlets, accepts up to 4 transformers total
Outlet safety covers	6
Outlet orientation	Block style with two rows of 3 outlets
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input cord length (ft.)	6
Input cord length (m)	1.83
Input cord gauge, type	14 gauge, SJT
Voltage compatibility (VAC)	120
Maximum Surge Amps	72000
<b>LEDS ALARMS &amp; SWITCHES</b>	
Switches	Combination AC circuit breaker and 2-position red illuminated on/off power switch
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
<b>SURGE / NOISE SUPPRESSION</b>	
AC suppression joule rating	1080
AC suppression response time	< 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Clamping voltage (RMS)	150
UL1449 let through rating	400v
EMI / RFI filtering	Up to 40 dB
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	Yes
<b>PHYSICAL</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

Shipping Dimensions (HWD/in)	11.02 x 7.08 x 1.77
Shipping Dimensions (HWD/cm)	27.99 x 17.98 x 4.50
Shipping weight (lbs)	1.97
Shipping weight (kg)	0.89
Unit Dimensions (HWD/in)	1.5 x 4.23 x 8.29
Unit Dimensions (HWD/cm)	3.81 x 10.74 x 21.06
Unit weight (lbs)	1.32
Unit weight (kg)	0.60
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
Housing Color	Light Gray
Receptacle Color	Dark Gray
AC line cord color	Light Gray
Style	Block
Outlets center to center measurement	Distance between standard outlets = 28.5; Distance between standard outlet and transformer outlet = 48.5mm
Keyhole slot center to center measurement	119mm
<b>SPECIAL FEATURES</b>	
Right-Angle Plug	No
<b>CERTIFICATIONS</b>	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 <a href="#">Ultimate Lifetime Insurance</a>

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.