

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

6-outlet, 6-ft cord, 1440 joules, Tel/Modem protection, Under-Monitor Protect It! Surge Suppressor

MODEL NUMBER: TMC-6



Highlights

- 6 outlets / 6-ft. cord
- 1440 joule rating
- Tel/modem surge protection
- Individual switches
- \$50,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Applications

 Ideal for PCs, notebook computers, peripherals and home electronics

Package Includes

- TOUCHMASTER COMPACT
 surge suppressor
- 6-ft. phone cord
- Instruction manual and warranty information

Description

Tripp Lite's TOUCHMASTER COMPACT surge suppressor offers complete AC and phone line surge suppression for comprehensive protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. RJ11 telephone line suppression jacks protect dialup and DSL modem lines, fax machines, cordless phones and more. TOUCHMASTER COMPACT offers 6 total outlets, 6 foot cord and LEDs to warn of power and wiring problems. Heavy grade AC suppression rated at 1440 joules shields equipment from surges and line noise. Attractive, slim design is perfect for use under desktop computer monitors or notebook computers. Individual switches offer power control over connected equipment. \$50,000 Ultimate Lifetime Insurance (USA, Puerto Rico and Canada only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 6 NEMA5-15R/6-ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle) FORMAT: Slim, compact design perfect for use under desktop monitors and notebook computers SUPPRESSION: AC: 150V RMS Clamping/1440 joules/400V UL1449 3rd Edition

Features

- 6 outlets
- 6-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment; 6-ft. telephone cord included
- Surge suppression rating: 1440 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Diagnostic LEDs confirm suppressor "protection present" (green), "grounded" (red) status and "power on" (green)
- Always-on outlet provides power for equipment you always need on, even when the "master" switch is off
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Allows for the computer to be controlled by the "master" switch and other outlets to be controlled either the "master" switch or corresponding switch on the



front panel

• \$50,000 Ultimate Lifetime Insurance (USA, Puerto Rico and Canada only) covers connected equipment

Specifications

OVERVIEW		
Intended Application	Home/Office	
Ουτρυτ		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Circuit Breaker (amps)	15	
Outlet quantity / type	6 NEMA 5-15R	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P input plug	
Input plug features	Space-saving right angle input plug	
Input cord length (ft.)	6	
Input cord length (m)	1.8	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
Maximum Surge Amps	84000	
LEDS ALARMS & SWITCHES		
Switches	Includes 5 front panel AC power switches. 4 switches control individual outlets and 1 serves as a main power switch that controls all but the one marked "unswitched" on the back panel	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	1440	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	150V	
UL1449 let through rating	400V - UL Verified	



DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (HWD/in)	2.25 x 12.5 x 14	
Shipping Dimensions (HWD/cm)	5.72 x 31.75 x 35.56	
Shipping weight (lbs)	3.4	
Shipping weight (kg)	1.54	
Unit Dimensions (HWD/in)	1.75 x 11.5 x 12	
Unit Dimensions (HWD/cm)	4.45 x 29.21 x 30.48	
Unit weight (lbs)	2.8	
Unit weight (kg)	1.27	
Material of construction	Plastic	
Housing Color	Black	
Receptacle Color	Black	
AC line cord color	Black	
Style	Under Monitor	
Form factors supported	Supports under monitor placement as a power control center for an entire PC system with peripherals	
SPECIAL FEATURES		
Right-Angle Plug	Yes	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000 Ultimate Lifetime Insurance	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.