

# VP2365-LED

23" 16:9 Widescreen HD LED Display

## Professionally Green Attitude



- > Full HD 1080p, 1920x1080 maximum resolution
- > 178 Degree Broad Viewing Angle  
What you see is what you get, VP2365-LED provides a wide viewing range for your professional observation.
- > Silver-free eIPS LED Production  
Viewsonic cares for our planet and you. The production of LED screens is completely silver-free and meets strict environmental and energy standards. LED Backlight Technology provides light source that's environment-friendly and energy-efficient. The production of LED panel is completely toxic-free and ecological. VP2365-LED is designed to use less energy and meet energy efficiency standards.
- > Advanced Displayport Interface  
The VESA certified Displayport Interface provides great functionality and connectivity with mainstream electronic devices. Enjoy multi-screen display and sound with only one Displayport cable.
- > Flexible Heights and Viewing Angles  
You can also move the screen up and down with the flexible base that allows 135mm height adjustment and 360 degree viewing angle.
- > Adjustable Pivot Knot Design for Viewing Flexibility  
Brand-new Pivot feature turns the screen 90 degree sideways. You can freely switch between landscape or portray display for different tasks, efficiency increases when the vision is right.
- > Great Output Integration by USB Hub  
Built-in USB hub provides connection to four or more output devices, making VP2365-LED the most powerful display of information.

Model Name	VP2365-LED	
LCD	Size Optimum Resolution Brightness Contrast Ratio Dynamic Contrast Ratio Viewing Angle Response Time Pixel Pitch Panel Surface Color Support	23" Widescreen 1920x1080 250 cd/m <sup>2</sup> (typ) 1000 :1 (Typ.) 20,000,000:1 178° (H), 178° (V) 6ms (Typ.) 0.2652(H) x 0.2652(V) mm Anti-Glare, Hard coating (3H) 16.7 M
INPUT	Analogue Sync Frequency	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync / Composite Sync / SOG Fh = 24 – 82 kHz ; Fv = 50 – 75 Hz
COMPATIBILITY	PC Mac	VGA up to 1920x1080 Non Interlaced Power Mac, up to 1920x1080
CONNECTOR	Analogue Digital Audio USB	VGA DVI-D NA USB x 4 (1 up stream and 4 down stream)
SPEAKER	Speaker	NA
POWER	Voltage Consumption ECO mode	AC 100-240V (Universal); 50/60Hz(Switch) 35W(typ)/45W(typ) w/USB 30W (Optimize)/40W(Optimize) w/USB , 24W (Conserve)/37W(Conserve) w/USB
ERGONOMICS	Tilt Swivel Pivot Height Adjust	20~-5 degrees 360 degrees 0~90 degrees 0~135 mm
OPERATING CONDITION	Temperature Humidity	32° F~104° F (0°C~40° C) 20~90% (no condensation)
DIMENSIONS	Physical (w/stand)	510 mm (W) x 415 mm (H) x 210 mm (D)
WEIGHT	Net (w/stand)	4.80 Kg
REGULATIONS		CB, TCO5.1, WEEE, RoHS, VISTA Premium/WinXP/Win 7,GS, CE , ErP, REACH, GOST-R+Hygienic, Ukraine, BSMI, PSB, C-TICK, SASO

For more product information, visit us at [ap.viewsonic.com](http://ap.viewsonic.com)

**ViewSonic®**  
See the difference™