

## 22" LED Display

Captivating Widescreen Picture Performance

**VA2232wm-LED**



Available for this model:  
**Privacy Filter  
Screen Protector**  
VSPF2150  
(Sold Separately)

Enjoy budget-friendly widescreen viewing, ideal for home or office. Featuring native 1680x1050 resolution, a high 10M:1 MEGA dynamic contrast ratio, and sRGB color calibration, the ViewSonic VA2232wm-LED 22" widescreen LED monitor offers crisp text, vibrant images and accurate color. Good for the environment as well as your budget, the mercury-free LED backlight noticeably reduces power costs compared to a traditional CCFL monitor, while the proprietary ViewSonic Eco-mode reduces power use up to an additional 35%\*.

**Key Features:**

1680x1050 resolution  
10M:1 MEGA Dynamic Contrast Ratio  
Energy-saving LED backlight and Eco-mode  
Built-in sRGB color correction technology  
VESA-compliant mount

**Designed for:**

Home  
Business  
Government  
Education

# 22" LED Display

**VA2232wm-LED**



## Specifications

<b>LCD Panel</b>	Type	22" Wide Color TFT Active Matrix LED
	Display Area	18.7" horizontal x 11.7" vertical; 22" diagonal
	Optimum Resolution	1680x1050
	Brightness	250 cd/m <sup>2</sup> (typ)
	Contrast Ratio	1000:1 static (typ), 10,000,000:1 dynamic
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	5ms (typ.)
	Backlight	White-light LED
	Backlight Life	40,000 hours (typ.)
	Aspect Ratio	16:10
	Panel Surface	Anti-glare, hard-coating (3H)
<b>INPUT</b>	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Digital	DVI (TMDS, 100 ohms)
	Audio	3.5mm mini stereo audio in
	Frequency	Fh: 24~82kHz, Fv: 50~75Hz
	Sync	H/V separated (TTL)
<b>AUDIO OUTPUT</b>	Speakers	2watt (x2)
<b>COMPATIBILITY</b>	PC	Up to 1680x1050 @ 60Hz (preferred)
	Mac®	PowerMax Up to 1680x1050
<b>CONNECTOR</b>	Analog	15-pin mini D-sub (VGA)
	Digital	DVI-D (with HDCP)
	Audio	3.5mm mini stereo audio in
	Power	Internal 50/60 Hz
<b>POWER</b>	Voltage	AC 100~240V (universal), 50/60 Hz
	Consumption	26W (typ)
		Optimize: 18W Conserve: 14W

## CONTROLS

CONTROLS		Basic OSD	Power, 1, down, up, 2 Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI), Audio adjust (Volume mute), Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off), Memory Recall
ERGONOMICS		Tilt	Forward 5°, Back 20°
OPERATING CONDITIONS	Temperature		32–104°F (0–40°C)
	Humidity		20–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand		20.1 x 16.4 x 7.7 in. / 510.7 x 416.2 x 195.4 mm
	Physical without stand		20.1 x 13.9 x 2.41 in. / 510.7 x 352.4 x 61.2 mm
	Packaging		22.4 x 19.6 x 5.7 in. / 570 x 498 x 145 mm
WEIGHT	Net with stand		8.6 lb. / 3.9 kg
	Net without stand		7.8 lb. / 3.5 kg
	Gross		12.3 lb. / 5.6 kg
WALL MOUNT			VESA® 100 x 100 mm
REGULATIONS			UL / cUL, FCC-B (including ICES003), CE, CB, TUV-S, NOM, BSMI, PSB, Energy Star, EPEAT Silver, RoHS
RECYCLE/DISPOSAL			Please dispose of in accordance with local, state or federal laws.
WARRANTY			Three-year limited warranty on parts, labor and backlight

## Optional Accessories

Desktop Display Wall Mount Kit .....	LCD-WMK-001
DVI-D to DVI-D Cable, 6FT .....	CB-00008187
DisplayPort to DVI Adapter.....	LCD-CABLE-001

## What's in the box?

VA2232wm-LED Display, power cable, VGA video cable, audio cable, ViewSonic Wizard CD, Quick Start Guide



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.