

28" Full HD Ergonomic LED Monitor with Integrated Client Endpoint Mount

Stunning Color Performance with SuperClear® Pro MVA Technology

VG2847Smh



Featuring a VDI friendly design that provides for easy mounting of client devices, the ViewSonic® VG2847Smh is a 28" monitor ideal for the enterprise and VDI environments. This monitor features full ergonomic functionality including tilt, swivel, pivot, and height adjustments for maximum comfort and enhanced productivity. In addition, VDI client endpoints can be easily attached to the monitor's integrated client mount, saving desktop space without interfering with ergonomic functionality. The VG2847Smh also delivers exceptional front of screen performance with 1920x1080 resolution, SuperClear® Pro MVA technology, and true 8-bit color, providing sharp, crisp, and consistent image performance at wide viewing angles.

Key Features:

SuperClear® Pro MVA technology for richer colors, better color gradients, and sharper images

Integrated client mount, as well as ergonomic tilt, swivel, pivot, and height-adjustable design for maximum comfort and productivity

Future-proof DisplayPort, HDMI and VGA inputs

Exclusive ViewMode technology delivers superior color rendering and intuitive settings

Flicker-Free and Blue Light Filter technology provide more comfortable viewing

Designed for:

Business

Government

Education

28" Full HD Ergonomic LED Monitor with Integrated Client Endpoint Mount

VG2847Smh



Specifications

LCD PANEL	Type	Color a-Si Active Matrix TFT LCD
	Display Area	24.4" horizontal x 13.4" vertical; 28.0" diagonal
	Optimum Resolution	1920x1080
	Brightness	300 cd/m ² (typ.)
	Contrast Ratio	3,000:1 (typ.)
	Dynamic Contrast Ratio	20,000,000:1
	Viewing Angles	176° horizontal, 176° vertical
	Colors	16.7M (true 8-bit)
	Response Time	6.5ms (GTG)
	Backlight	White-light LED
	Backlight Life	40,000 hours (min.)
	Panel Surface	Anti-glare, hard-coating (3H)
VIDEO INPUT	Digital	VGA, DisplayPort, HDMI
	Frequency	Fh: 15~82kHz, Fv: 24~75Hz
	Sync	Separate Sync, Composite Sync, Sync on Green
AUDIO OUTPUT	Speakers	2-watt (x2)
COMPATIBILITY	PC	Up to 1920x1080 non-interlaced
	Mac®	Up to 1920x1080
CONNECTOR	Video In	VGA, DisplayPort, HDMI
	Audio In	3.5mm mini jack
	Audio Out	3.5mm mini jack
	USB Hub	USB 2.0 (x2), USB upstream
	Power	External power adapter
CONTROLS	Front Panel Buttons	Power, 1, Up, Down, 2
	OSD	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

ERGONOMICS	Tilt	Forward 5° / Back 37°
	Swivel	340°
	Rotation	90°
	Height	0-135mm
POWER	Voltage	AC 100-240V (universal), 50 / 60Hz
	Consumption	35W (typ.) / 50W (max.)
	Optimize	28W (typ.)
	Conserve	24W (typ.)
OPERATING CONDITIONS	Temperature	32-104° F (0-40° C)
	Humidity	10-90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand	26.0 x 19.0 x 10.5 in. / 659.7 x 483.4 x 266mm
	Physical without Stand	26.0 x 15.4 x 1.9 in. / 659.7 x 391.0 x 49.3 mm
	Packaging	7.7 x 19.4 x 29.2 in. / 196 x 493 x 742 mm
WEIGHT	Net with Stand	16.3 lb. / 7.4 kg
	Net without Stand	10.6 lb. / 4.8 kg
	Gross	21.8 lb. / 9.9 kg
WALL MOUNT	VESA	100 x 100 mm
REGULATIONS		WEEE, WHQL, cULus, FCC, ENERGY STAR, EPEAT Gold
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state, or federal laws
WARRANTY		Three-year limited warranty on parts, labor and backlight

Optional Accessories

ViewSonic HDMI male to DVI male cable 1.8 meter	CB-00008948
Mini DisplayPort cable, 1.8m	CB-00010958
DisplayPort cable Male to Male 9.2m 28AWG	CB-00010684
DisplayPort cable.....	CB-00010555
DisplayPort to DVI Adapter.....	LCD-CABLE-001

What's in the box?

VG2847Smh monitor, Power cable, VGA cable, DisplayPort cable, Quick Start Guide, ViewSonic Wizard CD (User Guide)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.