

LASYSTEMS - Brusselsesteenweg 208 - 1730 Asse - Belgium

Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

WatchGuard XTM 33-W (WG033551)

XTM 33-W - 850 Mbps, 802.11b/g/n, 5x Gigabit Ethernet, USB, Serial, PPPoE, VLAN, QoS, Red



Introducing the WatchGuard XTM 3 Series! The newest member of the XTM family is a powerhouse performer for small businesses that want next-generation security features and fast firewall/VPN throughput at a small-business price.

The XTM 3 Series appliances include a suite of flexible management tools to give small businesses the tools they need to stay on top of network activity. They also include the Pro version of Fireware XTM operating system for advanced networking features, including VLAN support, multi-WAN load balancing, and dynamic routing. Real-time monitoring and rich reporting are included at no extra cost.

Keep traffic moving

The XTM 3 Series provides up to 1.4 Gbps firewall throughput, 240 Mbps VPN throughput, and up to seven 1-Gigabit Ethernet ports to support high-speed LAN backbone infrastructures and gigabit WAN connections.

Layer on protection

WatchGuard offers six security subscriptions for its next-generation XTM 3 Series solution, so businesses can build up protection where they need it most. Subscriptions can be purchased individually or bundled together for even greater savings.

Wireless security with guest access

Everyone loves wireless. With dual-band 802.11/n, the XTM 33-W model delivers reliable wireless connectivity while allowing you to provide controlled Internet access to guest users without compromising security.

Application Control

Control the use of Web 2.0 and other applications on your network for tighter security, better use of bandwidth, and greater productivity.

VPN setup in seconds

Nothing could be easier than our drag-and-drop Branch Office VPN setup - three clicks and your remote office is connected.

3 ways to manage your appliance

Choose to use the management tool that suits your work style and the task at hand. Options include our feature-rich intuitive centralized console, a command line interface, or web UI for access from anywhere, anytime.

Fireware XTM Pro included

The Pro version of our Fireware XTM OS is included with purchase for advanced networking features like policy-based routing, dynamic routing, multi-WAN load balancing, and VLAN support.

Remote connectivity options

Includes SSL and IPSec VPN for flexibility in remote access, with support for Apple iOS devices such as the iPhone, iPad, and IPod touch.

Reporting made easy

Monitoring and reporting tools, included at no extra cost, support industry and regulatory compliance with drill-down functions that make it easy to pinpoint specific activities.

Faster, safe web surfing

Add a simple subscription to Reputation Enabled Defense to your XTM solution and your organization will have faster web performance and even stronger security - with no additional hardware to buy.

Green security

Our firewalls are designed with efficiency in mind, consuming very little energy. Compare our power consumption to other security products and see how WatchGuard can make your data center more energy efficient. Green up your network with WatchGuard.

Main specifications:

Data transmission Firewall throughput: VPN throughput: IPS/IDS throughput: Branch Office VPN: Mobile VPN IPSec: Mobile VPN SSL:	850 Mbit/s 100 Mbit/s 328 Mbit/s 50 5 55
Networking Wi-Fi: Wi-Fi standards: Wi-Fi data rate (max): Networking standards: Number of users: Number of VLANs: DHCP server: DHCP client: Quality of Service (QoS) support:	Y 802.11b,802.11g,802.11n 300 Mbit/s IEEE 802.11b,IEEE 802.11g,IEEE 802.11n,IEEE 802.3,IEEE 802.3ab,IEEE 802.3ad,IEEE 802.3u 500 user(s) 50 Y Y Y
Ports & interfaces Connectivity technology: USB 2.0 ports quantity: Ethernet LAN (RJ-45) ports: Serial ports quantity:	Wired & Wireless 1 5 1
Protocols Management protocols: Supported network protocols: Routing protocols:	SNMP, CLI HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3 IP
Security Security algorithms: Firewall security:	128-bit AES,256-bit AES,3DES,DES,MD5,WEP,WPA,WPA2 ICSA, CC EAL4+ FIPS 140-2
Management features LED indicators: Management platform: Web-based management:	Y WSM Y
Power AC input voltage: Power consumption (typical):	100-240 V 24 W
Performance Concurrent connections: Antennas quantity: Certification:	40000 3 WEEE, RoHS, REACH
Design Rack mounting:	Ν
Weight & dimensions Dimensions (WxDxH):	197 x 273 x 127 mm
Packaging content Bundled software:	Fireware XTM
Other features	

Safety:

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.